



**ANTIGRAFFITI COATING (component A) - Two component
polyurethane coating (COMPONENT A)
24-056**

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** ANTIGRAFFITI COATING (component A) - Two component polyurethane coating (COMPONENT A)
24-056
Saturated polyester resin (Viscosity 3000 cP at 20°C)
- CAS: Non-applicable
EC: Non-applicable
Index: Non-applicable
REACH: Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Surface treatment. For professional user/industrial user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Evochem S.A.
Tzaverdella Place
133 41 Phili - Attica - Greece
Phone.: 0030 210 5590460 , 0030 210 5590155 - Fax: 0030 210 6254737 , 0030 210 5590244
info@evochem.gr
http://www.evochem.gr
- 1.4 Emergency telephone number:** National Poisoning Center 2107793777

SECTION 2: HAZARDS IDENTIFICATION **

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Flam. Liq. 3: Flammable liquids, Category 3, H226
Skin Irrit. 2: Skin irritation, Category 2, H315
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Warning
-  
- Hazard statements:**
Flam. Liq. 3: H226 - Flammable liquid and vapour
Skin Irrit. 2: H315 - Causes skin irritation
STOT SE 3: H336 - May cause drowsiness or dizziness
- Precautionary statements:**
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280: Wear protective gloves/protective clothing/eye protection/face protection
P302+P352: IF ON SKIN: Wash with plenty of water
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
P403+P233: Store in a well-ventilated place. Keep container tightly closed
P403+P235: Store in a well-ventilated place. Keep cool
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively
- Supplementary information:**
EUH066: Repeated exposure may cause skin dryness or cracking
- Substances that contribute to the classification**

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**ANTIGRAFFITI COATING (component A) - Two component
polyurethane coating (COMPONENT A)
24-056**
SECTION 2: HAZARDS IDENTIFICATION ** (continued)

N-butyl acetate (CAS: 123-86-4)

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **
3.1 Substance:

Chemical description: Two part polyurethane resin system

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: Non-applicable EC: Non-applicable Index: Non-applicable REACH Non-applicable	Saturated polyester resin (Viscosity 3000 cP at 20°C)⁽¹⁾	Not classified	19 - <24 %
	Regulation 1272/2008		
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH 01-2119488216-32-XXX	Xylene⁽²⁾	ATP CLP00 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	19 - <24 %
	Regulation 1272/2008		
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH 01-2119485493-29-XXX	N-butyl acetate⁽²⁾	ATP CLP00 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	19 - <24 %
	Regulation 1272/2008		
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH 01-2119475791-29-XXX	2-methoxy-1-methylethyl acetate⁽³⁾	ATP ATP01 Flam. Liq. 3: H226 - Warning	2,4 - <4,9 %
	Regulation 1272/2008		
CAS: 141-78-6 EC: 205-500-4 Index: 607-022-00-5 REACH 01-2119475103-46-XXX	Ethyl acetate⁽³⁾	ATP CLP00 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	0,24 - <0,9 %
	Regulation 1272/2008		
CAS: 77-58-7 EC: 201-039-8 Index: 050-030-00-3 REACH 01-2119496068-27-XXX	Dibutyltin Dilaurate⁽³⁾	Self-classified Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Muta. 2: H341; Repr. 1B: H360; Skin Corr. 1C: H314; Skin Sens. 1: H317; STOT RE 1: H372; STOT SE 1: H370 - Danger	<0,09 %
	Regulation 1272/2008		

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

⁽²⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

⁽³⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

3.2 Mixture:

Non-applicable

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES
4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

- CONTINUED ON NEXT PAGE -

**ANTIGRAFFITI COATING (component A) - Two component
polyurethane coating (COMPONENT A)
24-056****SECTION 4: FIRST AID MEASURES (continued)**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

- CONTINUED ON NEXT PAGE -

ANTIGRAFFITI COATING (component A) - Two component polyurethane coating (COMPONENT A) 24-056

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
Maximum Temp.: 35 °C
Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	Environmental limits		
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m ³
	IOELV (STEL)	100 ppm	442 mg/m ³
	Year	2018	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	IOELV (8h)	50 ppm	275 mg/m ³
	IOELV (STEL)	100 ppm	550 mg/m ³
	Year	2018	
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	IOELV (8h)	200 ppm	734 mg/m ³
	IOELV (STEL)	400 ppm	1468 mg/m ³
	Year	2018	
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	IOELV (8h)		
	IOELV (STEL)		
	Year	2018	

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	289 mg/m ³	289 mg/m ³	77 mg/m ³	Non-applicable

- CONTINUED ON NEXT PAGE -

ANTIGRAFFITI COATING (component A) - Two component polyurethane coating (COMPONENT A)
24-056

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	960 mg/m ³	960 mg/m ³	480 mg/m ³	480 mg/m ³
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	153,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	275 mg/m ³	Non-applicable
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
	Inhalation	1468 mg/m ³	1468 mg/m ³	734 mg/m ³	734 mg/m ³
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	1 mg/kg	Non-applicable	0,2 mg/kg	Non-applicable
	Inhalation	0,07 mg/m ³	Non-applicable	0,01 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14,8 mg/m ³	Non-applicable
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	859,7 mg/m ³	859,7 mg/m ³	102,34 mg/m ³	102,34 mg/m ³
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	1,67 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	54,8 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	Non-applicable
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
	Inhalation	734 mg/m ³	734 mg/m ³	367 mg/m ³	367 mg/m ³
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	Oral	0,01 mg/kg	Non-applicable	0,002 mg/kg	Non-applicable
	Dermal	0,5 mg/kg	Non-applicable	0,08 mg/kg	Non-applicable
	Inhalation	0,02 mg/m ³	Non-applicable	0,003 mg/m ³	Non-applicable

PNEC:

Identification				
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L
	Soil	0,0903 mg/kg	Marine water	0,018 mg/L
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0981 mg/kg
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L
	Soil	0,29 mg/kg	Marine water	0,0635 mg/L
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	STP	650 mg/L	Fresh water	0,24 mg/L
	Soil	0,148 mg/kg	Marine water	0,024 mg/L
	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg
	Oral	200 g/kg	Sediment (Marine water)	0,115 mg/kg

- CONTINUED ON NEXT PAGE -

ANTIGRAFFITI COATING (component A) - Two component polyurethane coating (COMPONENT A)
24-056

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Dibutyltin Dilaurate	STP	100 mg/L	Fresh water	0,000463 mg/L
CAS: 77-58-7	Soil	Non-applicable	Marine water	0,0000463 mg/L
EC: 201-039-8	Intermittent	0,00463 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	0,2 g/kg	Sediment (Marine water)	Non-applicable

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

If product is used at the concentration dosing conditions specified in the relevant instructions for use (section 15), personal protective equipment described in section 8.2 for UNDILUTED products will not be required.

Safe handling recommendations for undiluted product:

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CE CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CE CAT III	EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face mask	CE CAT II	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CE CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CE CAT III	EN 13287:2008 EN ISO 20345:2011 EN 13832-1:2006	Replace boots at any sign of deterioration.

F.- Additional emergency measures

- CONTINUED ON NEXT PAGE -

ANTIGRAFFITI COATING (component A) - Two component polyurethane coating (COMPONENT A) 24-056

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 48,3 % weight
V.O.C. density at 20 °C: 478,57 kg/m³ (478,57 g/L)
Average carbon number: 6,94
Average molecular weight: 113,07 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 497,24 kg/m³ (497,24 g/L)
EU limit for the product (Cat. A.J): 500 g/L (2010)
Components: 24-008 - 4 % v/v ; 24-057 - 31,7 % v/v

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid
Appearance: Transparent
Colour: Not available
Odour: Not available
Odour threshold: Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 132 °C
Vapour pressure at 20 °C: 1046 Pa
Vapour pressure at 50 °C: 5269 Pa (5 kPa)
Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 991 kg/m³
Relative density at 20 °C: 0,991
Dynamic viscosity at 20 °C: Non-applicable *
Kinematic viscosity at 20 °C: Non-applicable *
Kinematic viscosity at 40 °C: Non-applicable *
Concentration: 995 - 1075 g/L (active ingredient)
pH: Non-applicable *
Vapour density at 20 °C: Non-applicable *
Partition coefficient n-octanol/water 20 °C: Non-applicable *
Solubility in water at 20 °C: Non-applicable *
Solubility properties: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**ANTIGRAFFITI COATING (component A) - Two component
polyurethane coating (COMPONENT A)
24-056**

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

Flammability:

Flash Point:	25 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	315 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

Explosive:

Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

9.2 Other information:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- CONTINUED ON NEXT PAGE -

**ANTIGRAFFITI COATING (component A) - Two component
polyurethane coating (COMPONENT A)
24-056**

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
- Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) - single exposure:
- Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- G- Specific target organ toxicity (STOT)-repeated exposure:
- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:
- Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	LD50 oral	4100 mg/kg	Rat
	LD50 dermal	20000 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	

- CONTINUED ON NEXT PAGE -

ANTIGRAFFITI COATING (component A) - Two component polyurethane coating (COMPONENT A)
24-056

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Dibutyltin Dilaurate	175 mg/kg	Non-applicable	Rat
CAS: 77-58-7	Non-applicable	Non-applicable	
EC: 201-039-8	Non-applicable	Non-applicable	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
	LC50	EC50		
Xylene CAS: 1330-20-7 EC: 215-535-7	13.5 mg/L (96 h)	3.4 mg/L (48 h)	Oncorhynchus mykiss	Fish
		10 mg/L (72 h)	Ceriodaphnia dubia	Crustacean
			Skeletonema costatum	Algae
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	62 mg/L (96 h)	73 mg/L (24 h)	Leuciscus idus	Fish
		675 mg/L (72 h)	Daphnia magna	Crustacean
			Scenedesmus subspicatus	Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	161 mg/L (96 h)	481 mg/L (48 h)	Pimephales promelas	Fish
		Non-applicable	Daphnia sp.	Crustacean
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	230 mg/L (96 h)	717 mg/L (48 h)	Pimephales promelas	Fish
		3300 mg/L (48 h)	Daphnia magna	Crustacean
			Scenedesmus subspicatus	Algae
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	0.1 - 1 mg/L (96 h)	0.1 - 1 mg/L		Fish
		0.1 - 1 mg/L		Crustacean
		0.1 - 1 mg/L		Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
	BOD5	COD	Concentration	Period
Xylene CAS: 1330-20-7 EC: 215-535-7	Non-applicable	Non-applicable	Non-applicable	28 days
	Non-applicable	Non-applicable	% Biodegradable	88 %
	Non-applicable	0.79	% Biodegradable	84 %
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Non-applicable	Non-applicable	Concentration	Non-applicable
	Non-applicable	Non-applicable	Period	5 days
	0.79	Non-applicable	% Biodegradable	84 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Non-applicable	Non-applicable	Concentration	785 mg/L
	Non-applicable	Non-applicable	Period	8 days
	Non-applicable	Non-applicable	% Biodegradable	100 %
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	1.36 g O2/g	1.69 g O2/g	Concentration	100 mg/L
	1.69 g O2/g	0.81	Period	14 days
	0.81	Non-applicable	% Biodegradable	83 %
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	0.00054 g O2/g	Non-applicable	Concentration	100 mg/L
	Non-applicable	Non-applicable	Period	28 days
	Non-applicable	Non-applicable	% Biodegradable	50 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
	BCF	Pow Log
Xylene CAS: 1330-20-7 EC: 215-535-7	9	2.77
	Low	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	4	1.78
	Low	

- CONTINUED ON NEXT PAGE -

**ANTIGRAFFITI COATING (component A) - Two component
polyurethane coating (COMPONENT A)
24-056**

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bioaccumulation potential	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF	1
	Pow Log	0.43
	Potential	Low
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	BCF	30
	Pow Log	0.73
	Potential	Moderate
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	BCF	31
	Pow Log	3.12
	Potential	Moderate

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Koc	59	Henry	13,58 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,324E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
	It is not possible to assign a specific code, as it depends on the intended use by the user	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP4 Irritant — skin irritation and eye damage, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION ****Transport of dangerous goods by land:**

With regard to ADR 2017 and RID 2017:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**ANTIGRAFFITI COATING (component A) - Two component
polyurethane coating (COMPONENT A)
24-056**

SECTION 14: TRANSPORT INFORMATION ** (continued)



- 14.1 UN number:** UN1993
14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Xylene)
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: III
14.5 Environmental hazards: No
14.6 Special precautions for user
 Special regulations: 274, 601, 640E
 Tunnel restriction code: D/E
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 38-16:



- 14.1 UN number:** UN1993
14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Xylene)
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: III
14.5 Environmental hazards: No
14.6 Special precautions for user
 Special regulations: 274, 223, 955
 EmS Codes: F-E, S-E
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2017:



- 14.1 UN number:** UN1993
14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Xylene)
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: III
14.5 Environmental hazards: No
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

** Changes with regards to the previous version

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
 Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
 Article 95, REGULATION (EU) No 528/2012: Non-applicable

- CONTINUED ON NEXT PAGE -

**ANTIGRAFFITI COATING (component A) - Two component
polyurethane coating (COMPONENT A)
24-056**

SECTION 15: REGULATORY INFORMATION (continued)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Contains Dibutyltin Dilaurate

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Relevant instructions for use:

Mix component A with component B thinning up to 5% with MERCOLA polyurethane solvent

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

- Removed substances
Toluene (108-88-3)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Pictograms
- Hazard statements
- Precautionary statements

TRANSPORT INFORMATION (SECTION 14):

- Packing group

Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness

H315: Causes skin irritation

H226: Flammable liquid and vapour

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Aquatic Acute 1: H400 - Very toxic to aquatic life

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects

Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Liq. 2: H225 - Highly flammable liquid and vapour

Flam. Liq. 3: H226 - Flammable liquid and vapour

Muta. 2: H341 - Suspected of causing genetic defects

Repr. 1B: H360 - May damage fertility or the unborn child

Skin Corr. 1C: H314 - Causes severe skin burns and eye damage

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure. (Oral)

STOT SE 1: H370 - Causes damage to organs

STOT SE 3: H336 - May cause drowsiness or dizziness

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**ANTIGRAFFITI COATING (component A) - Two component
polyurethane coating (COMPONENT A)
24-056****SECTION 16: OTHER INFORMATION ** (continued)****Principal bibliographical sources:**

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol–water partition coefficient

Koc: Partition coefficient of organic carbon

*** Changes with regards to the previous version*

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -