



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier: CL 12 FIREPLACE CLEANER 24-236
- **1.2** Relevant identified uses of the substance or mixture and uses advised against: Relevant uses: cleaner

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet: EVOCH

EVOCHEM S.A. Tzaverdella Place 133 41 PHILI , ATTICA - GREECE Phone.: 0030 210 5590460 , 0030 210 5590155 -Fax: 0030 210 6254737 , 0030 210 5590244 Email: info@evochem.gr; vmergoupis@evochem.gr; sales@evochem.gr

1.4 Emergency telephone number: National Poisoning Center 2107793777

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Eye Dam. 1: Serious eye damage, Category 1, H318 Skin Corr. 1B: Skin corrosion, Category 1B, H314

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:



Danger

Hazard statements:

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P264: Wash thoroughly after handling

P280: Wear protective gloves/protective clothing/eye protection/face protection

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P501: Dispose of contents/container according to the separated collection system used in your municipality

Supplementary information:

EUH208: Contains Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction

Substances that contribute to the classification

Sodium hydroxide

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Version: 1





SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Chemical description: Acid solution

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: Non-applicable EC: 939-625-7 Index: Non-applicable REACH 01-2119985168-23-XXX	Alkane C6-C8 (even numbered), 1-sulphonic acid, sodium salt 1 Self-classified Regulation 1272/2008 Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	4,9 - <9,9 %
CAS: 34590-94-8 EC: 252-104-2 Index: Non-applicable REACH 01-2119450011-60-XXX	Dipropylene Glycol Methyl Ether 2 Not classified Regulation 1272/2008 Image: Classified in the second seco	2,4 - <4,9 %
CAS: 1310-73-2 EC: 215-185-5 Index: 011-002-00-6 REACH 01-2119457892-27-XXX	Sodium hydroxide 1 ATP CLP00 Regulation 1272/2008 Skin Corr. 1A: H314 - Danger	2,4 - <4,9 %
CAS: 55965-84-9 EC: Non-applicable	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and ATP CLP00 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) 1	
Index: 613-167-00-5 REACH Non-applicable :	Regulation 1272/2008 Acute Tox. 3: H301+H311+H331; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	<0,09 %

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

² Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:





SECTION 5: FIREFIGHTING MEASURES (continued)

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:	5 °C
Maximum Temp.:	35 °C
Maximum time:	12 Months

B.- General conditions for storage

- CONTINUED ON NEXT PAGE -





SECTION 7: HANDLING AND STORAGE (continued)

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification Er			vironmental limits		
Dipropylene Glycol Methyl Ether	IOELV (8h)	50 ppm	308 mg/m ³		
CAS: 34590-94-8	IOELV (STEL)				
EC: 252-104-2	Year	2018			

DNEL (Workers):

		Short e	xposure	Long e	kposule
Identification		Systemic	Local	Systemic	Local
Dipropylene Glycol Methyl Ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 34590-94-8	Dermal	Non-applicable	Non-applicable	65 mg/kg	Non-applicable
EC: 252-104-2	Inhalation	Non-applicable	Non-applicable	310 mg/m ³	Non-applicable
Sodium hydroxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1310-73-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 215-185-5	Inhalation	Non-applicable	Non-applicable	Non-applicable	1 mg/m ³

DNEL (General population):

		Short e	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Dipropylene Glycol Methyl Ether	Oral	Non-applicable	Non-applicable	1,67 mg/kg	Non-applicable
CAS: 34590-94-8	Dermal	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
EC: 252-104-2	Inhalation	Non-applicable	Non-applicable	37,2 mg/m ³	Non-applicable
Sodium hydroxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1310-73-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 215-185-5	Inhalation	Non-applicable	Non-applicable	Non-applicable	1 mg/m ³

PNEC:

Identification				
Dipropylene Glycol Methyl Ether	STP	4168 mg/L	Fresh water	19 mg/L
CAS: 34590-94-8	Soil	2,74 mg/kg	Marine water	1,9 mg/L
EC: 252-104-2	Intermittent	190 mg/L	Sediment (Fresh water)	70,2 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,02 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands





Image: Mandatory hand protection minor risks Image: Construction of the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance reliability and has therefore to be checked prior to the application" D. Ocular and facial protection Perform of the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance reliability and has therefore to be checked prior to the application" D. Ocular and facial protection Perform of the product is a glasses against splash/projections. EN 166:2001 Clean daily and disinfect periodically at the manufacturer's instructions. Use if risk of splashing. E Body protection Perform of the period section Cen Standard Remarks More clothing Cen Standard Remarks Clean daily and disinfect periodically at the manufacturer's instructions. Use if risk of splashing. E Body protection Vork clothing Cen Standard Remarks More clothing Cen Standard Remarks Replace before any evidence of deteric periods of prolonged exposure to the professional/industrial users CE III is regional center with the regulations in users CE III is regional prolonged exposure to the professional/industrial users CE	Pictogram	PPE	Labelling	CEN Standard	Remarks
reliability and has therefore to be checked prior to the application" 2 Ocular and facial protection Petcogram Percent Per	,		CATI		Replace gloves in case of any sign of damag prolonged periods of exposure to the produ professional users/industrials, we recommend CE III gloves in line with standards EN 420 a 374.
- Ocular and facial protection Pictogram PPE Labelling CEN Standard Remarks Protection Panoramic glasses against splash/projections. EN 166:2001 Clean daily and disinfect periodically as the manufacturer's instructions. Use if risk of splashing. Protection obligatoria de la cara Panoramic glasses against splash/projections. EN 166:2001 Clean daily and disinfect periodically as the manufacturer's instructions. Use if risk of splashing. - Body protection Ptotogram PPE Labelling CEN Standard Replace before any evidence of deteric periodis of prolonged exposure to the periods of prolonged exposure to the periodis of prolonged exp	"As the product is				ial can not be predicted in advance with
Pictogram PPE Labelling CEN Standard Remarks Protection Panoramic glasses against splash/projections. Ex 150 4007:2012 Clean daily and disinfect periodically at the manufacturer's instructions. Use if risk of splashing. Protection Period control Ex 150 4007:2012 Clean daily and disinfect periodically at the manufacturer's instructions. Use if risk of splashing. Protection Protection Replace before any evidence of detection periods of prolonged exposure to the professional/industrial users CET II is re- in accordance with the regulations in 5229:2001. EX 150 633:2005. EX 150 EX 464:1994. Anti-slip work shoes CEX Entrol Replace before any evidence of detection periods of prolonged exposure to the professional/industrial users CE III is re- in accordance with the regulations in Ex y EN 13832-1	•		prior to the applic	ation"	
Paroramic glasses against splash/projections. EN 166:2001 EN ISO 4007:2012 Clean daily and disinfect periodically at the manufacturer's instructions. Use if risk of splashing. Body protection PPE Labelling CEN Standard Replace before any evidence of detroit professional/industrial users CE III is rec Body protection Work clothing CEN Standard Replace before any evidence of detroit professional/industrial users CE III is rec Additional emergency measures Energency measure Replace before any evidence of detroit periods of prolonged exposure to the p professional/industrial users CE III is rec Additional emergency measures Energency measure Standards Energency measure Standards Emergency measure Standards Energency measure Standards III is rec Introduct and its containers. NSI 2358-1 ISO 3864-1:2002 Energency measure Standards Intergency measure Standards Energency measure Standards Intergency controls: naccordance with the community legislation for the protection of the environment it is recommended to avoid environment for the product and its container. For additional information see subsection 7.1.D Iotalia organic compounds: ////////////////////////////////////			Labelling	CEN Standard	Pemarke
Splash/projections. Splash/projections. Splash/projections. EN ISO 4007:2012 the manufacturer's instructions. Use if risk of splashing. Body protection Sody protection EN ISO 4007:2012 the manufacturer's instructions. Use if risk of splashing. Body protection PPE Labelling CEN Standard Replace before any evidence of deteric periods of prolonged exposure to the professional/industrial users CE III is reclinated on accordance with the regulations in Environmental exposure to the professional/industrial users CE III is reclinated on accordance with the regulations in Environmental exposure controls: Additional emergency measures Emergency measure Standards Emergency measure Standards Imergency measure ANSI 2358-1 ISO 3864-1:2002 Events stations DIN 12 899 ISO 3864-1:2002 DIN 12 899 ISO 3864-1:2002 Intergency measure Ansi 2358-1 ISO 3864-1:2002 Events stations DIN 12 899 ISO 3864-1:2002 Intergency measure Ansi 2358-1 ISO 3864-1:2002 DIN 12 899 ISO 3864-1:2002 DIN 12 899 ISO 3864-1:2002 Intergency measure Ansi 2358-1 ISO 3864-1:2002 DIN 12 899 ISO 3864-1:2002 DIN 12 899 ISO 3864-1:2002 Intergency measure Ansi 2358-1 ISO 3864-1:2002 DIN 12 899 ISO 3864-1:2002 DIN 12 899 ISO 3864-1:2002 Intergency measure Anset 2458-	rictogram		Labening		
Pictogram PPE Labelling CEN Standard Remarks Work clothing Image: Centrol of the periods of prolonged exposure to the professional/industrial users CE III is reclared with the regulations in EN y EN 13832-1 - Additional emergency measures Emergency measure Standards Emergency measure Standards Image: Emergency shower ANSI Z358-1 ISO 3864-1:2002 Image: Exposure controls: Image: Exposure controls: accordance with the community legislation for the protection of the environment it is recommended to avoid environment both the product and its container. For additional information see subsection 7.1.D Image: Exposure control = 0.1.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.			CAT II		the manufacturer's instructions. Use if ther
Work clothing Replace before any evidence of deteric periods of prolonged exposure to the professional/industrial users CE III is necordance with the regulations in 6529:2001. EN ISO 6530:2005, EN ISO EN 464:1994. Anti-slip work shoes Image: Control ison of prolonged exposure to the professional/industrial users CE III is necordance with the regulations in escordance with the regulations in escordance with the regulations in EN y EN 13832-1 - Additional emergency measures Image: Control ison of prolonged exposure to the professional/industrial users CE III is recondance with the regulations in EN y EN 13832-1 - Additional emergency measures Image: Control ison of prolonged exposure to the professional/industrial users CE III is recondance with the regulations in EN y EN 13832-1 - Additional emergency measures Image: Control ison of prolonged exposure to the professional/industrial users CE III is recondance with the regulations in EN y EN 13832-1 - Additional emergency measures Image: Control ison of the protection of the environment it is recommended to avoid environment both the product and its container. For additional information see subsection 7.1.0 - Diatile organic compounds: Image: Control ison of the protection of the environment it is recommended to avoid environment both the product and its container. For additional information see subsection 7.1.0 - Diatile organic compounds: Image: Control ison of the protection of the environment it is recommended to avoid environment both the product and its container. For additional information see subsection 7.1.0 - Oc. (Supply): 1	- Body protection				
Anti-slip work shoes Energency measure Standards Additional emergency measures Energency measure Standards Additional emergency measures Energency measure Standards Image: Energency shower Iso 3864-1:2002 Eyewash stations Image: Energency shower Iso 2010/75/EU, this product has the following characteristics: accordance with the community legislation for the protection of the environment it is recommended to avoid environment both the product and its container. For additional information see subsection 7.1.D olatile organic compounds: Ith registration of the following characteristics: 0.C. (Supply): 10,87 % weight 0.C. density at 20 °C: 114,44 kg/m³ (114,44 g/L)	Pictogram	PPE	Labelling	CEN Standard	Remarks
errors Emergency measures Emergency measure Standards Image: Standards Emergency measure Standards Standards Standards Emergency measure Standards Standards Standards Emergency measure Standards Standards Standards Standards Standards Emergency measure Standards Standards		Anti-slip work choose	CATI	EN ISO 20247-2012	professional/industrial users CE III is recomm in accordance with the regulations in EN I 6529:2001, EN ISO 6530:2005, EN ISO 13688 EN 464:1994.
Emergency measure Standards Emergency measure Standards MNSI Z358-1 ISO 3864-1:2002 Image: Comparison of the standards DIN 12 899 ISO 3864-1:2002 Image: Comparison of the standards of the s		Anti-Sip work shoes	CAT II	EN 150 20547.2012	periods of prolonged exposure to the produ professional/industrial users CE III is recomm in accordance with the regulations in EN ISO
ANSI 2358-1 ISO 3864-1:2002 DIN 12 899 ISO 3864-1:2002 Invironmental exposure controls: In accordance with the community legislation for the protection of the environment it is recommended to avoid environment f both the product and its container. For additional information see subsection 7.1.D Volatile organic compounds: With regard to Directive 2010/75/EU, this product has the following characteristics: 0.0.C. (Supply): 10,87 % weight 0.0.C. density at 20 °C: 114,44 kg/m³ (114,44 g/L)	- Additional emerge	ncy measures			
ISO 3864-1:2002 ISO 3864-1:2002 ISO 3864-1:2002 ISO 3864-1:2002 ISO 3864-1:2002 ISO 3864-1:2002 Invironmental exposure controls: ISO 3864-1:2002 In accordance with the community legislation for the protection of the environment it is recommended to avoid environment foot the product and its container. For additional information see subsection 7.1.D ISO 3864-1:2002 Intersection of the product and its container. For additional information see subsection 7.1.D ISO 3864-1:2002 Intersection of the product and its container. For additional information see subsection 7.1.D ISO 3864-1:2002 Intersection of the product and its container. For additional information see subsection 7.1.D ISO 3864-1:2002 Intersection of the product and its container. For additional information see subsection 7.1.D ISO 3864-1:2002 Intersection of the product and its container. For additional information see subsection 7.1.D ISO 3864-1:2002 Intersection of the product and its container. For additional information see subsection 7.1.D ISO 3864-1:2002 Intersection of the product and its container. For additional information see subsection 7.1.D ISO 3864-1:2002 Intersection of the product and its container. For additional information see subsection 7.1.D ISO 3864-1:2002 Intersection of the product and its container. For additiner and the product andits container. For additiner andition and t	Emergency mea	asure S	tandards	Emergency meas	ure Standards
accordance with the community legislation for the protection of the environment it is recommended to avoid environment both the product and its container. For additional information see subsection 7.1.D olatile organic compounds: With regard to Directive 2010/75/EU, this product has the following characteristics: O.C. (Supply): 10,87 % weight O.C. density at 20 °C: 114,44 kg/m ³ (114,44 g/L)	Emergency sho	ISO 3			ISO 3864-1:2002
f both the product and its container. For additional information see subsection 7.1.D colatile organic compounds: /ith regard to Directive 2010/75/EU, this product has the following characteristics: .O.C. (Supply): 10,87 % weight .O.C. density at 20 °C: 114,44 kg/m³ (114,44 g/L)	nvironmental exp	osure controls:			
Volatile organic compounds: Vith regard to Directive 2010/75/EU, this product has the following characteristics: V.O.C. (Supply): 10,87 % weight V.O.C. density at 20 °C: 114,44 kg/m³ (114,44 g/L)					recommended to avoid environmental s
/ith regard to Directive 2010/75/EU, this product has the following characteristics:.O.C. (Supply):10,87 % weight.O.C. density at 20 °C:114,44 kg/m³ (114,44 g/L)	•		ional information	see subsection 7.1.D	
Y.O.C. (Supply): 10,87 % weight Y.O.C. density at 20 °C: 114,44 kg/m³ (114,44 g/L)	-				
.O.C. density at 20 °C: 114,44 kg/m ³ (114,44 g/L)	-			ing characteristics:	
verage carbon number: 4,16			(114,44 g/L)		
	verage molecular we	ight: 95,27 g/mol			

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and cl	nemical properties:	
For complete information see the product	t datasheet.	
Appearance:		
Physical state at 20 °C:	Liquid	
Appearance:	Not available	
Colour:	Not available	
Odour:	Not available	
*Not relevant due to the nature of the product, no	t providing information property of its hazards.	

- CONTINUED ON NEXT PAGE -





SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES	S (continued)
Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	102 °C
Vapour pressure at 20 °C:	2511 Pa
Vapour pressure at 50 °C:	12886 Pa (13 kPa)
Evaporation rate at 20 °C:	Non-applicable *
Product description:	
Density at 20 °C:	1053 kg/m³
Relative density at 20 °C:	1,053
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Flammability:	
Flash Point:	65 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	189 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *
Explosive:	
Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *
9.2 Other information:	
Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *
*Not relevant due to the nature of the product, not providing infor	mation property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:



SECTION 10: STABILITY AND REACTIVITY (continued)



CL 12 FIREPLACE CLEANER 24-236

Shock and friction Contact with ai Increase in temperature Sunlight Humidit Not applicable Not applicable Not applicable Not applicable Not applicable 10.5 Incompatible materials: Combustive mate Avoid strong acids Not applicable Precaution Not applicable Not applicable 10.6 Hazardous decomposition products: See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds. SECTION 11: TOXICOLOGICAL INFORMATION 11.1 Information on toxicological effects: The experimental information related to the toxicological properties of the product itself is not available Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health . **Dangerous health implications:** In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure: A.- Ingestion (acute effect): Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3. Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2. B- Inhalation (acute effect): Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3. Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract C- Contact with the skin and the eyes (acute effect): Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2. Contact with the eyes: Produces serious eye damage after contact. D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction): Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3. Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. E- Sensitizing effects: Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3. Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.





SECTION 11: TOXICOLOGICAL INFORMATION (continued)

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	ļ	Acute toxicity		
Alkane C6-C8 (even numbered), 1-sulphonic acid, sodium salt	LD50 oral	500 mg/kg	Rat	
CAS: Non-applicable	LD50 dermal	Non-applicable		
EC: 939-625-7	LC50 inhalation	Non-applicable		
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)	LD50 oral	100 mg/kg	Rat	
CAS: 55965-84-9	LD50 dermal	300 mg/kg	Rat	
EC: Non-applicable	LC50 inhalation	Non-applicable		

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification		Acute toxicity	Species	Genus
Alkane C6-C8 (even numbered), 1-sulphonic acid, sodium salt	LC50	Non-applicable		
CAS: Non-applicable	EC50	421 mg/L (48 h)	Daphnia magna	Crustacean
EC: 939-625-7	EC50	Non-applicable		
Dipropylene Glycol Methyl Ether	LC50	10000 mg/L (96 h)	Pimephales promelas	Fish
CAS: 34590-94-8	EC50	1919 mg/L (48 h)	Daphnia magna	Crustacear
EC: 252-104-2	EC50	Non-applicable		
Sodium hydroxide	LC50	189 mg/L (48 h)	Leuciscus idus	Fish
CAS: 1310-73-2	EC50	33 mg/L	Crangon crangon	Crustacear
EC: 215-185-5	EC50	Non-applicable		
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)	LC50	0.1 - 1 mg/L (96 h)		Fish
CAS: 55965-84-9	EC50	0.1 - 1 mg/L		Crustacear
EC: Non-applicable	EC50	0.1 - 1 mg/L		Algae

12.2 Persistence and degradability:

Identification	D	egradability	Biod	egradability
Alkane C6-C8 (even numbered), 1-sulphonic acid, sodium salt	BOD5	Non-applicable	Concentration	20 mg/L
CAS: Non-applicable	COD	Non-applicable	Period	28 days
EC: 939-625-7	BOD5/COD	Non-applicable	% Biodegradable	75 %
Dipropylene Glycol Methyl Ether	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 34590-94-8	COD	0.00202 g O2/g	Period	28 days
EC: 252-104-2	BOD5/COD	Non-applicable	% Biodegradable	73 %

12.3 Bioaccumulative potential:

	Identification	Bioaccumulation potential			
	Dipropylene Glycol Methyl Ether	BCF	1		
	CAS: 34590-94-8	Pow Log	-0.06		
	EC: 252-104-2	Potential	Low		
12.4	12.4 Mobility in soil:				

Not available

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

Version: 1





SECTION 12: ECOLOGICAL INFORMATION (continued)

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)		
20 01 14*	Acids		Dangerous	
Type of wast	e (Regulation (EU) No 1357/2014):			

HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:

man regard to / in			
	14.1	UN number:	UN1760
	14.2	UN proper shipping name:	CORROSIVE LIQUID, N.O.S. (Sodium hydroxide)
	14.3	Transport hazard class(es):	8
		Labels:	8
8	14.4	Packing group:	П
	14.5	Environmental hazards:	No
	14.6	Special precautions for user	
		Special regulations:	274
		Tunnel restriction code:	E
		Physico-Chemical properties:	see section 9
		Limited quantities:	1L
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable
Transport of da	ngerou	is goods by sea:	
With regard to IM	IDG 38-	16:	





SECTION 14: TRANSPORT INFORMATION (continued)			
		UN number:	1011760
		••••••••••	
Â		UN proper shipping name:	CORROSIVE LIQUID, N.O.S. (Sodium hydroxide)
	14.3	Transport hazard class(es):	8
		Labels:	8
		Packing group:	II
8		Environmental hazards:	No
N/	14.6	Special precautions for user	
		Special regulations:	274
		EmS Codes:	F-A, S-B
		Physico-Chemical properties:	see section 9
		Limited quantities:	1L
	14.7	Transport in bulk according to Annex II of Marpol and the	Non-applicable
		IBC Code:	
Transport of dangerous goods by air:			
With regard to IA	With regard to IATA/ICAO 2017:		
Â	14.1	UN number:	UN1760
	14.2	UN proper shipping name:	CORROSIVE LIQUID, N.O.S. (Sodium hydroxide)
	14.3	Transport hazard class(es):	8
		Labels:	8
	14.4	Packing group:	П
	14.5	Environmental hazards:	No
	14.6	Special precautions for user	
		Physico-Chemical properties:	see section 9
	14.7	Transport in bulk according to	Non-applicable
		Annex II of Marpol and the	
		IBC Code:	
<u> </u>			
SECTION 15, DECULA			
SECTION 15: REGULATORY INFORMATION			

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1), (ethylenedioxy)dimethanol.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (Product-type 2, 4, 6, 11, 12, 13) ; (ethylenedioxy)dimethanol (Product-type 2, 6, 11, 12, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Regulation (EC) No 648/2004 on detergents:

In accordance with this regulation the product complies with the following:

The tensoactives contained in this mixture comply with the biodegradibility criteria stipulated in Regulation (EC) nº648/2004 on detergents. The information to prove this is available to the relevant authorities of the Member States and will be shown to them by direct request or the request of a detergent manufacturer.

Labelling for contents:

Component	Concentration interval
Anionic surfactants	5 <= % (w/w) < 15

Preservation agents: (ethylenedioxy)dimethanol (DIMETHYLOL GLYCOL), Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (METHYLCHLOROISOTHIAZOLINONE / METHYLISOTHIAZOLINONE).

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):





SECTION 15: REGULATORY INFORMATION (continued)

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

- Regulation (EC) No 1223/2009 of the European Parliament and of the Council of 30 November 2009 on cosmetic products
- Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents
- Commission Regulation (EC) No 907/2006 of 20 June 2006 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes III and VII

- Commission Regulation (EC) No 551/2009 of 25 June 2009 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes V and VI thereto (surfactant derogation)

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H314: Causes severe skin burns and eye damage

H318: Causes serious eye damage

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

Acute Tox. 4: H302 - Harmful if swallowed

Aquatic Acute 1: H400 - Very toxic to aquatic life

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects

Eye Irrit. 2: H319 - Causes serious eye irritation

Skin Corr. 1A: H314 - Causes severe skin burns and eye damage

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

Classification procedure:

Skin Corr. 1B: Calculation method Eye Dam. 1: Calculation method


Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:







SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LOg-POW: Octanol–water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.