According to 1907/2006/EC (REACH), 2015/830/EU



1.3

EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΟ A) - High strength epoxy adhesive-putty (Component A) 24-004



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΟ A) - High strength epoxy adhesive-putty (Component A)

24-004

Calcium Carbonate

CAS: 471-34-1 EC: 207-439-9 Index: Non-applicable

REACH: 01-2119486795-18-XXXX

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Adhesive for construction

Uses advised against: All uses not specified in this section or in section 7.3

Details of the supplier of the safety data sheet: EVOCHEM S.A. Tzaverdella Place

133 41 PHILI , ATTICA - GREECE

Phone.: 0030 210 5590460 , 0030 210 5590155 -

Fax: 0030 210 5590460 , 0030 210 5590155 Fax: 0030 210 6254737 , 0030 210 5590244 info@evochem.gr; vmergoupis@evochem.gr;

sales@evochem.gr

1.4 Emergency telephone number: National Poisoning Center 2107793777

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Eye Irrit. 2: Eye irritation, Category 2, H319

Muta. 2: Germ cell mutagenicity, Category 2, H341

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1: Sensitisation, skin, Category 1, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning







Hazard statements:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects

Eye Irrit. 2: H319 - Causes serious eye irritation Muta. 2: H341 - Suspected of causing genetic defects

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children P264: Wash thoroughly after handling

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of water

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P308+P313: IF exposed or concerned: Get medical advice/attention

P501: Dispose of contents/container according to the separated collection system used in your municipality

Supplementary information:

Date of compilation: 08/12/2014 Revised: 14/06/2018 Version: 3 (Replaced 2) **Page 1/13**

^{**} Changes with regards to the previous version

According to 1907/2006/EC (REACH), 2015/830/EU



EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΌ A) - High strength epoxy adhesive-putty (Component A) 24-004



SECTION 2: HAZARDS IDENTIFICATION ** (continued)

EUH205: Contains epoxy constituents. May produce an allergic reaction

Substances that contribute to the classification

reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) (CAS: 25068-38-6); 2,3-epoxypropyl neodecanoate (CAS: 26761-45-5)

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Chemical description: Epoxides

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 471-34-1 EC: 207-439-9 Index: Non-applicable	Calcium Carbonate ⁽¹⁾ Regulation 1272/2008 Not classified	24 - <50 %
REACH 01-2119486795-18-XXX		
CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) ⁽²⁾ ATP CLP00	
EC: 500-033-5 Index: 603-074-00-8 REACH 01-2119456619-26-XXX	Regulation 1272/2008 Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	24 - <50 %
CAS: 26761-45-5	2,3-epoxypropyl neodecanoate ⁽²⁾ Self-classified	
EC: 247-979-2 Index: Non-applicable REACH 01-2119431597-33-XXX	Regulation 1272/2008 Aquatic Chronic 2: H411; Muta. 2: H341; Skin Sens. 1: H317 - Warning	2,4 - <4,9 %
CAS: 111-76-2	2-butoxyethanol ⁽³⁾ ATP CLP00	
EC: 203-905-0 Index: 603-014-00-0 REACH 01-2119475108-36-XXX	Regulation 1272/2008 Acute Tox. 4: H302+H312+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	<0,09 %

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

3.2 Mixture:

Non-applicable

SECTION 4: FIRST AID MEASURES

4.1 **Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

- CONTINUED ON NEXT PAGE -

By eye contact:

^{**} Changes with regards to the previous version

 ⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830
 (2) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

⁽³⁾ Substance with a Union workplace exposure limit

According to 1907/2006/EC (REACH), 2015/830/EU



EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΟ A) - High strength epoxy adhesive-putty (Component A) 24-004



SECTION 4: FIRST AID MEASURES (continued)

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation



According to 1907/2006/EC (REACH), 2015/830/EU

EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΌ A) - High strength epoxy adhesive-putty (Component A) 24-004



SECTION 7: HANDLING AND STORAGE (continued)

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 35 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

		Environmental limits		
2-butoxyethanol		IOELV (8h)	20 ppm	98 mg/m ³
CAS: 111-76-2		IOELV (STEL)	50 ppm	246 mg/m ³
EC: 203-905-0		Year	2018	•

DNEL (Workers):

		Short exposure		Long exposure	
Identification	Systemic	Local	Systemic	Local	
Calcium Carbonate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 471-34-1	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 207-439-9	Inhalation	Non-applicable	Non-applicable	10 mg/m ³	Non-applicable
reaction product: bisphenol-A-(epichlorhydrin) (MW < 700)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 25068-38-6	Dermal	8,33 mg/kg	Non-applicable	8,33 mg/kg	Non-applicable
EC: 500-033-5	Inhalation	12,25 mg/m ³	Non-applicable	12,25 mg/m ³	Non-applicable
2,3-epoxypropyl neodecanoate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 26761-45-5	Dermal	Non-applicable	Non-applicable	1,4 mg/kg	Non-applicable
EC: 247-979-2	Inhalation	Non-applicable	Non-applicable	1,965 mg/m ³	Non-applicable
2-butoxyethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	663 mg/m ³	246 mg/m ³	98 mg/m ³	Non-applicable

DNEL (General population):

According to 1907/2006/EC (REACH), 2015/830/EU



EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΌ A) - High strength epoxy adhesive-putty (Component A) 24-004



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

	Short	exposure	Long exposure		
Identification	Identification			Systemic	Local
Calcium Carbonate	Oral	6,1 mg/kg	Non-applicable	6,1 mg/kg	Non-applicable
CAS: 471-34-1	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 207-439-9	Inhalation	Non-applicable	Non-applicable	10 mg/m ³	Non-applicable
reaction product: bisphenol-A-(epichlorhydrin) (MW < 700)	Oral	0,75 mg/kg	Non-applicable	0,75 mg/kg	Non-applicable
CAS: 25068-38-6	Dermal	3,571 mg/kg	Non-applicable	3,571 mg/kg	Non-applicable
EC: 500-033-5	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
2,3-epoxypropyl neodecanoate	Oral	Non-applicable	Non-applicable	1,1 mg/kg	Non-applicable
CAS: 26761-45-5	Dermal	Non-applicable	Non-applicable	0,7 mg/kg	Non-applicable
EC: 247-979-2	Inhalation	Non-applicable	Non-applicable	1 mg/m³	Non-applicable
2-butoxyethanol	Oral	13,4 mg/kg	Non-applicable	3,2 mg/kg	Non-applicable
CAS: 111-76-2	Dermal	44,5 mg/kg	Non-applicable	38 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	426 mg/m ³	123 mg/m ³	49 mg/m ³	Non-applicable

PNEC:

Identification				
Calcium Carbonate	STP	100 mg/L	Fresh water	Non-applicable
CAS: 471-34-1	Soil	Non-applicable	Marine water	Non-applicable
EC: 207-439-9	Intermittent	Non-applicable	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
reaction product: bisphenol-A-(epichlorhydrin) (MW < 700)	STP	10 mg/L	Fresh water	0,006 mg/L
CAS: 25068-38-6	Soil	0,196 mg/kg	Marine water	0,0006 mg/L
EC: 500-033-5	Intermittent	0,018 mg/L	Sediment (Fresh water)	0,996 mg/kg
	Oral	11 g/kg	Sediment (Marine water)	0,0996 mg/kg
2,3-epoxypropyl neodecanoate	STP	50 mg/L	Fresh water	0,0012 mg/L
CAS: 26761-45-5	Soil	Non-applicable	Marine water	0,00012 mg/L
EC: 247-979-2	Intermittent	0,012 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
2-butoxyethanol	STP	463 mg/L	Fresh water	8,8 mg/L
CAS: 111-76-2	Soil	3,13 mg/kg	Marine water	0,88 mg/L
EC: 203-905-0	Intermittent	9,1 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	Non-applicable

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Date of compilation: 08/12/2014 Revised: 14/06/2018 Version: 3 (Replaced 2) **Page 5/13**

According to 1907/2006/EC (REACH), 2015/830/EU



EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΌ A) - High strength epoxy adhesive-putty (Component A) 24-004



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CAT III	EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face mask	CAT II	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks	CAT III	EN 13034:2005+A1:2009 EN 168:2001 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk	CATIII	EN ISO 20345:2011 EN 13832-1:2006	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2002	Eyewash stations	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

*Not relevant due to the nature of the product, not providing information property of its hazards.

V.O.C. (Supply): 0,04 % weight V.O.C. density at 20 °C: 0 kg/m^3 (0 g/L)

Average carbon number: 6

Average molecular weight: 118,2 g/mol

9.1 Information on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 20 °C: Appearance: Viscous Colour: Odour: Characteristic

- CONTINUED ON NEXT PAGE -

Date of compilation: 08/12/2014 Revised: 14/06/2018 Version: 3 (Replaced 2) **Page 6/13**

According to 1907/2006/EC (REACH), 2015/830/EU



EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΌ A) - High strength epoxy adhesive-putty (Component A) 24-004



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Odour threshold: Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 259 °C Vapour pressure at 20 °C: 4 Pa

Vapour pressure at 50 °C: 32 Pa (0 kPa)

Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: $2 - 2 \text{ kg/m}^3$ Relative density at 20 °C: 1,75 - 1,85

Dynamic viscosity at 20 °C: 180000 - 220000 cP
Kinematic viscosity at 20 °C: Non-applicable *
Kinematic viscosity at 40 °C: >20,5 cSt

Concentration: Non-applicable *
pH: Non-applicable *
Vapour density at 20 °C: Non-applicable *

Partition coefficient n-octanol/water 20 °C:

Solubility in water at 20 °C:

Non-applicable *

Explosive properties:

Non-applicable *

Oxidising properties:

Non-applicable *

Flammability:

Flash Point: Non Flammable (>60 °C)

Flammability (solid, gas):

Autoignition temperature:

238 °C

Lower flammability limit: Non-applicable *

Upper flammability limit:

Non-applicable *

Explosive:

Lower explosive limit:

Upper explosive limit:

Non-applicable *

Non-applicable *

9.2 Other information:

Surface tension at 20 °C:

Refraction index:

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Date of compilation: 08/12/2014 Revised: 14/06/2018 Version: 3 (Replaced 2) **Page 7/13**

According to 1907/2006/EC (REACH), 2015/830/EU



EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΌ A) - High strength epoxy adhesive-putty (Component A) 24-004



SECTION 10: STABILITY AND REACTIVITY (continued)

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - Mutagenicity: Exposure to this product can cause genetic modifications. For more specific information on the possible health effects see section 2.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

According to 1907/2006/EC (REACH), 2015/830/EU



EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΌ A) - High strength epoxy adhesive-putty (Component A) 24-004



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
2,3-epoxypropyl neodecanoate	LD50 oral	970000 mg/kg	Rat
CAS: 26761-45-5	LD50 dermal	Non-applicable	
EC: 247-979-2	LC50 inhalation	Non-applicable	
Calcium Carbonate	LD50 oral	6450 mg/kg	Rat
CAS: 471-34-1	LD50 dermal	Non-applicable	
EC: 207-439-9	LC50 inhalation	Non-applicable	
2-butoxyethanol	LD50 oral	1414 mg/kg	Rat
CAS: 111-76-2	LD50 dermal	1060 mg/kg	Rabbit
EC: 203-905-0	LC50 inhalation	11 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity:

Identification		Acute toxicity	Species	Genus	
Calcium Carbonate	LC50	56000 mg/L (96 h)	Gambussia afinis	Fish	
CAS: 471-34-1	EC50	Non-applicable			
EC: 207-439-9	EC50	Non-applicable			
reaction product: bisphenol-A-(epichlorhydrin) (MW < 700)	LC50	1 - 10 mg/L (96 h)		Fish	
CAS: 25068-38-6	EC50	1 - 10 mg/L		Crustacean	
EC: 500-033-5	EC50	1 - 10 mg/L		Algae	
2,3-epoxypropyl neodecanoate	LC50	5 mg/L (96 h)	Salmo gairdneri	Fish	
CAS: 26761-45-5	EC50	4.8 mg/L (96 h)	Daphnia magna	Crustacean	
EC: 247-979-2	EC50	3 mg/L (72 h)	Selenastrum capricornutum	Algae	
2-butoxyethanol	LC50	1490 mg/L (96 h)	Lepomis macrochirus	Fish	
CAS: 111-76-2	EC50	1815 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 203-905-0	EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae	

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
reaction product: bisphenol-A-(epichlorhydrin) (MW < 700)	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 25068-38-6	COD	Non-applicable	Period	28 days
EC: 500-033-5	BOD5/COD	Non-applicable	% Biodegradable	0 %
2,3-epoxypropyl neodecanoate	BOD5	Non-applicable	Concentration	3 mg/L
CAS: 26761-45-5	COD	Non-applicable	Period	28 days
EC: 247-979-2	BOD5/COD	Non-applicable	% Biodegradable	7 %
2-butoxyethanol	BOD5	0.71 g O2/g	Concentration	100 mg/L
CAS: 111-76-2	COD	2.2 g O2/g	Period	14 days
EC: 203-905-0	BOD5/COD	0.32	% Biodegradable	96 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential		
reaction product: bisphenol-A-(epichlorhydrin) (MW < 700)	BCF	4	
CAS: 25068-38-6	Pow Log	2.8	
EC: 500-033-5	Potential	Low	

According to 1907/2006/EC (REACH), 2015/830/EU



EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΌ A) - High strength epoxy adhesive-putty (Component A) 24-004



Page 10/13

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bio	Bioaccumulation potential		
2,3-epoxypropyl neodecanoate	BCF	371		
CAS: 26761-45-5	Pow Log	4.4		
EC: 247-979-2	Potential	High		
2-butoxyethanol	BCF	3		
CAS: 111-76-2	Pow Log	0.83		
EC: 203-905-0	Potential	Low		

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
2,3-epoxypropyl neodecanoate	Кос	143	Henry	Non-applicable
CAS: 26761-45-5	Conclusion	High	Dry soil	Non-applicable
EC: 247-979-2	Surface tension	Non-applicable	Moist soil	Non-applicable
2-butoxyethanol	Koc	8	Henry	1,621E-1 Pa·m³/mol
CAS: 111-76-2	Conclusion	Very High	Dry soil	No
EC: 203-905-0	Surface tension	2,729E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

	Code	Description	Waste class (Regulation (EU) No 1357/2014)
ĺ	08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP4 Irritant — skin irritation and eye damage, HP13 Sensitising, HP11 Mutagenic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:

According to 1907/2006/EC (REACH), 2015/830/EU

Evochem[®]

EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΌ A) - High strength epoxy adhesive-putty (Component A) 24-004



SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number: UN3082

14.2 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(reaction product: bisphenol-A-(epichlorhydrin) (MW < 700))

14.3 Transport hazard class(es): 9

Labels: 9

14.4Packing group:III14.5Environmental hazards:Yes

14.6 Special precautions for user

Special regulations: 274, 335, 375, 601
Tunnel restriction code: Non-applicable
Physico-Chemical properties: see section 9
Limited quantities: 5 L

14.7 Transport in bulk according to Non-applicable

Annex II of Marpol and the

IBC Code:

Transport of dangerous goods by sea:

With regard to IMDG 38-16:

14.1 UN number: UN3082

14.2 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(reaction product: bisphenol-A-(epichlorhydrin) (MW < 700))

14.3 Transport hazard class(es): 9

Labels: 9

14.4 Packing group: III **14.5 Environmental hazards:** Yes

14.6 Special precautions for user

Special regulations: 335, 969, 274
EmS Codes: F-A, S-F
Physico-Chemical properties: see section 9
Limited quantities: 5 L

14.7 Transport in bulk according to Non-applicable

Annex II of Marpol and the

IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2017:



14.1 UN number: UN3082

14.2 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(reaction product: bisphenol-A-(epichlorhydrin) (MW < 700))

14.3 Transport hazard class(es): 9

Labels: 9
14.4 Packing group: III
14.5 Environmental hazards: Yes

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Transport in bulk according to Non-applicable

Annex II of Marpol and the

IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Date of compilation: 08/12/2014 Revised: 14/06/2018 Version: 3 (Replaced 2) Page 11/13

According to 1907/2006/EC (REACH), 2015/830/EU



EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΌ A) - High strength epoxy adhesive-putty (Component A) 24-004



SECTION 15: REGULATORY INFORMATION (continued)

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- · Precautionary statements
- · Supplementary information

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction

H341: Suspected of causing genetic defects

H411: Toxic to aquatic life with long lasting effects

H315: Causes skin irritation

H319: Causes serious eye irritation

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects

Eye Irrit. 2: H319 - Causes serious eye irritation

Muta. 2: H341 - Suspected of causing genetic defects

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:



According to 1907/2006/EC (REACH), 2015/830/EU



EPOXITE FIX ALL 30' (ΣΥΣΤΑΤΙΚΌ A) - High strength epoxy adhesive-putty (Component A) 24-004

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor

LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol—water partition coefficient Koc: Partition coefficient of organic carbon



The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET
Date of compilation: 08/12/2014 Revised: 14/06/2018 Version: 3 (Replaced 2) Page 13/13