

MERCOLA

EPOXITE RESIN 95 (component B) - High strength epoxy adhesive (component B)

mponen 24-077

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- **1.1 Product identifier:** EPOXITE RESIN 95 (component B) High strength epoxy adhesive (component B) 24-077
- **1.2** Relevant identified uses of the substance or mixture and uses advised against: Relevant uses: Adhesive for construction

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet: EVOCHEM S.A.

Tzaverdella Place 133 41 PHILI , ATTICA - GREECE Phone.: 0030 210 5590460 , 0030 210 5590155 -Fax: 0030 210 6254737 , 0030 210 5590244 info@evochem.gr; vmergoupis@evochem.gr; sales@evochem.gr

1.4 Emergency telephone number: National Poisoning Center 2107793777

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Eye Dam. 1: Serious eye damage, Category 1, H318 Flam. Liq. 3: Flammable liquids, Category 3, H226 Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:





Hazard statements:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Eye Dam. 1: H318 - Causes serious eye damage Flam. Liq. 3: H226 - Flammable liquid and vapour Skin Irrit. 2: H315 - Causes skin irritation Skin Sens. 1A: H317 - May cause an allergic skin reaction

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P261: Avoid breathing dust/fume/gas/mist/vapours/spray P273: Avoid release to the environment P280: Wear protective gloves/protective clothing/eye protection/face protection P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P310: Immediately call a poison center/doctor P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

** Changes with regards to the previous version



MERCOLA

EPOXITE RESIN 95 (component B) - High strength epoxy adhesive

(component B) 24-077

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

Non-applicable

3.2 Mixture:

Chemical description: Epoxides

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification				
CAS: 68155-17-9 EC: 268-945-3 Index: Non-applicable REACH Non-applicable	Amides, from tall-oil fatty acids and tetraethylenepentamine ⁽¹⁾ Self-classified Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314 - Danger	24 - <50 %			
CAS: 68082-29-1 EC: 500-191-5	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids Self-classified and triethylenetetramine ⁽¹⁾				
Index: Non-applicable REACH 01-2119972320-44-XXX : X	Regulation 1272/2008 Aquatic Chronic 2: H411; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1A: H317 - Danger	24 - <50 %			
CAS: 8002-09-3	Pine oil ⁽¹⁾ Self-classified				
EC: Non-applicable Index: Non-applicable REACH Non-applicable	Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Sens. 1: H317 - Danger Image: Chronic 2: H411; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3:	4,9 - <9,9 %			
CAS: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol ⁽¹⁾ ATP CLP00				
EC: 202-013-9 Index: 603-069-00-0 REACH 01-2119560597-27-XXX	Regulation 1272/2008 Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	2,4 - <4,9 %			
CAS: 90640-66-7	Amines, polyethylenepoly-, tetraethylenepentamine fraction ⁽¹⁾ Self-classified				
EC: 292-587-7 Index: Non-applicable REACH 01-2119487290-37-XXX	Regulation 1272/2008 Acute Tox. 4: H302+H312; Aquatic Chronic 2: H411; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	0,24 - <0,9 %			
CAS: 90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction ⁽¹⁾ Self-classified				
EC: 292-588-2 Index: Non-applicable REACH 01-2119487919-13-XXX	Regulation 1272/2008 Acute Tox. 4: H312; Aquatic Chronic 3: H412; Skin Corr. 1B: H314; Skin Sens. 1: H317 -	0,24 - <0,9 %			

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:



24-077



SECTION 4: FIRST AID MEASURES (continued)

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO_2). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions







SECTION 7: HANDLING AND STORAGE (continued)

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:5 °CMaximum Temp.:35 °CMaximum time:12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

There are no occupational exposure limits for the substances contained in the product

DNEL (Workers):

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 68082-29-1	Dermal	Non-applicable	Non-applicable	1,1 mg/kg	Non-applicable
EC: 500-191-5	Inhalation	Non-applicable	Non-applicable	3,9 mg/m ³	Non-applicable
2,4,6-tris(dimethylaminomethyl)phenol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 90-72-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-013-9	Inhalation	Non-applicable	Non-applicable	0,31 mg/m ³	Non-applicable
Amines, polyethylenepoly-, tetraethylenepentamine fraction	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 90640-66-7	Dermal	Non-applicable	Non-applicable	0,74 mg/kg	Non-applicable
EC: 292-587-7	Inhalation	6940 mg/m ³	Non-applicable	1,29 mg/m ³	Non-applicable
Amines, polyethylenepoly-, triethylenetetramine fraction	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 90640-67-8	Dermal	Non-applicable	Non-applicable	0,57 mg/kg	Non-applicable
EC: 292-588-2	Inhalation	5380 mg/m ³	Non-applicable	1 mg/m ³	Non-applicable



EPOXITE RESIN 95 (component B) - High strength epoxy adhesive (component B) 24-077



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Long	Long exposure	
Identification		Systemic	Local	Systemic	Local	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Oral	Non-applicable	Non-applicable	0,56 mg/kg	Non-applicable	
CAS: 68082-29-1	Dermal	Non-applicable	Non-applicable	0,56 mg/kg	Non-applicable	
EC: 500-191-5	Inhalation	Non-applicable	Non-applicable	0,97 mg/m ³	Non-applicable	
Amines, polyethylenepoly-, tetraethylenepentamine fraction	Oral	26 mg/kg	Non-applicable	0,53 mg/kg	Non-applicable	
CAS: 90640-66-7	Dermal	10 mg/kg	Non-applicable	0,32 mg/kg	Non-applicable	
EC: 292-587-7	Inhalation	2071 mg/m ³	Non-applicable	0,38 mg/m ³	Non-applicable	
Amines, polyethylenepoly-, triethylenetetramine fraction	Oral	20 mg/kg	Non-applicable	0,41 mg/kg	Non-applicable	
CAS: 90640-67-8	Dermal	8 mg/kg	Non-applicable	0,25 mg/kg	Non-applicable	
EC: 292-588-2	Inhalation	1600 mg/m ³	Non-applicable	0,29 mg/m ³	Non-applicable	

PNEC:

Identification				
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	STP	3,84 mg/L	Fresh water	0,00434 mg/L
CAS: 68082-29-1	Soil	86,78 mg/kg	Marine water	0,000434 mg/L
EC: 500-191-5	Intermittent	0,0434 mg/L	Sediment (Fresh water)	434,02 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	43,4 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	STP	0,2 mg/L	Fresh water	0,084 mg/L
CAS: 90-72-2	Soil	Non-applicable	Marine water	0,0084 mg/L
EC: 202-013-9	Intermittent	0,84 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
Amines, polyethylenepoly-, tetraethylenepentamine fraction	STP	9,73 mg/L	Fresh water	0,0068 mg/L
CAS: 90640-66-7	Soil	0,683 mg/kg	Marine water	0,00068 mg/L
EC: 292-587-7	Intermittent	0,068 mg/L	Sediment (Fresh water)	3,43 mg/kg
	Oral	0,23 g/kg	Sediment (Marine water)	0,343 mg/kg
Amines, polyethylenepoly-, triethylenetetramine fraction	STP	4,25 mg/L	Fresh water	0,19 mg/L
CAS: 90640-67-8	Soil	19,1 mg/kg	Marine water	0,038 mg/L
EC: 292-588-2	Intermittent	0,2 mg/L	Sediment (Fresh water)	95,9 mg/kg
	Oral	0,18 g/kg	Sediment (Marine water)	19,2 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.
- Specific protection Pictogram	PPE	Labelling	CEN Standard	Remarks
	Protective gloves against minor risks	"		Replace gloves in case of any sign of damage. Fo prolonged periods of exposure to the product for professional users/industrials, we recommend usir



24-077



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

	Pictogram	PPE		Labelling	CEN S	Standard	Remarks
	Mandatory face protection	Panoramic glass splash/projec				66:2001 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
E	Body protection						
	Pictogram	PPE		Labelling	CEN S	Standard	Remarks
	Mandatory complete body protection	Antistatic and f protective clo			EN 114 EN 114 EN 1 EN 1 EN ISO	49-1:2006 49-2:1997 49-3:2004 68:2001 14116:2015 49-5:2008	Limited protection against flames.
	Mandatory foot protection	Safety footwe antistatic and hea propertie	at resistant			287:2008 20345:2011	Replace boots at any sign of deterioration.
F	Additional emerge	ncy measures					
	Emergency mea	sure	Stan	dards	E	Emergency measu	ure Standards
	Emergency sho	wer		2358-1 4-1:2002		Eyewash stations	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):

7,5 % weight Non-applicable V.O.C. density at 20 °C: Average carbon number: 2

Average molecular weight: 46,1 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1	Information on basic physical and chemical proper	ties:
	For complete information see the product datasheet.	
	Appearance:	
	Physical state at 20 °C:	Liquid
	Appearance:	Colorless
	Colour:	Amber
	Odour:	Aminic
	Odour threshold:	Non-applicable *
	Volatility:	
	Boiling point at atmospheric pressure:	115 °C
	Vapour pressure at 20 °C:	Non-applicable *
	*Not relevant due to the nature of the product, not providing informat	ion property of its hazards.



MERCOLA

EPOXITE RESIN 95 (component B) - High strength epoxy adhesive

(component B) 24-077

	9: PHYSICAL AND CHEMICAL PROPERTIES	(continued)
Vapo	our pressure at 50 °C:	<300000 Pa (300 kPa)
Evap	poration rate at 20 °C:	Non-applicable *
Prod	duct description:	
Dens	sity at 20 °C:	Non-applicable *
Relat	tive density at 20 °C:	Non-applicable *
Dyna	amic viscosity at 20 °C:	Non-applicable *
Kiner	matic viscosity at 20 °C:	Non-applicable *
Kiner	matic viscosity at 40 °C:	Non-applicable *
Conc	centration:	Non-applicable *
pH:		Non-applicable *
Vapo	our density at 20 °C:	Non-applicable *
Parti	ition coefficient n-octanol/water 20 °C:	Non-applicable *
Solut	bility in water at 20 °C:	Non-applicable *
Solut	bility properties:	Non-applicable *
Deco	omposition temperature:	Non-applicable *
Melti	ing point/freezing point:	Non-applicable *
Explo	osive properties:	Non-applicable *
Oxidi	lising properties:	Non-applicable *
Flam	nmability:	
Flash	h Point:	24 °C
Flam	nmability (solid, gas):	Non-applicable *
Auto	bignition temperature:	325 °C
Lowe	er flammability limit:	Not available
Uppe	er flammability limit:	Not available
Expl	losive:	
Lowe	er explosive limit:	Non-applicable *
Uppe	er explosive limit:	Non-applicable *
9.2 Othe	er information:	
Surfa	ace tension at 20 °C:	Non-applicable *
Refra	action index:	Non-applicable *
*Not r	relevant due to the nature of the product, not providing inform	nation property of its hazards.
SECTION :	10: STABILITY AND REACTIVITY	
10.1 Rea	ctivity:	
No h	nazardous reactions are expected because the proc	luct is stable under recommended storage conditions. See section 7.
LO.2 Cher	mical stability:	

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable
10.5	Incompatible materials:				
	Acids	Water	Combustive materials	Combustible materials	Others



EPOXITE RESIN 95 (component B) - High strength epoxy adhesive (component B)

24-077



SECT	TON 10: STABILITY AND	REACTIVITY (continu	ed)		
	Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases
10.6	Hazardous decomposition	on products:			
	See subsection 10.3, 10.4 a complex mixtures of chemi				
SECT	TON 11: TOXICOLOGIC	AL INFORMATION **			
11.1	Information on toxicolo	gical effects:			
	The experimental informati	on related to the toxicologi	cal properties of the produ	ct itself is not available	
	Dangerous health implie	cations:			
	In case of exposure that is adverse effects on health n A- Ingestion (acute effect)	nay result, depending on th	5	the recommended occup	pational exposure limits,
	dangerous for consump	tion. For more information			is substances classified as

- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

^{**} Changes with regards to the previous version



EPOXITE RESIN 95 (component B) - High strength epoxy adhesive (component B) 24-077



SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Specific toxicology information on the substances:

Identification		Acute toxicity		
Pine oil	LD50 oral	3200 mg/kg	Rat	
CAS: 8002-09-3	LD50 dermal	Non-applicable		
EC: Non-applicable	LC50 inhalation	Non-applicable		
2,4,6-tris(dimethylaminomethyl)phenol	LD50 oral	1200 mg/kg	Rat	
CAS: 90-72-2	LD50 dermal	Non-applicable		
EC: 202-013-9	LC50 inhalation	Non-applicable		
Amines, polyethylenepoly-, tetraethylenepentamine fraction	LD50 oral	1861 mg/kg	Rat	
CAS: 90640-66-7	LD50 dermal	1465 mg/kg	Rabbit	
EC: 292-587-7	LC50 inhalation	Non-applicable		
Amines, polyethylenepoly-, triethylenetetramine fraction	LD50 oral	2505 mg/kg	Rat	
CAS: 90640-67-8	LD50 dermal	1465 mg/kg	Rabbit	
EC: 292-588-2	LC50 inhalation	Non-applicable		

** Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

TOXICILY:					
Identification		Acute toxicity	Species	Genus	
Amides, from tall-oil fatty acids and tetraethylenepentamine	LC50	0.1 - 1 mg/L (96 h)		Fish	
CAS: 68155-17-9	EC50	0.1 - 1 mg/L		Crustacear	
EC: 268-945-3	EC50	0.1 - 1 mg/L		Algae	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products w tall-oil fatty acids and triethylenetetramine	vith LC50	7 mg/L (96 h)	Danio rerio	Fish	
CAS: 68082-29-1	EC50	7 mg/L (48 h)	Daphnia magna	Crustacear	
EC: 500-191-5	EC50	4 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae	
Pine oil	LC50	1 - 10 mg/L (96 h)		Fish	
CAS: 8002-09-3	EC50	1 - 10 mg/L		Crustacea	
EC: Non-applicable	EC50	1 - 10 mg/L		Algae	
2,4,6-tris(dimethylaminomethyl)phenol	LC50	345 mg/L (96 h)	QSAR	Fish	
CAS: 90-72-2	EC50	Non-applicable			
EC: 202-013-9	EC50	Non-applicable			
Amines, polyethylenepoly-, tetraethylenepentamine fraction	LC50	Non-applicable			
CAS: 90640-66-7	EC50	Non-applicable		-	
EC: 292-587-7	EC50	6.8 mg/L (72 h)	Selenastrum capricornutum	Algae	
Amines, polyethylenepoly-, triethylenetetramine fraction	LC50	330 mg/L (96 h)	Pimephales promelas	Fish	
CAS: 90640-67-8	EC50	31.1 mg/L (48 h)	Daphnia magna	Crustacea	
EC: 292-588-2	EC50	20 mg/L (72 h)	Selenastrum capricornutum	Algae	
Persistence and degradability:					
Identification	C	Degradability	Biodegradability		
Amines, polyethylenepoly-, tetraethylenepentamine fraction	OD5	Non-applicable C	oncentration 2 mg	g/L	
CAS: 90640-66-7	OD	Non-applicable Po	eriod 162	days	

12.3 Bioaccumulative potential:

EC: 292-587-7

Identification	Bio	Bioaccumulation potential	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	BCF	77	
CAS: 68082-29-1	Pow Log		
EC: 500-191-5	Potential	Moderate	

OD5/COD

** Changes with regards to the previous version

Non-applicable

% Biodegradable

0 %



EPOXITE RESIN 95 (component B) - High strength epoxy adhesive (component B) 24-077



Identification		Bioaccumulation potential			
2,4,6-tris(dimethylaminomethyl)phenol			BCF	3 0.77 Low	
CAS: 90-72-2	CAS: 90-72-2 EC: 202-013-9				
EC: 202-013-9					
Mobility in soil:					
Identification	Absorption/desorption			Volatility	
2,4,6-tris(dimethylaminomethyl)phenol	Кос	15130	Henry	9,312E-	12 Pa·m³/mo
CAS: 90-72-2	Conclusion	Immobile	Dry soil	No	
EC: 202-013-9	Surface tension	Non-applicable	Moist soil	No	
Amines, polyethylenepoly-, tetraethylenepentamine fraction	Кос	1590	Henry	Non-ap	plicable
CAS: 90640-66-7	Conclusion	Low	Dry soil	Non-ap	plicable
EC: 292-587-7	Surface tension	Non-applicable	Moist soil	Non-ap	plicable
Amines, polyethylenepoly-, triethylenetetramine fraction	Кос	1584	Henry	Non-ap	plicable
CAS: 90640-67-8	Conclusion	Low	Dry soil	Non-ap	plicable
EC: 292-588-2	Surface tension	Non-applicable	Moist soil	Non-ap	plicable
Results of PBT and vPvB assessment:					

12.6 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP4 Irritant — skin irritation and eye damage, HP8 Corrosive, HP13 Sensitising

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION **

Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:

** Changes with regards to the previous version



MERCOLA

EPOXITE RESIN 95 (component B) - High strength epoxy adhesive (component B) 24-077

SECTION 14: TRANSPORT	INFORMATION ** (continued)	
1/ 1	UN number:	UN1133
	UN proper shipping name:	ADHESIVES containing flammable liquid
	Transport hazard class(es):	3
	Labels:	3
14.4	Packing group:	III
14.5	Environmental hazards:	Yes
14.6	Special precautions for user	
	Special regulations:	640E
	Tunnel restriction code:	D/E
	Physico-Chemical properties:	see section 9
	Limited quantities:	5L
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable
Transport of dangero	us goods by sea:	
With regard to IMDG 38	-16:	
14.1	UN number:	UN1133
▲ <u>∧</u> 14.2	UN proper shipping name:	ADHESIVES containing flammable liquid
	Transport hazard class(es):	3
	Labels:	3
V 14.4	Packing group:	III
14.5	Environmental hazards:	Yes
14.6	Special precautions for user	
	Special regulations:	955, 223
	EmS Codes:	F-E, S-D
	Physico-Chemical properties:	see section 9
	Limited quantities:	5 L
14.7	Transport in bulk according to Annex II of Marpol and the	Non-applicable
	IBC Code:	
Transport of dangero	us goods by air:	
With regard to IATA/IC/	AO 2017:	
14.1	UN number:	UN1133
│	UN proper shipping name:	ADHESIVES containing flammable liquid
🛛 🗸 14.3	Transport hazard class(es):	3
	Labels:	3
14.4		III
	Environmental hazards:	Yes
14.6	Special precautions for user	
	Physico-Chemical properties:	see section 9
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable
** Changes with regards to the pre		

** Changes with regards to the previous version

SECTION 15: REGULATORY INFORMATION

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Ethanol. Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable Article 95, REGULATION (EU) No 528/2012: Non-applicable





SECTION 15: REGULATORY INFORMATION (continued)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,

- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

· New declared substances

Amides, from tall-oil fatty acids and tetraethylenepentamine (68155-17-9) Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine (68082-29-1) Pine oil (8002-09-3)

- 2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)
- Amines, polyethylenepoly-, tetraethylenepentamine fraction (90640-66-7)
- Amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)

· Removed substances

- Trientine (112-24-3)
- Toluene (108-88-3)
- Polyamide (68410-23-1)
- CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16): Pictograms
 - PICLOGIAINS
 - Hazard statements
 Precautionary statements
 - Supplementary information
- TRANSPORT INFORMATION (SECTION 14):
 - Packing group

Texts of the legislative phrases mentioned in section 2:

** Changes with regards to the previous version





MERCOLA

EPOXITE RESIN 95 (component B) - High strength epoxy adhesive

(component B) 24-077

SECTION 16: OTHER INFORMATION ** (continued)	
H318: Causes serious eye damage H317: May cause an allergic skin reaction H226: Flammable liquid and vapour H315: Causes skin irritation H411: Toxic to aquatic life with long lasting effects	
Texts of the legislative phrases mentioned in section 3:	
The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3	I
CLP Regulation (EC) No 1272/2008:	
Acute Tox. 4: H302 - Harmful if swallowed Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin Acute Tox. 4: H312 - Harmful in contact with skin Aquatic Acute 1: H400 - Very toxic to aquatic life Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways Eye Dam. 1: H318 - Causes serious eye damage Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 3: H226 - Flammable liquid and vapour Skin Corr. 1B: H314 - Causes severe skin burns and eye damage Skin Corr. 1C: H314 - Causes severe skin burns and eye damage Skin Irrit. 2: H315 - Causes skin irritation Skin Sens. 1: H317 - May cause an allergic skin reaction Skin Sens. 1: H317 - May cause an allergic skin reaction	
Classification procedure:	
Eye Dam. 1: Calculation method Skin Sens. 1A: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3) Skin Irrit. 2: Calculation method Aguatic Chronic 2: Calculation method	
Advice related to training:	
Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.	۱
Principal bibliographical sources:	
http://echa.europa.eu http://eur-lex.europa.eu	
Abbreviations and acronyms:	
ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50	
LC50: Lethal Concentration 50	
EC50: Effective concentration 50 Log-POW: Octanol–water partition coefficient	
Koc: Partition coefficient of organic carbon	

Koc: Partition coefficient of organic carbon

** Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.