

ISOCRYL PRIMER DUR AQUA - Roof & wall acrylic waterbased



primer 24-132

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING				
1.1	Product identifier:	ISOCRYL PRIMER DUR AQUA - Roof & wall acrylic waterbased primer 24-132 Acrylic resin (Viscosity < 600 cP at 20°C)		
	CAS:			
		Non-applicable		
	EC:	Non-applicable		
	Index:	Non-applicable		
	REACH:	Non-applicable		
1.2	Relevant identified	uses of the substance or mixture and uses advised against:		
	Relevant uses: Surfac	ze Primer		
	Uses advised against: All uses not specified in this section or in section 7.3			
1.3	1.3 Details of the supplier of the safety data sheet:			
	Evochem S.A. Tzaverdella Place 133 41 Phili - Attica - Greece Phone.: 0030 210 5590460 , 0030 210 5590155 - Fax: 0030 210 6254737 , 0030 210 5590244 info@evochem.gr http://www.evochem.gr			
1.4	Emergency telepho	one number: National Poisoning Center 2107793777		
SECT	TION 2: HAZARDS I	DENTIFICATION **		
2.1	Classification of th	e substance or mixture:		
	CLP Regulation (EC	C) No 1272/2008:		
	The product is not cla	assified as hazardous according to CLP Regulation (EC) No 1272/2008.		
2.2	Labol olomonto			

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Hazard statements:

Non-applicable

Precautionary statements:

Non-applicable

Supplementary information:

EUH208: Contains Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Chemical description: Aqueous mixture composed of additives and acrylic resin

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

** Changes with regards to the previous version



ISOCRYL PRIMER DUR AQUA - Roof & wall acrylic waterbased

primer 24-132



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

Identification	Chemical name/Classification		
CAS: Non-applicable EC: Non-applicable Index: Non-applicable REACH Non-applicable	Acrylic resin (Viscosity < 600 cP at 20°C) ⁽¹⁾ Not classified Regulation 1272/2008 Regulation 1272/2008	9,9 - <19 %	
	failing to meet any of the criteria set out in Regulation (EU) No. 2015/830 ation on the hazards of the substances consult sections 8, 11, 12, 15 and 16.		
Mixture:			
Non-applicable			

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Consult a doctor in case of discomfort showing the SDS for the product.

By inhalation:

In case of symptoms, move the person affected into fresh air.

By skin contact:

In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes to the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety data Sheet

By eye contact:

Rinse with water until the product has been eliminated. In case of problems, consult a doctor showing the SDS for the product.

By ingestion/aspiration:

In case of consumption in large quantities, it is recommended to seek medical assistance.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Product is non-flammable, with a low risk of fire due to the flammabliity characteristics of the product in normal conditions of storage, handling and use. In the case of the existence of sustained combustion as a result of improper handling, storage or use any type of extinguishing agent can be used (ABC Powder, water,...)

5.2 Special hazards arising from the substance or mixture:

Due to its non-flammable nature, the product does not present a fire risk under normal conditions of storage, handling and use.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

- CONTINUED ON NEXT PAGE -



ISOCRYL PRIMER DUR AQUA - Roof & wall acrylic waterbased

primer 24-132



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Isolate leaks provided that there is no additional risk for the people performing this task.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

It is recommended to transfer at a slow speed to avoid the creation of electrostatic charges that could affect flammable products. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is not necessary to take special measures to prevent environmental risks. For more information see subsection 6.2

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:5 °CMaximum Temp.:35 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1	Control	parameters:
-----	---------	-------------

Substances whose occupational exposure limits have to be monitored in the work environment

There are no occupational exposure limits for the substances contained in the product

DNEL (Workers):

Non-applicable

DNEL (General population):

Non-applicable

PNEC:

Non-applicable

8.2 Exposure controls:

A.- General security and hygiene measures in the work place



ISOCRYL PRIMER DUR AQUA - Roof & wall acrylic waterbased

primer 24-132



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

If product is used at the concentration dosing conditions specified in the relevant instructions for use (section 15), personal protective equipment described in section 8.2 for UNDILUTED products will not be required.

Safe handling recommendations for undiluted product:

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands



D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	oramic glasses against splash/projections.	CAT II	EN 166:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2001, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CAT II	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345 y EN 13832-1

F.- Additional emergency measures

It is not necessary to take additional emergency measures.

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

,	
V.O.C. (Supply):	0,05 % weight
V.O.C. density at 20 °C:	0,56 kg/m³ (0,56 g/L)
Average carbon number:	4
Average molecular weight:	122,1 g/mol
With regard to Directive 2004/4	12/EC, this product which is ready to use has the following characteristics:
V.O.C. density at 20 °C:	0,28 kg/m³ (0,28 g/L)
EU limit for the product (Cat. A	.H): 30 g/L (2010)
Components: 001 - 50 % v/	/v

- CONTINUED ON NEXT PAGE -



ISOCRYL PRIMER DUR AQUA - Roof & wall acrylic waterbased

primer 24-132



SECTIO	N 9: PHYSICAL AND CHEMICAL PROPERTIES					
9.1 Ir	nformation on basic physical and chemical proper	ties:				
Fo	For complete information see the product datasheet.					
A	Appearance:					
Pł	hysical state at 20 °C:	Liquid				
Ap	ppearance:	Transparent				
Co	olour:	Not available				
0	dour:	Characteristic				
0	dour threshold:	Non-applicable *				
V	olatility:					
Вс	oiling point at atmospheric pressure:	100 °C				
Va	apour pressure at 20 ºC:	2350 Pa				
Va	apour pressure at 50 °C:	12381 Pa (12 kPa)				
E١	vaporation rate at 20 °C:	Non-applicable *				
P	roduct description:					
De	ensity at 20 °C:	1040 kg/m ³				
Re	elative density at 20 ºC:	1,04				
D	ynamic viscosity at 20 °C:	Non-applicable *				
Ki	inematic viscosity at 20 °C:	Non-applicable *				
Ki	inematic viscosity at 40 °C:	Non-applicable *				
Co	oncentration:	990 - 1050 g/L (active ingredient)				
pł	H:	6,5 - 7,5				
Va	apour density at 20 °C:	Non-applicable *				
Pa	artition coefficient n-octanol/water 20 °C:	Non-applicable *				
So	olubility in water at 20 °C:	Non-applicable *				
So	olubility properties:	Non-applicable *				
De	ecomposition temperature:	Non-applicable *				
Μ	elting point/freezing point:	Non-applicable *				
E>	xplosive properties:	Non-applicable *				
O	xidising properties:	Non-applicable *				
FI	Flammability:					
Fl	ash Point:	Non Flammable (>60 °C)				
Fl	ammability (solid, gas):	Non-applicable *				
Au	utoignition temperature:	Non-applicable *				
Lo	ower flammability limit:	Non-applicable *				
U	pper flammability limit:	Non-applicable *				
E	xplosive:					
Lo	ower explosive limit:	Non-applicable *				
U	pper explosive limit:	Non-applicable *				
.2 0	ther information:					
Su	urface tension at 20 °C:	Non-applicable *				
Re	efraction index:	Non-applicable *				
*N	Not relevant due to the nature of the product, not providing information	ion property of its hazards.				

SECTION 10: STABILITY AND REACTIVITY



ISOCRYL PRIMER DUR AQUA - Roof & wall acrylic waterbased

primer 24-132



SECT	SECTION 10: STABILITY AND REACTIVITY (continued)				
10.1	D.1 Reactivity: No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.				
10.2	Chemical stability:				
	Chemically stable under the	conditions of storage, hand	ling and use.		
10.3	Possibility of hazardous r	eactions:			
	Under the specified condition	ns, hazardous reactions that	t lead to excessive temper	ratures or pressure are no	t expected.
10.4	Conditions to avoid:				
	Applicable for handling and s	storage at room temperatur	e:		
	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
10.5	Incompatible materials:				
	Acids Avoid strong acids	Water Not applicable	Combustive materials Not applicable	Combustible materials Not applicable	Others Avoid alkalis or strong bases
10.6	Hazardous decompositio				
10.0	See subsection 10.3, 10.4 ar	-	ific decomposition produc	ts Depending on the dec	composition conditions
	complex mixtures of chemica				
0.000					
SECT	TON 11: TOXICOLOGICA				
11.1	Information on toxicolog	ical effects:			
	LD50 oral > 2000 mg/kg (rat)				
	Dangerous health implications:				
	In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure: A- Ingestion (acute effect):				
	 Acute toxicity : Based on available data, the classification criteria are not met Corrosivity/Irritability: Based on available data, the classification criteria are not met 				
	B- Inhalation (acute effect):				
	- Acute toxicity : Based on available data, the classification criteria are not met				
	 Corrosivity/Irritability: Based on available data, the classification criteria are not met Contact with the skin and the eyes (acute effect): 				
	 Contact with the skin: Based on available data, the classification criteria are not met 				
		s: Based on available data,			
	D- CMR effects (carcinogeni	city, mutagenicity and toxic	ity to reproduction):		
		ed on available data, the cla			
		on available data, the class : Based on available data, t			
	E- Sensitizing effects:	,			
	- Respiratory: Based o	n available data, the classifi	cation criteria are not me	t	
		available data, the classific			
	F- Specific target organ toxi	icity (STOT) - single exposu	ire:		
	Based on available data,	the classification criteria an	e not met		
	G- Specific target organ toxi	city (STOT)-repeated expo	sure:		
	 Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met Skin: Based on available data, the classification criteria are not met H- Aspiration hazard: 				
	Based on available data, the classification criteria are not met				
	- CONTINUED ON NEXT PAGE -				



ISOCRYL PRIMER DUR AQUA - Roof & wall acrylic waterbased

primer 24-132



JLCI	ION II: TOXICOLOGICAL INFORMATION (continued)
	Other information:
	Non-applicable
	Specific toxicology information on the substances:
	Not available
SECT	ION 12: ECOLOGICAL INFORMATION
The ex	perimental information related to the eco-toxicological properties of the product itself is not available
	Toxicity:
	Not available
12.2	Persistence and degradability:
	Not available
12.3	Bioaccumulative potential:
	Not available
12.4	Mobility in soil:
	Not available
12.5	Results of PBT and vPvB assessment:
	Product fails to meet PBT/vPvB criteria
12.6	Other adverse effects:
	Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
	It is not possible to assign a specific code, as it depends on the intended use by the user	Non dangerous

Type of waste (Regulation (EU) No 1357/2014):

Non-applicable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID, IMDG, IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- CONTINUED ON NEXT PAGE -



ISOCRYL PRIMER DUR AQUA - Roof & wall acrylic waterbased

primer 24-132



SECTION 15: REGULATORY INFORMATION (continued)

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1), (ethylenedioxy)dimethanol.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Relevant instructions for use:

Dilute up to 100% with water

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

Removed substances

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no.

- 220-239-6] (3:1) (55965-84-9)
- CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):
- Pictograms
 - Hazard statements
- Precautionary statements
- Supplementary information

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Non-applicable

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

** Changes with regards to the previous version



ISOCRYL PRIMER DUR AQUA - Roof & wall acrylic waterbased

primer 24-132



SECTION 16: OTHER INFORMATION ** (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 Log-POW: Octanol–water partition coefficient Koc: Partition coefficient of organic carbon

** Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.