



ISOMIX CEMENT COLOR YELLOW

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier: ISOMIX CEMENT COLOR YELLOW
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:
Relevant uses: Colorants (pigments and dyestuffs), inorganic
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 **Details of the supplier of the safety data sheet:** EVOCHEM S.A.
Tzavardella Place
133 41 PHILI , ATTICA - GREECE
Phone.: 0030 210 5590460 , 0030 210 5590155 -
Fax: 0030 210 6254737 , 0030 210 5590244
info@evochem.gr; vmergoupis@evochem.gr;
sales@evochem.gr
www.evochem.gr
- 1.4 Emergency telephone number: National Poisoning Center 2107793777

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification : Not classified.

Classification according to Directive 67/548/EEC [DSD]

Classification : Not classified.

2.2 Label elements

Hazard pictograms : Not applicable.

Signal word : No signal word.

Hazard statements : ☒ No known significant effects or critical hazards.

Additional warning phrases : Not applicable.

Precautionary statements

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification : Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

ISOMIX CEMENT COLOR YELLOW

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product definition (REACH) : Mono-constituent substance
FeO(OH)

Within the present knowledge of the supplier, this product does not contain any hazardous ingredients in quantities requiring reporting in this section, in accordance with EU or national regulations.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Ingestion** : No special measures required.
- Skin contact** : No special measures required.
- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

See Section 11 for more detailed information on health effects and symptoms.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water spray (fog), foam, dry chemical or CO₂.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : No specific fire or explosion hazard.

Hazardous combustion products : No specific data.

5.3 Advice for firefighters

Special precautions for fire-fighters : Not applicable.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

ISOMIX CEMENT COLOR YELLOW

SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures** : No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Avoid breathing dust. Provide adequate ventilation. Put on appropriate personal protective equipment (see Section 8). Hazard of slipping on spilt product.
- 6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- 6.3 Methods and materials for containment and cleaning up**
- Small spill** : Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: HANDLING AND STORAGE

- 7.1 Precautions for safe handling** : No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities** : No special measures required.
- 7.3 Specific end use(s)**
- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters**
- Exposure limit values** : Not available.

<u>Derived effect levels</u>						
Ingredient name	Type	Exposure	Value	Population	Effects	Remarks
Iron hydroxide oxide yellow	DNEL	Long term Inhalation	10 mg/m ³	Workers	Systemic	Inhalable Dust
	DNEL	Long term Inhalation	10 mg/m ³	Workers	Local	Inhalable Dust
Conclusion/Summary		: Dust Inhalable 10 mg/m ³ , Respirable dust 3 mg/m ³				

- CONTINUED ON NEXT PAGE -

ISOMIX CEMENT COLOR YELLOW

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)

Predicted No Effect Concentration (PNEC)

Ingredient name	Compartment Detail	Value	Method Detail	Remarks
Conclusion/Summary		: PNECs : Not applicable.		

Recommended monitoring procedures : ☒ this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2 Exposure controls

Risk management measures

Occupational exposure controls

Technical measures : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal protection measures

Respiratory protection : Recommended: Dust-protection mask

Hand protection : Recommended: gloves

Eye protection : ☒ Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If operating conditions cause high dust concentrations to be produced, use dust goggles.
Recommended: safety glasses with side-shields

Skin protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Environmental exposure controls

Technical measures : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

CONTINUED ON NEXT PAGE

ISOMIX CEMENT COLOR YELLOW

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

General information

Appearance

Physical state	: Solid. [powders]
Colour	: Yellow.
Odour	: Odourless.

Important health, safety and environmental information

pH	: 3,5 to 8 [Conc. (% w/w): 5%]
Melting point	: 1000°C (>1832°F)
Vapour pressure	: not available
Density	: 4,26 kg/L (20°C)
Bulk density	: 300 to 1000 kg/m ³
Solubility	: 0,000001 g/l (water)
Decomposition temperature	: 180°C

9.2 Other information

No additional information.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: From approx. 180 °C conversion into Fe ₂ O ₃ .
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

- CONTINUED ON NEXT PAGE -

ISOMIX CEMENT COLOR YELLOW

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Potential acute health effects

Eye contact : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	Test
Iron hydroxide oxide yellow	LD50 Oral	- Rat	>10000 mg/kg	-	-
Iron hydroxide oxide yellow	LC50 Inhalation Dusts and mists	- Rat	>195 g/m ³	6 hours	-
	LC50 Inhalation Dusts and mists	- Rat	>195 mg/m ³	2 weeks	-

Irritation/Corrosion

Skin : Non-irritating. *Test results on an analogous product

Eyes : Non-irritating. *Test results on an analogous product

Sensitiser

Product/ingredient name	Route of exposure	Species	Result	Test description
Iron hydroxide oxide yellow	skin	Guinea pig	Not sensitizing	-

Chronic effects : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

- CONTINUED ON NEXT PAGE -

ISOMIX CEMENT COLOR YELLOW

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Product/ingredient name	Test	Result	Species	Exposure
Iron hydroxide oxide yellow	OECD 202 <i>Daphnia</i> sp. Acute Immobilization Test	Acute EC50 >100 mg/l	Daphnia - Daphnia magna	48 hours
	-	Acute LC0 >100000 mg/l	Fish - Danio rerio	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not applicable.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects

Other adverse effects : Not available.

AOX : Not available.

Remarks : No known significant effects or critical hazards.

ISOMIX CEMENT COLOR YELLOW

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Methods of disposal : Examine possibilities for re-utilisation. Product residues and uncleaned empty containers should be packaged, sealed, labelled, and disposed of or recycled according to relevant national and local regulations. Where large quantities are concerned, consult the supplier. When uncleaned empty containers are passed on, the recipient must be warned of any possible hazard that may be caused by residues. For disposal within the EC, the appropriate code according to the European Waste List (EWL) should be used. It is among the tasks of the polluter to assign the waste to waste codes specific to industrial sectors and processes according to the European Waste List (EWL).

Hazardous waste : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 91/689/EEC.

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: TRANSPORT INFORMATION

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	-	-	-	-
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)/ Marks	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No	No
14.6 Special precautions for user/Additional information	Not regulated.	Not regulated.	Not regulated.	Not regulated.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Hazard notes:

Not dangerous cargo.

Keep separated from foodstuffs.

- CONTINUED ON NEXT PAGE -

ISOMIX CEMENT COLOR YELLOW

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern


None of the components are listed.

Annex XVII - : Not applicable.

**Restrictions on the
manufacture, placing on
the market and use of
certain dangerous
substances, mixtures
and articles**

Other EU regulations

Seveso II Directive

 This product is not controlled under the Seveso II Directive.

15.2 Chemical Safety Assessment : Not applicable.

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
vPvB = Very Persistent and Very Bioaccumulative

History

Date of issue : 2013-01-25

Date of previous issue : 2011-02-02

Version : 2.02

 Indicates information that has changed from previously issued version.

The information contained in this security data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this security data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -