

**ISOMIX ONE COAT PLASTER – one coat  
application plaster****SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1 Product identifier:** ISOMIX ONE COAT PLASTER –one coat application plaster

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses: plaster. For professional use only.

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

EVOCHEM S.A.  
Tzavardella Place  
133 41 PHILI , ATTICA – GREECE  
Phone.: 0030 210 5590460 , 0030 210 5590155 –  
Fax: 0030 210 6254737 , 0030 210 5590244  
info@evochem.gr; vmergoupis@evochem.gr;  
sales@evochem.gr  
www.evochem.gr

**1.4 Emergency telephone number: National Poisoning Center 210 7793777**

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1 Classification of the substance or mixture:**

**Directive 67/548/EC and Directive 1999/45/EC:**

This product was classified in accordance with Directive 67/548/EC and Directive 1999/45/EC, adapting the requirements to Regulation (EC) n°1907/2006 (REACH regulation).

Xi: R37/38 - Irritating to respiratory system and skin, R41 - Risk of serious damage to eyes, R43 - May cause sensitization by skin contact

**CLP Regulation (EC) n° 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.

Eye Dam. 1: Serious eye damage, Category 1

Skin Irrit. 2: Dermal irritation, Category 2

Skin Sens. 1: Sensitization, dermal, Category 1

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3

**2.2 Label elements:**

**Directive 67/548/EC and Directive 1999/45/EC:**

In accordance with the legislation, the elements on the label are as follows:



**R Phrases:**

R37/38: Irritating to respiratory system and skin

R41: Risk of serious damage to eyes

R43: May cause sensitization by skin contact

**S Phrases:**

S24: Avoid contact with skin

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S37/39: Wear suitable gloves and eye/face protection

S51: Use only in well-ventilated areas

**Supplementary information:**

Non-applicable

**Substances that contribute to the classification:**

Cement, portland, chemicals

**CLP Regulation (EC) n° 1272/2008:**

Danger



**Hazard indications:**

- CONTINUED ON NEXT PAGE -

## ISOMIX ONE COAT PLASTER – one coat application plaster

### SECTION 2: HAZARDS IDENTIFICATION (continue)

Eye Dam. 1: H318 - Causes serious eye damage  
Skin Irrit. 2: H315 - Causes skin irritation  
Skin Sens. 1: H317 - May cause an allergic skin reaction  
STOT SE 3: H335 - May cause respiratory irritation

#### Cautionary advice:

P271: Use only outdoors or in a well-ventilated area  
P302+P352: IF ON SKIN: Wash with plenty of soap and water  
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310: Immediately call a POISON CENTER or doctor/physician  
P362: Take off contaminated clothing and wash before reuse

#### Supplementary information:

EUH208: Contains Cement, portland, chemicals. May produce an allergic reaction

#### Substances that contribute to the classification

Cement, portland, chemicals; Calcium dihydroxide

#### 2.3 Other hazards:

Non-applicable

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**Chemical description:** Mineral based mixture

#### Components:

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

| Identification                                                                           | Chemical name/Classification                                                                                                                                                                               | Concentration |
|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| CAS: 65997-15-1<br>EC: 266-043-4<br>Index: Non-applicable<br>REACH: Non-applicable       | <b>Cement, portland, chemicals</b> Self-classified<br>Directive 67/548/EC Xi: R37/38, R41, R43<br>Regulation 1272/2008 Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Danger | 10 - <25 %    |
| CAS: 1305-62-0<br>EC: 215-137-3<br>Index: Non-applicable<br>REACH: 01-2119475151-45-XXXX | <b>Calcium dihydroxide</b> Self-classified<br>Directive 67/548/EC Xi: R37/38, R41<br>Regulation 1272/2008 Eye Dam. 1: H318; Skin Irrit. 2: H315; STOT SE 3: H335 - Danger                                  | 2,5 - <10 %   |

To obtain more information on the risk of the substances consult sections 8, 11, 12 and 16.

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the MSDS of this product.

##### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

##### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

##### By eye contact:

Rinse eyes thoroughly with luke warm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the MSDS of the product.

##### By consumption:

Do not induce vomiting, but if it does happen keep the head up to avoid inhalation. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

- CONTINUED ON NEXT PAGE -

**ISOMIX ONE COAT PLASTER – one coat  
application plaster****SECTION 4: FIRST AID MEASURES (continue)****4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media:**

Product is non-flammable under normal conditions of storage, manipulation and use. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use tap water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive subproducts are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:**

Sweep up and shovel product or other means and place in container for reuse (preferred) or disposal See sections 8 and 13.

**6.2 Environmental precautions:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Sweep up and shovel product or other means and place in container for reuse (preferred) or disposal

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling:**

A.- Precautions for safe manipulation

Use in ventilated areas. Avoid the build up of dust

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container.

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

- CONTINUED ON NEXT PAGE -

## ISOMIX ONE COAT PLASTER – one coat application plaster

### SECTION 7: HANDLING AND STORAGE (continue)

Minimum Temp.: 5 °C  
 Maximum Temp.: 30 °C  
 Maximum time: 12 Months

#### B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food

Humidity: Avoid direct impact

#### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

| Identification      | Environmental limits |      |                     |
|---------------------|----------------------|------|---------------------|
| Calcium dihydroxide | IOELV (8h)           |      | 5 mg/m <sup>3</sup> |
| CAS: 1305-62-0      | IOELV STEL           |      |                     |
| EC: 215-137-3       | Year                 | 2012 |                     |

#### DNEL (Workers):

| Identification      |            | Short exposure |                     | Long exposure  |                     |
|---------------------|------------|----------------|---------------------|----------------|---------------------|
|                     |            | Systemic       | Local               | Systemic       | Local               |
| Calcium dihydroxide | Oral       | Non-applicable | Non-applicable      | Non-applicable | Non-applicable      |
| CAS: 1305-62-0      | Dermal     | Non-applicable | Non-applicable      | Non-applicable | Non-applicable      |
| EC: 215-137-3       | Inhalation | Non-applicable | 4 mg/m <sup>3</sup> | Non-applicable | 1 mg/m <sup>3</sup> |

#### DNEL (Population):

| Identification      |            | Short exposure |                     | Long exposure  |                     |
|---------------------|------------|----------------|---------------------|----------------|---------------------|
|                     |            | Systemic       | Local               | Systemic       | Local               |
| Calcium dihydroxide | Oral       | Non-applicable | Non-applicable      | Non-applicable | Non-applicable      |
| CAS: 1305-62-0      | Dermal     | Non-applicable | Non-applicable      | Non-applicable | Non-applicable      |
| EC: 215-137-3       | Inhalation | Non-applicable | 4 mg/m <sup>3</sup> | Non-applicable | 1 mg/m <sup>3</sup> |

#### PNEC:

| Identification      |              | Short exposure |                         | Long exposure  |       |
|---------------------|--------------|----------------|-------------------------|----------------|-------|
|                     |              | Systemic       | Local                   | Systemic       | Local |
| Calcium dihydroxide | STP          | 3 mg/L         | Fresh water             | 0,49 mg/L      |       |
| CAS: 1305-62-0      | Soil         | 1080 mg/kg     | Marine water            | 0,32 mg/L      |       |
| EC: 215-137-3       | Intermittent | 0,49 mg/L      | Sediment (Fresh water)  | Non-applicable |       |
|                     | Oral         | Non-applicable | Sediment (Marine water) | Non-applicable |       |



#### 8.2 Exposure controls:

##### A.- General security and hygiene measures in the work place

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the professional exposure limits. In case of using individual protection equipment they should have the "CE marking" in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

##### B.- Respiratory protection



| LRP Pictogram                                                                                                                 | PPE                               | Labelling                                                                                      | CEN Standard        | Remarks                                                                                                                                                              |
|-------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------------------------------------------------------------|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br>Mandatory respiratory tract protection | Filter mask for gases and vapours | <br>CAT III | EN 405:2001+A1:2009 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

##### C.- Specific protection for the hands



- CONTINUED ON NEXT PAGE -

## ISOMIX ONE COAT PLASTER – one coat application plaster



### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)

| LRP Pictogram                                                                                                  | PPE                        | Labelling                                                                         | CEN Standard                                                  | Remarks                                          |
|----------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------|--------------------------------------------------|
| <br>Mandatory hand protection | Chemical protective gloves |  | EN 374-1:2003<br>EN 374-3:2003/AC:2006<br>EN 420:2003+A1:2009 | Replace the gloves at any sign of deterioration. |



#### D.- Ocular and facial protection

| LRP Pictogram                                                                                                  | PPE                                     | Labelling                                                                         | CEN Standard                                                             | Remarks                                                                                                                   |
|----------------------------------------------------------------------------------------------------------------|-----------------------------------------|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| <br>Mandatory face protection | Panoramic glasses against liquid splash |  | EN 166:2001<br>EN 172:1994/A1:2000<br>EN 172:1994/A2:2001<br>EN 165:2005 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

#### E.- Bodily protection

| LRP Pictogram | PPE                  | Labelling                                                                          | CEN Standard                                   | Remarks                    |
|---------------|----------------------|------------------------------------------------------------------------------------|------------------------------------------------|----------------------------|
|               | Work clothing        |   | EN 340:2003                                    | For professional use only. |
|               | Anti-slip work shoes |  | EN ISO 20347:2004/A1:2007<br>EN ISO 20344:2011 | None                       |

#### F.- Additional emergency measures

| Emergency measure                                                                                       | Standards                      | Emergency measure                                                                                        | Standards                     |
|---------------------------------------------------------------------------------------------------------|--------------------------------|----------------------------------------------------------------------------------------------------------|-------------------------------|
| <br>Emergency shower | ANSI Z358-1<br>ISO 3864-1:2002 | <br>Eyewash stations | DIN 12 899<br>ISO 3864-1:2002 |

#### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

#### Volatil organic compounds:

With regard to Directive 1999/13/EC, this product has the following characteristics:

|                           |                             |
|---------------------------|-----------------------------|
| V.O.C. (Supply):          | 0 % weight                  |
| V.O.C. density at 20 °C:  | 0 kg/m <sup>3</sup> (0 g/L) |
| Average carbon number:    | Non-applicable              |
| Average molecular weight: | Non-applicable              |

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

##### Appearance:

|                          |               |
|--------------------------|---------------|
| Physical state at 20 °C: | Solid         |
| Appearance:              | Not available |
| Color:                   | Not available |
| Odor:                    | Not available |

##### Volatility:

|                                        |                  |
|----------------------------------------|------------------|
| Boiling point at atmospheric pressure: | Non-applicable * |
|----------------------------------------|------------------|

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

## ISOMIX ONE COAT PLASTER – one coat application plaster

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continue)

|                            |                  |
|----------------------------|------------------|
| Vapour pressure at 20 °C:  | Non-applicable * |
| Vapour pressure at 50 °C:  | Non-applicable * |
| Evaporation rate at 20 °C: | Non-applicable * |

#### Product description:

|                                              |                        |
|----------------------------------------------|------------------------|
| Density at 20 °C:                            | 2674 kg/m <sup>3</sup> |
| Relative density at 20 °C:                   | 2,674                  |
| Dynamic viscosity at 20 °C:                  | Non-applicable *       |
| Kinematic viscosity at 20 °C:                | Non-applicable *       |
| Kinematic viscosity at 40 °C:                | Non-applicable *       |
| Concentration:                               | Non-applicable *       |
| pH:                                          | Non-applicable *       |
| Vapour density at 20 °C:                     | Non-applicable *       |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable *       |
| Solubility in water at 20 °C:                | Non-applicable *       |
| Solubility property:                         | Non-applicable *       |
| Decomposition temperature:                   | Non-applicable *       |

#### Flammability:

|                           |                        |
|---------------------------|------------------------|
| Flash Point:              | Non Flammable (>60 °C) |
| Autoignition temperature: | Non-applicable *       |
| Lower flammability limit: | Non-applicable *       |
| Upper flammability limit: | Non-applicable *       |

#### 9.2 Other information:

|                           |                  |
|---------------------------|------------------|
| Surface tension at 20 °C: | Non-applicable * |
| Refraction index:         | Non-applicable * |

\*Not relevant due to the nature of the product, not providing information property of its hazards.

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected if the following technical instructions storage of chemicals. See section 7.

#### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the conditions no hazardous reactions are expected to produce a pressure or excessive temperatures.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight       | Humidity            |
|--------------------|------------------|-------------------------|----------------|---------------------|
| Not applicable     | Not applicable   | Not applicable          | Not applicable | Avoid direct impact |

#### 10.5 Incompatible materials:

| Acids        | Water               | Combustive materials | Combustible materials | Others                                      |
|--------------|---------------------|----------------------|-----------------------|---------------------------------------------|
| Incompatible | Avoid direct impact | Not applicable       | Not applicable        | Base metal salts (Al, NH <sub>4</sub> ,...) |

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION

- CONTINUED ON NEXT PAGE -

## ISOMIX ONE COAT PLASTER – one coat application plaster

### SECTION 11: TOXICOLOGICAL INFORMATION (continue)

#### 11.1 Information on toxicological effects:

No experimental information is available on the product itself in relation to the toxicological properties. When performing the danger classification on corrosive or irritant effects the recommendations included in section 3.2.5 of Annex VI of Directive 67/548/EC, in paragraphs b) and c) of section 3 of article 6 of Directive 1999/45/EC and in section 3.2.3.3.5. of Annex I of CLP Regulation were taken into account.

##### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

##### A.- Ingestion:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.

##### B- Inhalation:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

##### C- Contact with the skin and the eyes:

Produces serious eye damage after contact.

##### D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

##### E- Sensitizing effects:

Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

##### F- Specific target organ toxicity (STOT)-time exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

##### G- Specific target organ toxicity (STOT)-repeated exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

##### H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

##### Other information:

Non-applicable

##### Specific toxicology information on the substances:

| Identification      | Acute toxicity  |                | Genus |
|---------------------|-----------------|----------------|-------|
| Calcium dihydroxide | LD50 oral       | 7340 mg/kg     | Rat   |
| CAS: 1305-62-0      | LD50 dermal     | Non-applicable |       |
| EC: 215-137-3       | LC50 inhalation | Non-applicable |       |

### SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the ecotoxicological properties of the mixture itself is not available

#### 12.1 Toxicity:

| Identification      | Acute toxicity |                 | Specie           | Genus |
|---------------------|----------------|-----------------|------------------|-------|
| Calcium dihydroxide | LC50           | 160 mg/L (96 h) | Gambusia affinis | Fish  |
| CAS: 1305-62-0      | EC50           | Non-applicable  |                  |       |
| EC: 215-137-3       | EC50           | Non-applicable  |                  |       |

#### 12.2 Persistence and degradability:

Not available

#### 12.3 Bioaccumulative potential:

Not available

#### 12.4 Mobility in soil:

Not available

- CONTINUED ON NEXT PAGE -



**ISOMIX ONE COAT PLASTER – one coat  
application plaster**

**SECTION 12: ECOLOGICAL INFORMATION (continue)**

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

| Code      | Description                                                                            | Waste class (Directive 2008/98/EC) |
|-----------|----------------------------------------------------------------------------------------|------------------------------------|
| 08 04 09* | Waste adhesives and sealants containing organic solvents or other dangerous substances | Dangerous                          |

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2000/532/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2000/532/EC: Commission Decision of 3 May 2000

**SECTION 14: TRANSPORT INFORMATION**

This product is not regulated for transport (ADR/RID,IMDG,IATA)

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Active substances for which a decision of non-inclusion onto Annex I (Regulation (EU) No 528/2012): Calcium dihydroxide (excluded for the product type 18)

Regulation (EC) 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII, REACH):**

Non-applicable

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

**Other legislation:**

Non-applicable

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EC) N° 453/2010)

**Modifications related to the previous security card which concerns the ways of managing risks. :**

Non-applicable

**Text of R-phrases considered in section 3:**

Directive 67/548/EC and Directive 1999/45/EC:

- CONTINUED ON NEXT PAGE -





## Safety data sheet

According to 1907/2006/EC (REACH), 453/2010/EC

# Evochem®

### ISOMIX ONE COAT PLASTER – one coat application plaster

#### SECTION 16: OTHER INFORMATION (continue)

R37/38: Irritating to respiratory system and skin

R41: Risk of serious damage to eyes

R43: May cause sensitisation by skin contact

#### CLP Regulation (EC) n° 1272/2008:

Eye Dam. 1: H318 - Causes serious eye damage

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

STOT SE 3: H335 - May cause respiratory irritation

#### Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

<http://esis.jrc.ec.europa.eu>

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

#### Abbreviations and acronyms:

- ADR: European agreement concerning the international carriage of dangerous goods by road
- IMDG: International maritime dangerous goods code
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organisation
- COD: Chemical Oxygen Demand
- BOD5: 5-day biochemical oxygen demand
- BCF: Bioconcentration factor
- LD50: Lethal Dose 50
- CL50: Lethal Concentration 50
- EC50: Effective concentration 50
- Log-POW: Octanol–water partition coefficient
- Koc: Partition coefficient of organic carbon

The information contained in this security data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this security data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -