



extra 24-08

SECT	TION 1: IDENTIFICATION OF THE S	SUBSTANCE/MIXTURE	AND OF THE COMPANY/UNDERTAKING				
1.1	Product identifier:	SWAN ΔΙΑΛΥΤΙΚΟ ΠΟΛΥ 24-08	OYPEΘANHΣ EXTRA - Uretahne thinner extra				
		Toluene					
	CAS:	108-88-3					
	EC:	203-625-9					
	Index:	601-021-00-3					
	REACH:	01-2119471310-51-XXX					
1.2	Relevant identified uses of the sub	stance or mixture and u	ses advised against:				
	Relevant uses: Solvent for coatings						
	Uses advised against: All uses not speci	fied in this section or in se	ction 7.3				
1.3	Details of the supplier of the safety	data sheet:	EVOCHEM S.A. Tzaverdella Place 133 41 PHILI , ATTICA - GREECE Phone.: 0030 210 5590460 , 0030 210 5590155 - Fax: 0030 210 6254737 , 0030 210 5590244 info@evochem.gr; vmergoupis@evochem.gr; sales@evochem.gr www.evochem.gr				
1.4	Emergency telephone number: Na	tional Poisoning Center 210	7793777				
SECT	ION 2: HAZARDS IDENTIFICATION	V					
2.1	Classification of the substance or n						
2.1							
	 Directive 67/548/EC and Directive 1999/45/EC: This product was classified in accordance with Directive 67/548/EC and Directive 1999/45/EC, adapting the requirements to Regulation (EC) nº1907/2006 (REACH regulation). F: R11 - Highly flammable Repr. Cat 3: R63 - Possible risk of harm to the unborn child Xi: R36/38 - Irritating to eyes and skin Xn: R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation, R65 - Harmful: may cause lung damage if swallowed R66 - Repeated exposure may cause skin dryness or cracking 						
	R67 - Vapours may cause drowsines CLP Regulation (EC) nº 1272/2008						
			e with CLP Regulation (EC) nº 1272/2008.				
	Asp. Tox. 1: Aspiration hazard, Cate Eye Irrit. 2: Eye irritation, Category 2 Flam. Liq. 2: Flammable liquids, Cate Repr. 2: Reproductive toxicity, Category Skin Irrit. 2: Skin irritation, Category STOT RE 2: Specific target organ too STOT SE 3: Specific toxicity causing	2 egory 2 jory 2 (H361d) 2 kicity, repeated exposure, C					
2.2	Label elements:						
	Directive 67/548/EC and Directive						
	In accordance with the legislation, the second seco	ne elements on the label ar	e as follows:				





extra 24-08

SECTION 2: HAZARDS IDENTIFICATION (continue)

R11: Highly flammable

- R36/38: Irritating to eyes and skin
- R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation
- R63: Possible risk of harm to the unborn child
- R65: Harmful: may cause lung damage if swallowed
- R66: Repeated exposure may cause skin dryness or cracking
- R67: Vapours may cause drowsiness and dizziness

S Phrases

- S16: Keep away from sources of ignition No smoking
- S2: Keep out of the reach of children S43: In case of fire, use polyvalent powder ABC
- S46: If swallowed, seek medical advice immediately and show this container or label
- S9: Keep container in a well-ventilated place

Supplementary information:

Non-applicable

Substances that contribute to the classification:

Toluene (CAS: 108-88-3)

CLP Regulation (EC) nº 1272/2008:

Danger



Hazard statements:

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Lig. 2: H225 - Highly flammable liquid and vapour Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure STOT SE 3: H336 - May cause drowsiness or dizziness **Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand

- P102: Keep out of reach of children
- P103: Read label before use
- P280: Wear protective gloves/protective clothing/eye protection/face protection

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking

Substances that contribute to the classification

Toluene (CAS: 108-88-3); 2-butanone (CAS: 78-93-3)

2.3 **Other hazards:**

Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical description: Solvent/s

Components:

In accordance with Annex II of Regulation (EC) nº1907/2006 (point 3), the product contains:





SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continue)

Identification		Chemical name/Classification	Concentration
CAS: 108-88-3	Toluene	ATP CLP00	
EC: 203-625-9 Index: 601-021-00-3	Directive 67/548/EC	F: R11; Repr. Cat 3: R63; Xi: R38; Xn: R48/20, R65; R67	X 50 - <75 %
REACH:01-2119471310-51-XXX	X Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: 🤙 🎪	₿ >
CAS: 78-93-3	2-butanone	ATP CLP00	
EC: 201-159-0 Index: 606-002-00-3	Directive 67/548/EC	F: R11; Xi: R36; R66; R67	<mark>X</mark> 19 - <24 %
REACH: 01-2119457290-43-XXX	X Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the MSDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply,etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with luke warm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the MSDS of the product.

By consumption:

Do not induce vomiting, but if it does happen keep the head up to avoid inhalation. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire exginguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive subproducts are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflamation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.





24-08

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertizing agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as dangerous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in fixed places that comply with the necessary security conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to containers of small amounts. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:	5 °C
Maximun Temp.:	35 °C
Maximum time:	12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	Environmental limits			
Toluene	IOELV (8h)	50 ppm	192 mg/m ³	
CAS: 108-88-3	IOELV (STEL)	100 ppm	384 mg/m ³	
EC: 203-625-9	Year	2014		
2-butanone	IOELV (8h)	200 ppm	600 mg/m ³	
CAS: 78-93-3	IOELV (STEL)	300 ppm	900 mg/m ³	
EC: 201-159-0	Year	2014		

DNEL (Workers):

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	384 mg/m ³	384 mg/m ³	192 mg/m ³	192 mg/m ³
2-butanone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	600 mg/m ³	Non-applicable

DNEL (Population):

		Short	exposure	Long e	exposure
Identification		Systemic	Local	Systemic	Local
Toluene	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	226 mg/m ³	226 mg/m ³	56,5 mg/m ³	56,5 mg/m ³
2-butanone	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	106 mg/m ³	Non-applicable

PNEC:

Identification				
Toluene	STP	13,61 mg/L	Fresh water	0,68 mg/L
CAS: 108-88-3	Soil	2,89 mg/kg	Marine water	0,68 mg/L
EC: 203-625-9	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg
2-butanone	STP	709 mg/L	Fresh water	55,8 mg/L
CAS: 78-93-3	Soil	22,5 mg/kg	Marine water	55,8 mg/L
EC: 201-159-0	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg
	Oral	1000 g/kg	Sediment (Marine water)	284,7 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the professional exposure limits. In case of using indivudual protection equipment they should have the ""CE marking"" in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services

as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.



Evochem[®]

SWAN ΔΙΑΛΥΤΙΚΟ ΠΟΛΥΟΥΡΕΘΑΝΗΣ EXTRA - Uretahne thinner extra

24-08

SECTIO	N 8: EXPOSURE	CONTROLS/PERSON	AL PROTECT	ION (continue)			
	Pictogram	PPE	Labelling	CEN Standard		Remarks	
	Mandatory hand protection	NON-disposable chemical protective gloves		EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	manufa the p	he Breakthrough Time indicated by the acturer must exceed the period during which roduct is being used. Do not use protective ns after the product has come into contact with skin.	
D.	- Ocular and facial	protection					
	Pictogram	PPE	Labelling	CEN Standard		Remarks	
	Mandatory face protection	Face mask		EN 166:2001 EN 167:2001 EN 168:2001 EN 172:1994/A1:2000 EN 172:1994/A2:2001 EN ISO 4007:2012		daily and disinfect periodically according to anufacturer 's instructions. Use if there is a risk of splashing.	
E	- Bodily protection						
	Pictogram	PPE	Labelling	CEN Standard		Remarks	
	Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994		professional use only. Clean periodically ording to the manufacturer 's instructions.	
	Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistent properties		EN 13287:2008 EN ISO 20345:2011 EN 13832-1:2006 EN ISO 20344:2011	Re	place boots at any sign of deterioration.	
F	- Additional emerge	ency measures					
	Emergency mea	asure St	andards	Emergency measu	ire	Standards	
	Emergency sho	ISO 3	5I Z358-1 864-1:2002	Eyewash station	s	DIN 12 899 ISO 3864-1:2002	
Environmental exposure controls: In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D Volatil organic compounds: With regard to Directive 1999/13/EC, this product has the following characteristics: V.O.C. (Supply): 100 % weight V.O.C. density at 20 °C: 857,01 kg/m³ (857,01 g/L) Average carbon number: 6,1 Average molecular weight: 95,33 g/mol							
SECTIO	N 9: PHYSICAL A	AND CHEMICAL PROP	ERTIES				
Fo Ap		sic physical and chemi tion see the product data		5:			

 Physical state at 20 °C:
 Liquid

 Appearance:
 Not available

 Color:
 Not available

 Odor:
 Not available

 *Not relevant due to the nature of the product, not providing information property of its hazards.





24-08

SECT	ION 9: PHYSICAL AND CHEMI		TIES (continue)
	Volatility:		
	Boiling point at atmospheric pressu	re•	104 °C
	Vapour pressure at 20 °C:		4423 Pa
	Vapour pressure at 50 °C:		17400 Pa (17 kPa)
	Evaporation rate at 20 °C:		Non-applicable *
	Product description:		
	Density at 20 °C:		857 kg/m³
	Relative density at 20 °C:		0,857
	Dynamic viscosity at 20 °C:		0,57 cP
	Kinematic viscosity at 20 °C:		0,66 cSt
	Kinematic viscosity at 40 °C:		<20,5 cSt
	Concentration:		Non-applicable *
	pH:		Non-applicable *
	Vapour density at 20 °C:		Non-applicable *
	Partition coefficient n-octanol/wate	20 ºC:	Non-applicable *
	Solubility in water at 20 °C:		Non-applicable *
	Solubility property:		Non-applicable *
	Decomposition temperature:		Non-applicable *
	Melting point/freezing point:		Non-applicable *
	Flammability:		
	Flash Point:	5 °C	
	Autoignition temperature:	423 °C	
	Lower flammability limit:	Not ava	ilable
	Upper flammability limit:	Not ava	ilable
9.2	Other information:		
	Surface tension at 20 °C:	Non-applicable	*
	Refraction index:	Non-applicable	*
	*Not relevant due to the nature of the pro	duct, not providing	information property of its hazards.

*Not relevant due to the nature of the product, not providing information property of its hazar

SECT	SECTION 10: STABILITY AND REACTIVITY									
10.1	Reactivity:									
	No hazardous reactions are expected if the following technical instructions storage of chemicals. See section 7.									
10.2	Chemical stability:		-	-						
	Chemically stable under the	e conditions of storage, h	andling and use.							
10.3	Possibility of hazardous	0,1	5							
	Under the specified condition		that lead to excessive tem	peratures or pressure are r	not expected.					
10.4	•	,		F	····					
	Applicable for handling and	storage at room temper	ature:							
	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity					
	Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable					
10.5	Incompatible materials:	1								
	Acids	Water	Combustive materials	Combustible materials	Others					
	Not applicable	Not applicable	Avoid direct impact	Avoid direct impact	Not applicable					
10.6	Hazardous decomposition	on products:								





24-08

SECTION 10: STABILITY AND REACTIVITY (continue)

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

No experimental information is available on the product itself in relation to the toxicological properties. When performing the danger classification on corrosive or irritant effects the recommendations included in section 3.2.5 of Annex VI of Directive 67/548/EC, in paragraphs b) and c) of section 3 of article 6 of Directive 1999/45/EC and in section 3.2.3.3.5. of Annex I of CLP Regulation were taken into account.

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.

B- Inhalation:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes:

Produces skin inflammation.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

Exposure to this product can have adverse effects on the fetus. For more specific information on the possible health effects see section 2.

E- Sensitizing effects:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensibilizing effects. For more information see section 3.

F- Specific target organ toxicity (STOT)-time exposure:

Exposure in high concentrations can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion and in serious cases, loss of concentration.

G- Specific target organ toxicity (STOT)-repeated exposure:

Exposure in high concentrations can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion and in serious cases, loss of concentration.

H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification		ļ	Acute toxicity	
Toluene		LD50 oral	5580 mg/kg	Rat
CAS: 108-88-3		LD50 dermal	12124 mg/kg	Rat
EC: 203-625-9		LC50 inhalation	28,1 mg/L (4 h)	Rat
2-butanone		LD50 oral	4000 mg/kg	Rat
CAS: 78-93-3		LD50 dermal	6400 mg/kg	Rabbit
EC: 201-159-0		LC50 inhalation	23,5 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the ecotoxicological properties of the product itself is not available

12.1 Toxicity:





SECTION 12: ECOLOGICAL INFORMATION (continue)

Identification		Acute toxicity	Specie	Genus
Toluene	LC50	13 mg/L (96 h)	Carassius auratus	Fish
CAS: 108-88-3	EC50	11,5 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-625-9	EC50	125 mg/L (48 h)	Scenedesmus subspicatus	Alga
2-butanone	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
CAS: 78-93-3	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-159-0	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Alga

12.2 Persistence and degradability:

Identification	De	egradability	Biodegradability	
Toluene	BOD5	2.5 g O2/g	Concentration	100 mg/L
CAS: 108-88-3	COD	Non-applicable	Period	14 days
EC: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
2-butanone	BOD5	2.03 g O2/g	Concentration	Non-applicable
CAS: 78-93-3	COD	2.31 g O2/g	Period	20 days
EC: 201-159-0	BOD5/COD	0.88	% Biodegradable	89 %

12.3 Bioaccumulative potential:

Identification		Bio	Bioaccumulation potential	
Toluene		BCF	13	
CAS: 108-88-3		Pow Log	2,73	
EC: 203-625-9		Potential	Low	
2-butanone		BCF	3	
CAS: 78-93-3		Pow Log	0,29	
EC: 201-159-0		Potential	Low	

12.4 Mobility in soil:

Identification	Absorp	Absorption/desorption		Volatility	
Toluene	Кос	178	Henry	6,728E+2 Pa·m ³ /mol	
CAS: 108-88-3	Conclusion	Moderate	Dry soil	Yes	
EC: 203-625-9	Surface tension	27930 N/m (25 ℃)	Moist soil	Yes	
2-butanone	Кос	30	Henry	5,765E+0 Pa·m ³ /mol	
CAS: 78-93-3	Conclusion	Very High	Dry soil	Yes	
EC: 201-159-0	Surface tension	23960 N/m (25 ℃)	Moist soil	Yes	

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Directive 2008/98/EC)		
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances Dangerous			
Waste management (disposal and evaluation):				

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2000/532/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) $n^{0}1907/2006$ (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2000/532/EC: Commission Decision of 3 May 2000





		24-	0

SECTION 14: TRANSPO	RT INFORMATION				
Transport of dance	erous goods by land:				
• •	With regard to ADR 2013 and RID 2013:				
-	4.1 UN number:	UN1263			
	4.1 UN number: 4.2 UN proper shipping name:	PAINT RELATED MATERIAL			
	4.3 Transport hazard class(es):	3			
	Labels:	3			
14	4.4 Packing group:	II			
14	4.5 Dangerous for the	No			
	environment:				
1,	4.6 Special precautions for user Special regulations:	163, 640D, 650			
	Tunnel restriction code:	D/E			
	Physico-Chemical properties:	see section 9			
	Limited quantities:	5 L			
14	4.7 Transport in bulk according	Non-applicable			
	to Annex II of MARPOL 73/78 and the IBC Code:				
Transport of dance	jerous goods by sea:				
With regard to IMD					
-	4.1 UN number:	UN1263			
_	4.2 UN proper shipping name:	PAINT RELATED MATERIAL			
	4.3 Transport hazard class(es):	3			
	Labels:	3			
	4.4 Packing group:	II			
3 14	4.5 Dangerous for the environment:	No			
•	4.6 Special precautions for user				
1	Special regulations:	163, 944			
	EmS Codes:	F-E, S-E			
	Physico-Chemical properties:	see section 9			
	Limited quantities:	5 L			
14	4.7 Transport in bulk according to Annex II of MARPOL	Non-applicable			
	73/78 and the IBC Code:				
Transport of dang	Transport of dangerous goods by air:				
With regard to IATA	With regard to IATA/ICAO 2014:				
14	4.1 UN number:	UN1263			
14	4.2 UN proper shipping name:	PAINT RELATED MATERIAL			
	4.3 Transport hazard class(es):	3			
3	Labels:	3			
· · · · · · · · · · · · · · · · · · ·	4.4 Packing group: 4.5 Dangerous for the	II No			
1	environment:				
14	4.6 Special precautions for user				
	Physico-Chemical properties:	see section 9			
14	4.7 Transport in bulk according to Annex II of MARPOL	Non-applicable			
	73/78 and the IBC Code:				
	-,				

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable





SWAN Δ IA Λ YTIKO Π O Λ YOYPE Θ ANH Σ EXTRA - Uretahne thinner

extra 24-08

SECTION 15: REGULATORY INFORMATION (continue)

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Active substances for which a decision of non-inclusion onto Annex I (Regulation (EU) No 528/2012): Non-applicable

Regulation (EC) 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII, REACH):

Contains more than 0,1 % of Toluene by weight. The use of this product is prohibited in adhesives or spray paints for sale to the general public.

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

Non-applicable

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) Nº 1907/2006 (Regulation (EC) Nº 453/2010)

Modifications related to the previous security card which concerns the ways of managing risks. :

Non-applicable

Text of R-phrases considered in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

Directive 67/548/EC and Directive 1999/45/EC:

- R11: Highly flammable
- R36: Irritating to eyes
- R38: Irritating to skin

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation

- R63: Possible risk of harm to the unborn child
- R65: Harmful: may cause lung damage if swallowed
- R66: Repeated exposure may cause skin dryness or cracking
- R67: Vapours may cause drowsiness and dizziness

CLP Regulation (EC) nº 1272/2008:

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Lig. 2: H225 - Highly flammable liquid and vapour

Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure

STOT SE 3: H336 - May cause drowsiness or dizziness

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:





24-08

SECTION 16: OTHER INFORMATION (continue)

http://esis.jrc.ec.europa.eu http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

- ADR: European agreement concerning the international carriage of dangerous goods by road
- -IMDG: International maritime dangerous goods code
- -IATA: International Air Transport Association
- -ICAO: International Civil Aviation Organisation
- -COD: Chemical Oxygen Demand
- -BOD5: 5-day biochemical oxygen demand
- -BCF: Bioconcentration factor
- -LD50: Lethal Dose 50
- -CL50: Lethal Concentration 50
- -EC50: Effective concentration 50 -Log-POW: Octanol-water partition coefficient
- -Koc: Partition coefficient of organic carbon

The information contained in this security data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this security data sheet only refers to this product, which should not be used for needs other than those specified.