



**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** TEAK OIL SPRAY - Wood maintenance and protection (spray)  
24-43  
Distillates (petroleum), hydrotreated light
- CAS: 64742-47-8  
EC: 265-149-8  
Index: 649-422-00-2  
REACH: 01-2119484819-18-XXXX
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Decoration and protection of wood  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:** EVOCHEM S.A.  
Tzaverdella Place  
133 41 PHILI , ATTICA - GREECE  
Phone.: 0030 210 5590460 , 0030 210 5590155 -  
Fax: 0030 210 6254737 , 0030 210 5590244  
info@evochem.gr; vmergoupis@evochem.gr;  
sales@evochem.gr  
www.evochem.gr
- 1.4 Emergency telephone number:** National Poisoning Center 2107793777

**SECTION 2: HAZARDS IDENTIFICATION**

- 2.1 Classification of the substance or mixture:**  
**Directive 67/548/EC and Directive 1999/45/EC:**  
This product was classified in accordance with Directive 67/548/EC and Directive 1999/45/EC, adapting the requirements to Regulation (EC) n°1907/2006 (REACH regulation).  
F+: R12 - Extremely flammable  
Xi: R43 - May cause sensitisation by skin contact  
R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
- CLP Regulation (EC) n° 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.  
Acute Tox. 4: Acute toxicity, Category 4  
Aerosol 1: Pressurised container: May burst if heated.  
Aerosol 1: Flammable aerosols, Category 1  
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3  
Skin Sens. 1: Sensitisation, skin, Category 1
- 2.2 Label elements:**  
**Directive 67/548/EC and Directive 1999/45/EC:**  
In accordance with the legislation, the elements on the label are as follows:
-  **F+**  
Extremely flammable
-  **Xi**  
Irritant
- R Phrases:**  
R12: Extremely flammable  
R43: May cause sensitisation by skin contact  
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
- S Phrases:**  
S2: Keep out of the reach of children  
S23: Do not breathe vapour and spray  
S46: If swallowed, seek medical advice immediately and show this container or label  
S51: Use only in well-ventilated areas
- Supplementary information:**

- CONTINUED ON NEXT PAGE -

**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 2: HAZARDS IDENTIFICATION (continue)**

P96: 94/1/EC-Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use  
P97: 2008/47/EC-Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children  
P98: Not to be used in vessels with a total length of less than 25 metres or vessels used predominantly on inland navigation routes and lakes, nor in devices or equipment used in fish farming or the shellfishing

**Substances that contribute to the classification:**

Turpentine, oil (CAS: 8006-64-2)

**CLP Regulation (EC) n° 1272/2008:**

**Danger**



**Hazard statements:**

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled  
Aerosol 1: H229 - Pressurised container: May burst if heated  
Aerosol 1: H222 - Extremely flammable aerosol  
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects  
Skin Sens. 1: H317 - May cause an allergic skin reaction

**Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand  
P102: Keep out of reach of children  
P103: Read label before use  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P251: Do not pierce or burn, even after use  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P410+P412: Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F  
P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment

**Supplementary information:**

EUH208: Contains Butanone oxime, Turpentine, oil. May produce an allergic reaction

**Substances that contribute to the classification**

Xylene (mixture of isomers) (CAS: 1330-20-7); Turpentine, oil (CAS: 8006-64-2); 1,2,4-trimethylbenzene (CAS: 95-63-6)

**2.3 Other hazards:**

Non-applicable

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**Chemical description:** Solution based on solvents, mineral oils, glycol-ethers, preservatives and colourants.

**Components:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

| Identification   | Chemical name/Classification  | Concentration |
|--|---|---------------|
| CAS: 64742-47-8<br>EC: 265-149-8<br>Index: 649-422-00-2<br>REACH:01-2119484819-18-XXXX | <b>Distillates (petroleum), hydrotreated light</b> ATP CLP00  | 24 - <50 %    |
|  | Directive 67/548/EC Xn: R65   |               |
|  | Regulation 1272/2008 Asp. Tox. 1: H304 - Danger   |               |
| CAS: 1330-20-7<br>EC: 215-535-7<br>Index: 601-022-00-9<br>REACH:01-2119488216-32-XXXX  | <b>Xylene (mixture of isomers)</b> ATP CLP00  | 2,4 - <4,9 %  |
|  | Directive 67/548/EC Xi: R38; Xn: R20/21; R10  |               |
|  | Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning   |               |
| CAS: 8006-64-2<br>EC: 232-350-7<br>Index: 650-002-00-6<br>REACH:01-2119502456-45-XXXX  | <b>Turpentine, oil</b> ATP CLP00  | 0,9 - <2,4 %  |
|  | Directive 67/548/EC N: R51/53; Xi: R36/38, R43; Xn: R20/21/22, R65; R10   |               |
|  | Regulation 1272/2008 Acute Tox. 4: H302+H312+H332; Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger |               |
| CAS: 95-63-6<br>EC: 202-436-9<br>Index: 601-043-00-3<br>REACH:01-2119472135-42-XXXX    | <b>1,2,4-trimethylbenzene</b> ATP CLP00   | 0,9 - <2,4 %  |
|  | Directive 67/548/EC N: R51/53; Xi: R36/37/38; Xn: R20; R10  |               |
|  | Regulation 1272/2008 Acute Tox. 4: H332; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning                                |               |

- CONTINUED ON NEXT PAGE -

**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continue)**

| Identification   | Chemical name/Classification   | Concentration  |
|--|--|----------------|
| CAS: 108-67-8<br>EC: 203-604-4<br>Index: 601-025-00-5<br>REACH:01-2119463878-19-XXXX | <b>Mesitylene</b> ATP CLP00  | 0,9 - <2,4 %   |
|  | Directive 67/548/EC N: R51/53; Xi: R37; R10  |                |
|  | Regulation 1272/2008 Aquatic Chronic 2: H411; Flam. Liq. 3: H226; STOT SE 3: H335 - Warning              |                |
| CAS: 96-29-7<br>EC: 202-496-6<br>Index: 616-014-00-0<br>REACH:01-2119539477-28-XXXX  | <b>Butanone oxime</b> ATP CLP00  | 0,24 - <0,9 %  |
|  | Directive 67/548/EC Carc. Cat 3: R40; Xi: R41, R43; Xn: R21  |                |
|  | Regulation 1272/2008 Acute Tox. 4: H312; Carc. 2: H351; Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger    |                |
| CAS: 100-41-4<br>EC: 202-849-4<br>Index: 601-023-00-4<br>REACH:01-2119489370-35-XXXX | <b>Ethylbenzene</b> ATP ATP06  | 0,09 - <0,24 % |
|  | Directive 67/548/EC F: R11; Xn: R20, R48/20, R65   |                |
|  | Regulation 1272/2008 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger |                |
| CAS: 67-56-1<br>EC: 200-659-6<br>Index: 603-001-00-X<br>REACH:01-2119433307-44-XXXX  | <b>Methanol</b> ATP CLP00  | <0,09 %        |
|  | Directive 67/548/EC F: R11; T: R23/24/25, R39/23/24/25   |                |
|  | Regulation 1272/2008 Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger          |                |

To obtain more information on the risk of the substances consult sections 8, 11, 12 and 16.

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the MSDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of modifications on the skin (stinging, redness, rashes, blisters, ...), seek medical advice with this Security Data Sheet

**By eye contact:**

Rinse eyes thoroughly with luke warm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the MSDS of the product.

**By consumption:**

Do not induce vomiting, but if it does happen keep the head up to avoid inhalation. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES**

**5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit, ...) in accordance with Directive 89/654/EC.

**Additional provisions:**

- CONTINUED ON NEXT PAGE -

**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 5: FIREFIGHTING MEASURES (continue)**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertizing agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

Minimum Temp.: 5 °C  
Maximum Temp.: 35 °C  
Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

- CONTINUED ON NEXT PAGE -

**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the work environment

| Identification   | Environmental limits |                       |      |
|--|----------------------|-----------------------|------|
|  | IOELV (8h)           | IOELV (STEL)          | Year |
| Xylene (mixture of isomers)<br>CAS: 1330-20-7<br>EC: 215-535-7 | 50 ppm               | 221 mg/m <sup>3</sup> | 2014 |
|  | 100 ppm              | 442 mg/m <sup>3</sup> |      |
|  |                      |                       |      |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9        | 20 ppm               | 100 mg/m <sup>3</sup> | 2014 |
|  |                      |                       |      |
|  |                      |                       |      |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                 | 100 ppm              | 442 mg/m <sup>3</sup> | 2014 |
|  | 200 ppm              | 884 mg/m <sup>3</sup> |      |
|  |                      |                       |      |
| Methanol<br>CAS: 67-56-1<br>EC: 200-659-6                      | 200 ppm              | 260 mg/m <sup>3</sup> | 2014 |
|  |                      |                       |      |
|  |                      |                       |      |

**DNEL (Workers):**

| Identification   |            | Short exposure        |                       | Long exposure          |                        |
|--|------------|-----------------------|-----------------------|------------------------|------------------------|
|  |            | Systemic              | Local                 | Systemic               | Local                  |
| Xylene (mixture of isomers)<br>CAS: 1330-20-7<br>EC: 215-535-7 | Oral       | Non-applicable        | Non-applicable        | Non-applicable         | Non-applicable         |
|  | Dermal     | Non-applicable        | Non-applicable        | 180 mg/kg              | Non-applicable         |
|  | Inhalation | 289 mg/m <sup>3</sup> | 289 mg/m <sup>3</sup> | 77 mg/m <sup>3</sup>   | Non-applicable         |
| Turpentine, oil<br>CAS: 8006-64-2<br>EC: 232-350-7             | Oral       | Non-applicable        | Non-applicable        | Non-applicable         | Non-applicable         |
|  | Dermal     | Non-applicable        | Non-applicable        | 1,6 mg/kg              | Non-applicable         |
|  | Inhalation | Non-applicable        | Non-applicable        | 11,2 mg/m <sup>3</sup> | 0,77 mg/m <sup>3</sup> |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9        | Oral       | Non-applicable        | Non-applicable        | Non-applicable         | Non-applicable         |
|  | Dermal     | Non-applicable        | Non-applicable        | 16171 mg/kg            | Non-applicable         |
|  | Inhalation | 100 mg/m <sup>3</sup> | 100 mg/m <sup>3</sup> | 100 mg/m <sup>3</sup>  | 100 mg/m <sup>3</sup>  |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4                   | Oral       | Non-applicable        | Non-applicable        | Non-applicable         | Non-applicable         |
|  | Dermal     | Non-applicable        | Non-applicable        | 16171 mg/kg            | Non-applicable         |
|  | Inhalation | 100 mg/m <sup>3</sup> | 100 mg/m <sup>3</sup> | 100 mg/m <sup>3</sup>  | 100 mg/m <sup>3</sup>  |
| Butanone oxime<br>CAS: 96-29-7<br>EC: 202-496-6                | Oral       | Non-applicable        | Non-applicable        | Non-applicable         | Non-applicable         |
|  | Dermal     | 2,5 mg/kg             | Non-applicable        | 1,3 mg/kg              | Non-applicable         |
|  | Inhalation | Non-applicable        | Non-applicable        | 9 mg/m <sup>3</sup>    | 3,33 mg/m <sup>3</sup> |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                 | Oral       | Non-applicable        | Non-applicable        | Non-applicable         | Non-applicable         |
|  | Dermal     | Non-applicable        | Non-applicable        | 180 mg/kg              | Non-applicable         |
|  | Inhalation | Non-applicable        | 293 mg/m <sup>3</sup> | 77 mg/m <sup>3</sup>   | Non-applicable         |
| Methanol<br>CAS: 67-56-1<br>EC: 200-659-6                      | Oral       | Non-applicable        | Non-applicable        | Non-applicable         | Non-applicable         |
|  | Dermal     | 40 mg/kg              | Non-applicable        | 40 mg/kg               | Non-applicable         |
|  | Inhalation | 260 mg/m <sup>3</sup> | 260 mg/m <sup>3</sup> | 260 mg/m <sup>3</sup>  | 260 mg/m <sup>3</sup>  |

**DNEL (Population):**

| Identification   |            | Short exposure         |                        | Long exposure          |                        |
|--|------------|------------------------|------------------------|------------------------|------------------------|
|  |            | Systemic               | Local                  | Systemic               | Local                  |
| Xylene (mixture of isomers)<br>CAS: 1330-20-7<br>EC: 215-535-7 | Oral       | Non-applicable         | Non-applicable         | 1,6 mg/kg              | Non-applicable         |
|  | Dermal     | Non-applicable         | Non-applicable         | 108 mg/kg              | Non-applicable         |
|  | Inhalation | Non-applicable         | Non-applicable         | 14,8 mg/m <sup>3</sup> | Non-applicable         |
| Turpentine, oil<br>CAS: 8006-64-2<br>EC: 232-350-7             | Oral       | Non-applicable         | Non-applicable         | 0,57 mg/kg             | Non-applicable         |
|  | Dermal     | Non-applicable         | Non-applicable         | Non-applicable         | Non-applicable         |
|  | Inhalation | Non-applicable         | Non-applicable         | Non-applicable         | Non-applicable         |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9        | Oral       | Non-applicable         | Non-applicable         | 15 mg/kg               | Non-applicable         |
|  | Dermal     | Non-applicable         | Non-applicable         | 9512 mg/kg             | Non-applicable         |
|  | Inhalation | 29,4 mg/m <sup>3</sup> | 29,4 mg/m <sup>3</sup> | 29,4 mg/m <sup>3</sup> | 29,4 mg/m <sup>3</sup> |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4                   | Oral       | Non-applicable         | Non-applicable         | 15 mg/kg               | Non-applicable         |
|  | Dermal     | Non-applicable         | Non-applicable         | 9512 mg/kg             | Non-applicable         |
|  | Inhalation | 29,4 mg/m <sup>3</sup> | 29,4 mg/m <sup>3</sup> | 29,4 mg/m <sup>3</sup> | 29,4 mg/m <sup>3</sup> |

- CONTINUED ON NEXT PAGE -

**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)**

| Identification                                  |            | Short exposure       |                      | Long exposure         |                      |
|---|------------|----------------------|----------------------|-----------------------|----------------------|
|   |            | Systemic             | Local                | Systemic              | Local                |
| Butanone oxime<br>CAS: 96-29-7<br>EC: 202-496-6 | Oral       | Non-applicable       | Non-applicable       | Non-applicable        | Non-applicable       |
|   | Dermal     | 1,5 mg/kg            | Non-applicable       | 0,78 mg/kg            | Non-applicable       |
|   | Inhalation | Non-applicable       | Non-applicable       | 2,7 mg/m <sup>3</sup> | 2 mg/m <sup>3</sup>  |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4  | Oral       | Non-applicable       | Non-applicable       | 1,6 mg/kg             | Non-applicable       |
|   | Dermal     | Non-applicable       | Non-applicable       | Non-applicable        | Non-applicable       |
|   | Inhalation | Non-applicable       | Non-applicable       | 15 mg/m <sup>3</sup>  | Non-applicable       |
| Methanol<br>CAS: 67-56-1<br>EC: 200-659-6       | Oral       | 8 mg/kg              | Non-applicable       | 8 mg/kg               | Non-applicable       |
|   | Dermal     | 8 mg/kg              | Non-applicable       | 8 mg/kg               | Non-applicable       |
|   | Inhalation | 50 mg/m <sup>3</sup> | 50 mg/m <sup>3</sup> | 50 mg/m <sup>3</sup>  | 50 mg/m <sup>3</sup> |

**PNEC:**

| Identification   |              |                |                         |                |
|--|--------------|----------------|-------------------------|----------------|
| Xylene (mixture of isomers)<br>CAS: 1330-20-7<br>EC: 215-535-7 | STP          | 6,58 mg/L      | Fresh water             | 0,327 mg/L     |
|  | Soil         | 2,31 mg/kg     | Marine water            | 0,327 mg/L     |
|  | Intermittent | 0,327 mg/L     | Sediment (Fresh water)  | 12,46 mg/kg    |
|  | Oral         | Non-applicable | Sediment (Marine water) | 12,46 mg/kg    |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9        | STP          | 2,41 mg/L      | Fresh water             | 0,12 mg/L      |
|  | Soil         | 2,34 mg/kg     | Marine water            | 0,12 mg/L      |
|  | Intermittent | 0,12 mg/L      | Sediment (Fresh water)  | 13,56 mg/kg    |
|  | Oral         | Non-applicable | Sediment (Marine water) | 13,56 mg/kg    |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4                   | STP          | 2,02 mg/L      | Fresh water             | 0,101 mg/L     |
|  | Soil         | 1,34 mg/kg     | Marine water            | 0,101 mg/L     |
|  | Intermittent | 0,101 mg/L     | Sediment (Fresh water)  | 7,86 mg/kg     |
|  | Oral         | Non-applicable | Sediment (Marine water) | 7,86 mg/kg     |
| Butanone oxime<br>CAS: 96-29-7<br>EC: 202-496-6                | STP          | 177 mg/L       | Fresh water             | 0,256 mg/L     |
|  | Soil         | Non-applicable | Marine water            | Non-applicable |
|  | Intermittent | 0,118 mg/L     | Sediment (Fresh water)  | Non-applicable |
|  | Oral         | Non-applicable | Sediment (Marine water) | Non-applicable |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                 | STP          | 9,6 mg/L       | Fresh water             | 0,1 mg/L       |
|  | Soil         | 2,68 mg/kg     | Marine water            | 0,01 mg/L      |
|  | Intermittent | 0,1 mg/L       | Sediment (Fresh water)  | 13,7 mg/kg     |
|  | Oral         | 20 g/kg        | Sediment (Marine water) | 1,37 mg/kg     |
| Methanol<br>CAS: 67-56-1<br>EC: 200-659-6                      | STP          | 100 mg/L       | Fresh water             | 154 mg/L       |
|  | Soil         | 23,5 mg/kg     | Marine water            | 15,4 mg/L      |
|  | Intermittent | 1540 mg/L      | Sediment (Fresh water)  | 570,4 mg/kg    |
|  | Oral         | Non-applicable | Sediment (Marine water) | Non-applicable |

**8.2 Exposure controls:**

**A.- General security and hygiene measures in the work place**

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the professional exposure limits. In case of using individual protection equipment they should have the "CE marking" in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**

| Pictogram | PPE  | Labelling | CEN Standard                               | Remarks   |
|-----------|--|-----------|--|---|
|           | Filter mask for gases, vapours and particles |           | EN 149:2001+A1:2009<br>EN 405:2001+A1:2009 | Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected. |



**C.- Specific protection for the hands**

- CONTINUED ON NEXT PAGE -





**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**





**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)**

| Pictogram  | PPE                                       | Labelling   | CEN Standard  | Remarks  |
|--|---|---|---|--|
| <br>Mandatory hand protection | NON-disposable chemical protective gloves |  | EN 374-1:2003<br>EN 374-3:2003/AC:2006<br>EN 420:2003+A1:2009 | The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. |



D.- Ocular and facial protection

| Pictogram  | PPE       | Labelling   | CEN Standard  | Remarks   |
|--|-----------|---|---|---|
| <br>Mandatory face protection | Face mask |  | EN 166:2001<br>EN 167:2001<br>EN 168:2001<br>EN 172:1994/A1:2000<br>EN 172:1994/A2:2001<br>EN ISO 4007:2012 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Bodily protection

| Pictogram   | PPE   | Labelling  | CEN Standard  | Remarks   |
|---|---|--|---|---|
| <br>Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties |   | EN 1149-1,2,3<br>EN 13034:2005+A1:2009<br>EN ISO 13982-1:2004/A1:2010<br>EN ISO 6529:2001<br>EN ISO 6530:2005<br>EN ISO 13688:2013<br>EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
| <br>Mandatory foot protection         | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties |  | EN 13287:2008<br>EN ISO 20345:2011<br>EN 13832-1:2006<br>EN ISO 20344:2011  | Replace boots at any sign of deterioration.   |

F.- Additional emergency measures

| Emergency measure   | Standards                      | Emergency measure  | Standards                     |
|---|--------------------------------|--|-------------------------------|
| <br>Emergency shower | ANSI Z358-1<br>ISO 3864-1:2002 | <br>Eyewash stations | DIN 12 899<br>ISO 3864-1:2002 |

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatil organic compounds:**

With regard to Directive 1999/13/EC, this product has the following characteristics:

V.O.C. (Supply): 74,85 % weight  
V.O.C. density at 20 °C: 650 kg/m<sup>3</sup> (650 g/L)  
Average carbon number: 11,37  
Average molecular weight: 164,76 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 650 kg/m<sup>3</sup> (650 g/L)  
EUlimit for the product (Cat. B.E): 840 g/L (2010)  
Components: Non-applicable

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continue)**

Physical state at 20 °C: Aerosol  
Appearance: Transparent  
Color: Not available  
Odor: Characteristic

**Volatility:**

Boiling point at atmospheric pressure: -42 °C (Propellant)  
Vapour pressure at 20 °C: Non-applicable \*  
Vapour pressure at 50 °C: <300000 Pa (300 kPa)  
Evaporation rate at 20 °C: Non-applicable \*

**Product description:**

Density at 20 °C: Non-applicable \*  
Relative density at 20 °C: Non-applicable \*  
Dynamic viscosity at 20 °C: Non-applicable \*  
Kinematic viscosity at 20 °C: Non-applicable \*  
Kinematic viscosity at 40 °C: Non-applicable \*  
Concentration: 800 - 820 g/L (active ingredient)  
pH: Non-applicable \*  
Vapour density at 20 °C: Non-applicable \*  
Partition coefficient n-octanol/water 20 °C: Non-applicable \*  
Solubility in water at 20 °C: Non-applicable \*  
Solubility property: Non-applicable \*  
Decomposition temperature: Non-applicable \*  
Melting point/freezing point: Non-applicable \*  
Recipient pressure: Non-applicable \*

**Flammability:**

Flash Point: -104 °C (Propellant)  
Autoignition temperature: 410 °C (Propellant)  
Lower flammability limit: Non-applicable \*  
Upper flammability limit: Non-applicable \*

**9.2 Other information:**

Surface tension at 20 °C: Non-applicable \*  
Refraction index: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected if the following technical instructions storage of chemicals. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight            | Humidity       |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable     | Not applicable   | Risk of combustion      | Avoid direct impact | Not applicable |

- CONTINUED ON NEXT PAGE -



**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 10: STABILITY AND REACTIVITY (continue)**

**10.5 Incompatible materials:**

| Acids          | Water          | Combustive materials | Combustible materials | Others         |
|----------------|----------------|----------------------|-----------------------|----------------|
| Not applicable | Not applicable | Avoid direct impact  | Avoid direct impact   | Not applicable |

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion:

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.

B- Inhalation:

Exposure in high concentrations can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion and in serious cases, loss of concentration.

C- Contact with the skin and the eyes:

Above all, may have harmful effects for health if the product is absorbed through the skin. For more information on the secondary effects of contact with the skin see section 2.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.

E- Sensitizing effects:

Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT)-time exposure:

Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous as a result of a single exposure. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

| Identification   | Acute toxicity  |               | Genus  |
|--|-----------------|---------------|--------|
|  | LD50 oral       | LD50 dermal   |        |
| Turpentine, oil<br>CAS: 8006-64-2<br>EC: 232-350-7             | LD50 oral       | 500 mg/kg     | Rat    |
|  | LD50 dermal     | 1100 mg/kg    | Rat    |
|  | LC50 inhalation | 11 mg/L (4 h) | Rat    |
| Xylene (mixture of isomers)<br>CAS: 1330-20-7<br>EC: 215-535-7 | LD50 oral       | 2100 mg/kg    | Rat    |
|  | LD50 dermal     | 1100 mg/kg    | Rat    |
|  | LC50 inhalation | 11 mg/L (4 h) | Rat    |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9        | LD50 oral       | 3400 mg/kg    | Rat    |
|  | LD50 dermal     | 3160 mg/kg    | Rabbit |
|  | LC50 inhalation | 11 mg/L (4 h) | Rat    |
| Ethylbenzene   | LD50 oral       | 3500 mg/kg    | Rat    |

- CONTINUED ON NEXT PAGE -

**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 11: TOXICOLOGICAL INFORMATION (continue)**

| Identification                                  | Acute toxicity  |                 | Genus  |
|---|-----------------|-----------------|--------|
|   | LD50            | LC50            |        |
| CAS: 100-41-4<br>EC: 202-849-4                  | LD50 dermal     | 15354 mg/kg     | Rabbit |
|   | LC50 inhalation | 17,2 mg/L (4 h) | Rat    |
| Butanone oxime<br>CAS: 96-29-7<br>EC: 202-496-6 | LD50 oral       | 2100 mg/kg      | Rat    |
|   | LD50 dermal     | 1100 mg/kg      | Rat    |
|   | LC50 inhalation | Non-applicable  |        |
| Methanol<br>CAS: 67-56-1<br>EC: 200-659-6       | LD50 oral       | 100 mg/kg       | Rat    |
|   | LD50 dermal     | 300 mg/kg       | Rabbit |
|   | LC50 inhalation | 3 mg/L (4 h)    | Rat    |

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the ecotoxicological properties of the product itself is not available

**12.1 Toxicity:**

| Identification   | Acute toxicity |                    | Specie                  | Genus      |
|--|----------------|--------------------|-------------------------|------------|
|  | LC50           | EC50               |                         |            |
| Xylene (mixture of isomers)<br>CAS: 1330-20-7<br>EC: 215-535-7 | LC50           | 13,5 mg/L (96 h)   | Oncorhynchus mykiss     | Fish       |
|  | EC50           | 0,6 mg/L (96 h)    | Gammarus lacustris      | Crustacean |
|  | EC50           | 10 mg/L (72 h)     | Skeletonema costatum    | Alga       |
| Turpentine, oil<br>CAS: 8006-64-2<br>EC: 232-350-7             | LC50           | 1 - 10 mg/L (96 h) |                         | Fish       |
|  | EC50           | 1 - 10 mg/L        |                         | Crustacean |
|  | EC50           | 1 - 10 mg/L        |                         | Alga       |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9        | LC50           | 7,72 mg/L (96 h)   | Pimephales promelas     | Fish       |
|  | EC50           | 6,14 mg/L (48 h)   | Daphnia magna           | Crustacean |
|  | EC50           | Non-applicable     |                         |            |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4                   | LC50           | 12,5 mg/L (96 h)   | Carassius auratus       | Fish       |
|  | EC50           | 50 mg/L (24 h)     | Daphnia magna           | Crustacean |
|  | EC50           | 53 mg/L (48 h)     | Scenedesmus subspicatus | Alga       |
| Butanone oxime<br>CAS: 96-29-7<br>EC: 202-496-6                | LC50           | 843 mg/L (96 h)    | Pimephales promelas     | Fish       |
|  | EC50           | 750 mg/L (48 h)    | Daphnia magna           | Crustacean |
|  | EC50           | 83 mg/L (72 h)     | Scenedesmus subspicatus | Alga       |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                 | LC50           | 42,3 mg/L (96 h)   | Pimephales promelas     | Fish       |
|  | EC50           | 75 mg/L (48 h)     | Daphnia magna           | Crustacean |
|  | EC50           | 63 mg/L (3 h)      | Chlorella vulgaris      | Alga       |
| Methanol<br>CAS: 67-56-1<br>EC: 200-659-6                      | LC50           | 15400 mg/L (96 h)  | Lepomis macrochirus     | Fish       |
|  | EC50           | 12000 mg/L (96 h)  | Nitrocras spinipes      | Crustacean |
|  | EC50           | 530 mg/L (168 h)   | Microcystis aeruginosa  | Alga       |

**12.2 Persistence and degradability:**

| Identification  | Degradability |                | Biodegradability |          |
|---|---------------|----------------|------------------|----------|
|   | BOD5          | COD            | Concentration    | Period   |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9 | BOD5          | Non-applicable | Concentration    | 100 mg/L |
|   | COD           | Non-applicable | Period           | 28 days  |
|   | BOD5/COD      | 0.43           | % Biodegradable  | 18 %     |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4            | BOD5          | Non-applicable | Concentration    | 100 mg/L |
|   | COD           | Non-applicable | Period           | 14 days  |
|   | BOD5/COD      | Non-applicable | % Biodegradable  | 0 %      |
| Butanone oxime<br>CAS: 96-29-7<br>EC: 202-496-6         | BOD5          | Non-applicable | Concentration    | 100 mg/L |
|   | COD           | Non-applicable | Period           | 28 days  |
|   | BOD5/COD      | Non-applicable | % Biodegradable  | 24 %     |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4          | BOD5          | Non-applicable | Concentration    | 100 mg/L |
|   | COD           | Non-applicable | Period           | 14 days  |
|   | BOD5/COD      | Non-applicable | % Biodegradable  | 90 %     |
| Methanol<br>CAS: 67-56-1<br>EC: 200-659-6               | BOD5          | Non-applicable | Concentration    | 100 mg/L |
|   | COD           | 1.42 g O2/g    | Period           | 14 days  |
|   | BOD5/COD      | Non-applicable | % Biodegradable  | 92 %     |

- CONTINUED ON NEXT PAGE -

**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 12: ECOLOGICAL INFORMATION (continue)**

**12.3 Bioaccumulative potential:**

| Identification  | Bioaccumulation potential |       |
|---|---------------------------|-------|
| Distillates (petroleum), hydrotreated light<br>CAS: 64742-47-8<br>EC: 265-149-8 | BCF                       | 130   |
|   | Pow Log                   | 3,3   |
|   | Potential                 | High  |
| Xylene (mixture of isomers)<br>CAS: 1330-20-7<br>EC: 215-535-7                  | BCF                       | 9     |
|   | Pow Log                   | 2,77  |
|   | Potential                 | Low   |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9                         | BCF                       | 154   |
|   | Pow Log                   | 3,78  |
|   | Potential                 | High  |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4                                    | BCF                       | 182   |
|   | Pow Log                   | 3,42  |
|   | Potential                 | High  |
| Butanone oxime<br>CAS: 96-29-7<br>EC: 202-496-6                                 | BCF                       | 5     |
|   | Pow Log                   | 0,59  |
|   | Potential                 | Low   |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                                  | BCF                       | 1     |
|   | Pow Log                   | 3,15  |
|   | Potential                 | Low   |
| Methanol<br>CAS: 67-56-1<br>EC: 200-659-6                                       | BCF                       | 3     |
|   | Pow Log                   | -0,77 |
|   | Potential                 | Low   |

**12.4 Mobility in soil:**

| Identification   | Absorption/desorption |                   | Volatility |                                 |
|--|-----------------------|-------------------|------------|---------------------------------|
| Xylene (mixture of isomers)<br>CAS: 1330-20-7<br>EC: 215-535-7 | Koc                   | 202               | Henry      | 5,249E+2 Pa·m <sup>3</sup> /mol |
|  | Conclusion            | Moderate          | Dry soil   | Yes                             |
|  | Surface tension       | Non-applicable    | Moist soil | Yes                             |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9        | Koc                   | 537               | Henry      | 6,242E+2 Pa·m <sup>3</sup> /mol |
|  | Conclusion            | Low               | Dry soil   | Yes                             |
|  | Surface tension       | 29190 N/m (25 °C) | Moist soil | Yes                             |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4                   | Koc                   | 1445              | Henry      | 8,886E+2 Pa·m <sup>3</sup> /mol |
|  | Conclusion            | Low               | Dry soil   | Yes                             |
|  | Surface tension       | 28050 N/m (25 °C) | Moist soil | Yes                             |
| Butanone oxime<br>CAS: 96-29-7<br>EC: 202-496-6                | Koc                   | 3                 | Henry      | Non-applicable                  |
|  | Conclusion            | Very High         | Dry soil   | Non-applicable                  |
|  | Surface tension       | 25700 N/m (25 °C) | Moist soil | Non-applicable                  |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                 | Koc                   | 520               | Henry      | 7,984E+2 Pa·m <sup>3</sup> /mol |
|  | Conclusion            | Moderate          | Dry soil   | Yes                             |
|  | Surface tension       | 28590 N/m (25 °C) | Moist soil | Yes                             |
| Methanol<br>CAS: 67-56-1<br>EC: 200-659-6                      | Koc                   | Non-applicable    | Henry      | Non-applicable                  |
|  | Conclusion            | Non-applicable    | Dry soil   | Non-applicable                  |
|  | Surface tension       | 23550 N/m (25 °C) | Moist soil | Non-applicable                  |

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

| Code      | Description   | Waste class (Directive 2008/98/EC) |
|-----------|---|------------------------------------|
| 16 05 04* | Gases in pressure containers (including halons) containing dangerous substances | Dangerous                          |

- CONTINUED ON NEXT PAGE -

**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 13: DISPOSAL CONSIDERATIONS (continue)**

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2000/532/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2000/532/EC: Commission Decision of 3 May 2000

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2013 and RID 2013:



- |   |                     |
|---|---------------------|
| <b>14.1 UN number:</b>  | UN1950              |
| <b>14.2 UN proper shipping name:</b>  | AEROSOLS, flammable |
| <b>14.3 Transport hazard class(es):</b>   | 2                   |
| Labels:   | 2.1                 |
| <b>14.4 Packing group:</b>  | N/A                 |
| <b>14.5 Dangerous for the environment:</b>  | No                  |
| <b>14.6 Special precautions for user</b>  |                     |
| Special regulations:  | 190, 327, 625       |
| Tunnel restriction code:  | D                   |
| Physico-Chemical properties:  | see section 9       |
| Limited quantities:   | 1 L                 |
| <b>14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:</b> | Non-applicable      |

**Transport of dangerous goods by sea:**

With regard to IMDG 36-12:



- |   |                     |
|---|---------------------|
| <b>14.1 UN number:</b>  | UN1950              |
| <b>14.2 UN proper shipping name:</b>  | AEROSOLS, flammable |
| <b>14.3 Transport hazard class(es):</b>   | 2                   |
| Labels:   | 2.1                 |
| <b>14.4 Packing group:</b>  | N/A                 |
| <b>14.5 Dangerous for the environment:</b>  | No                  |
| <b>14.6 Special precautions for user</b>  |                     |
| Special regulations:  | Non-applicable      |
| EmS Codes:  | F-D, S-U            |
| Physico-Chemical properties:  | see section 9       |
| Limited quantities:   | 1 L                 |
| <b>14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:</b> | Non-applicable      |

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2014:

- CONTINUED ON NEXT PAGE -

**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 14: TRANSPORT INFORMATION (continue)**



|   |                     |
|---|---------------------|
| <b>14.1 UN number:</b>  | UN1950              |
| <b>14.2 UN proper shipping name:</b>  | AEROSOLS, flammable |
| <b>14.3 Transport hazard class(es):</b>   | 2                   |
| Labels:   | 2.1                 |
| <b>14.4 Packing group:</b>  | N/A                 |
| <b>14.5 Dangerous for the environment:</b>  | No                  |
| <b>14.6 Special precautions for user</b>  |                     |
| Physico-Chemical properties:  | see section 9       |
| <b>14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:</b> | Non-applicable      |

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable  
Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable  
Active substances for which a decision of non-inclusion onto Annex I (Regulation (EU) No 528/2012): Non-applicable  
Regulation (EC) 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII, REACH):**

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

**Other legislation:**

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009, 2009 No. 716  
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (CDG 2009), SI 2009 No 1348  
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011, 2011 No. 1885  
Control of Substances Hazardous to Health Regulations 2002 (as amended)  
EH40/2005 Workplace exposure limits  
The Waste Regulations 2011, 2011 No. 988  
Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers  
Commission Directive 94/1/EC of 6 January 1994 adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of the relating Member States to aerosol dispensers  
Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers  
Commission Directive 2013/10/EU of 19 March 2013 amending Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION**

- CONTINUED ON NEXT PAGE -

**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 16: OTHER INFORMATION (continue)**

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EC) N° 453/2010)

**Modifications related to the previous security card which concerns the ways of managing risks. :**

CLP Regulation (EC) n° 1272/2008:

- Hazard statements

**Text of R-phrases considered in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**Directive 67/548/EC and Directive 1999/45/EC:**

- R10: Flammable
- R11: Highly flammable
- R20: Harmful by inhalation
- R20/21: Harmful by inhalation and in contact with skin
- R20/21/22: Harmful by inhalation, in contact with skin and if swallowed
- R21: Harmful in contact with skin
- R23/24/25: Toxic by inhalation, in contact with skin and if swallowed
- R36/37/38: Irritating to eyes, respiratory system and skin
- R36/38: Irritating to eyes and skin
- R37: Irritating to respiratory system
- R38: Irritating to skin
- R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed
- R40: Limited evidence of a carcinogenic effect
- R41: Risk of serious damage to eyes
- R43: May cause sensitisation by skin contact
- R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation
- R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
- R65: Harmful: may cause lung damage if swallowed

**CLP Regulation (EC) n° 1272/2008:**

- Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled
- Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled
- Acute Tox. 4: H312 - Harmful in contact with skin
- Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled
- Acute Tox. 4: H332 - Harmful if inhaled
- Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects
- Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways
- Carc. 2: H351 - Suspected of causing cancer
- Eye Dam. 1: H318 - Causes serious eye damage
- Eye Irrit. 2: H319 - Causes serious eye irritation
- Flam. Liq. 2: H225 - Highly flammable liquid and vapour
- Flam. Liq. 3: H226 - Flammable liquid and vapour
- Skin Irrit. 2: H315 - Causes skin irritation
- Skin Sens. 1: H317 - May cause an allergic skin reaction
- STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure
- STOT SE 1: H370 - Causes damage to organs
- STOT SE 3: H335 - May cause respiratory irritation

**Advice related to training:**

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

- <http://esis.jrc.ec.europa.eu>
- <http://echa.europa.eu>
- <http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

- CONTINUED ON NEXT PAGE -





**TEAK OIL SPRAY - Wood maintenance and protection (spray)**  
**24-43**

**SECTION 16: OTHER INFORMATION (continue)**

- ADR: European agreement concerning the international carriage of dangerous goods by road
- IMDG: International maritime dangerous goods code
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organisation
- COD: Chemical Oxygen Demand
- BOD5: 5-day biochemical oxygen demand
- BCF: Bioconcentration factor
- LD50: Lethal Dose 50
- CL50: Lethal Concentration 50
- EC50: Effective concentration 50
- Log-POW: Octanol–water partition coefficient
- Koc: Partition coefficient of organic carbon

The information contained in this security data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this security data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -