

**X-TRA FOAM ADAPTER
24-07-7**

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** X-TRA FOAM ADAPTER
24-07-7
- Other means of identification:**
- UFI:** 4MW0-T056-700P-3ADY
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
 Relevant uses (Consumer use): Adhesive for binding
 Relevant uses (Professional users): Adhesive for binding
 Relevant uses (Industrial user): Adhesive for binding
 Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
 Evochem S.A.
 Tzavardella Place
 133 41 Phili - Attica - Greece
 Phone: 0030 210 5590460 , 0030 210 5590155 - Fax: 0030 210 6254737 , 0030 210 5590244
 info@evochem.gr
 http://www.evochem.gr
- 1.4 Emergency telephone number:** National Poisoning Center 2107793777 (Greece), 1401 (Cyprus)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
- CLP Regulation (EC) No 1272/2008:**
 Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
 Acute Tox. 4: Acute inhalation toxicity, Category 4, H332
 Aerosol 1: Flammable aerosols, Category 1, H222
 Aerosol 1: Pressurised container: May burst if heated., H229
 Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
 Carc. 2: Carcinogenicity, Category 2, H351
 Eye Irrit. 2: Eye irritation, Category 2, H319
 Lact.: Reproductive toxicity, effects on or via lactation, H362
 Resp. Sens. 1: Sensitisation, respiratory, Category 1, H334
 Skin Irrit. 2: Skin irritation, Category 2, H315
 Skin Sens. 1: Sensitisation, skin, Category 1, H317
 STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2, H373
 STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
- 2.2 Label elements:**
- CLP Regulation (EC) No 1272/2008:**
 Danger
- 


- Hazard statements:**
 Acute Tox. 4: H332 - Harmful if inhaled.
 Aerosol 1: H222 - Extremely flammable aerosol.
 Aerosol 1: H229 - Pressurised container: May burst if heated.
 Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
 Carc. 2: H351 - Suspected of causing cancer (Inhalation).
 Eye Irrit. 2: H319 - Causes serious eye irritation.
 Lact.: H362 - May cause harm to breast-fed children.
 Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 Skin Irrit. 2: H315 - Causes skin irritation.
 Skin Sens. 1: H317 - May cause an allergic skin reaction.
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
 STOT SE 3: H335 - May cause respiratory irritation.
- Precautionary statements:**

- CONTINUED ON NEXT PAGE -

X-TRA FOAM ADAPTER
24-07-7**SECTION 2: HAZARDS IDENTIFICATION (continued)**

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

EUH204: Contains isocyanates. May produce an allergic reaction.

Additional Labelling:

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.
As from 24 August 2023 adequate training is required before industrial or professional use.

UFI: 4MW0-T056-700P-3ADY

2.3 Other hazards:

Product contains PBT/vPvB substances: Alkanes, C14-17, chloro
Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Substance:**

Not relevant

3.2 Mixture:

Chemical description: Aqueous solution based on anionic polymers and preservatives.

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 9016-87-9 EC: 618-498-9 Index: Not relevant REACH: Not relevant	4,4'-methylenediphenyl diisocyanate, isomers and homologues⁽¹⁾	Self-classified	24 - <50 %
	Regulation 1272/2008	Acute Tox. 4: H332; Carc. 2: H351; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335 - Danger	
CAS: 115-10-6 EC: 204-065-8 Index: 603-019-00-8 REACH: 01-2119472128-37-XXXX	Dimethyl ether⁽²⁾	ATP CLP00	9,9 - <19 %
	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	
CAS: 85535-85-9 EC: 287-477-0 Index: 602-095-00-X REACH: 01-2119519269-33-XXXX	Alkanes, C14-17, chloro⁽¹⁾	ATP ATP01	9,9 - <19 %
	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Lact.: H362; EUH066 - Warning	
CAS: 68647-60-9 EC: 271-960-8 Index: Not relevant REACH: Not relevant	Hydrocarbons, C>-4⁽¹⁾	Self-classified	9,9 - <19 %
	Regulation 1272/2008	Asp. Tox. 1: H304 - Danger	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	% (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319 % (w/w) >=0,1: Resp. Sens. 1 - H334 % (w/w) >=5: STOT SE 3 - H335

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

- CONTINUED ON NEXT PAGE -

X-TRA FOAM ADAPTER
24-07-7

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Acute toxicity		Genus
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	LD50 oral	Not relevant	
	LD50 dermal	Not relevant	
	LC50 inhalation vapour	11 mg/L	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

- CONTINUED ON NEXT PAGE -

**X-TRA FOAM ADAPTER
24-07-7**

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Keep away from sources of ignition, heat, open flame, or hot surfaces. No smoking. Close the valve after each use and when it has been emptied. Replace all valve protections as soon as the container has been disconnected from the equipment. Use appropriate means to move bottles: do not drag them, roll them, make them fall, etc. Avoid back-suction of water into the container. Avoid feedback into the container. Purge air from the system before introducing the gas. Use only equipment with the appropriate specifications, which are suitable for this product, as well as its supply temperature and pressure. In case of doubt, contact your gas supplier. Ensure adequate ventilation. Use the necessary personal protective equipment. Ensure the existence and implementation of safe work procedures and comply with the safe handling procedures for chemicals. Comply with the essential safety requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum provisions for the protection of the safety and health of workers under the criteria of choice of Directive 1999/92/EC (ATEX 137). See section 10 for conditions and materials to be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 35 °C

Maximum time: 12 Months

B.- General conditions for storage

- CONTINUED ON NEXT PAGE -

X-TRA FOAM ADAPTER
24-07-7

SECTION 7: HANDLING AND STORAGE (continued)

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)	1000 ppm	1920 mg/m³
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	IOELV (STEL)		

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	0,1 mg/m³	Not relevant	0,05 mg/m³
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	1894 mg/m³	Not relevant
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	47,9 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	6,7 mg/m³	Not relevant

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	0,05 mg/m³	Not relevant	0,025 mg/m³
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	471 mg/m³	Not relevant
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	Oral	Not relevant	Not relevant	0,58 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	28,75 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	2 mg/m³	Not relevant

PNEC:

Identification					
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	STP	1 mg/L	Fresh water		1 mg/L
	Soil	1 mg/kg	Marine water		0,1 mg/L
	Intermittent	10 mg/L	Sediment (Fresh water)		Not relevant
	Oral	Not relevant	Sediment (Marine water)		Not relevant
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	STP	160 mg/L	Fresh water		0,155 mg/L
	Soil	0,045 mg/kg	Marine water		0,016 mg/L
	Intermittent	1,549 mg/L	Sediment (Fresh water)		0,681 mg/kg
	Oral	Not relevant	Sediment (Marine water)		0,069 mg/kg

- CONTINUED ON NEXT PAGE -

X-TRA FOAM ADAPTER
24-07-7
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	STP	80 mg/L	Fresh water	0,001 mg/L
	Soil	11,9 mg/kg	Marine water	0,0002 mg/L
	Intermittent	Not relevant	Sediment (Fresh water)	13 mg/kg
	Oral	0,01 g/kg	Sediment (Marine water)	2,6 mg/kg

8.2 Exposure controls:
A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.
All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: AX)		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 UNE-EN ISO 18526-1 al 4:2020 UNE-EN ISO 18526-1 al 4:2020 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2005/A1:2011 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1995	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2022 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

- CONTINUED ON NEXT PAGE -

X-TRA FOAM ADAPTER
24-07-7

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container.
For more detailed information, please refer to subsection 7.1.D.

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	9,9 % weight
V.O.C. density at 20 °C:	Not relevant
Average carbon number:	Not relevant
Average molecular weight:	Not relevant

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Undefined
Colour:	 Beige
Odour:	Not relevant *
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	-25 °C
Vapour pressure at 20 °C:	Not relevant *
Vapour pressure at 50 °C:	<300000 Pa (300 kPa)
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	Not relevant *
Relative density at 20 °C:	Not relevant *
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	Not relevant *
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

Flammability:

Flash Point:	-41 °C
--------------	--------

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

X-TRA FOAM ADAPTER
24-07-7

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Flammability (solid, gas):	Not relevant *
Autoignition temperature:	240 °C
Lower flammability limit:	Not relevant *
Upper flammability limit:	Not relevant *

Particle characteristics:

Median equivalent diameter:	Not relevant *
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Precaution	Precaution	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- CONTINUED ON NEXT PAGE -

X-TRA FOAM ADAPTER
24-07-7

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
IARC: 4,4'-methylenediphenyl diisocyanate, isomers and homologues (3); Alkanes, C14-17, chloro (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: May cause harm to breast-fed children

E- Sensitizing effects:

- Respiratory: Prolonged exposure can result in specific respiratory hypersensitivity.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	LD50 oral		
	LD50 dermal		
	LC50 inhalation gases	4500 mg/L	
	LC50 inhalation vapour	11 mg/L	
	LC50 inhalation dust	1,5 mg/L	
	LC50 inhalation mist	1,5 mg/L	
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	LD50 oral		
	LD50 dermal		
	LC50 inhalation gases	164000 ppm (4 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

- CONTINUED ON NEXT PAGE -

X-TRA FOAM ADAPTER
24-07-7**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:**Acute toxicity:**

Identification	Concentration	Species	Genus
Alkanes, C14-17, chloro	LC50 >0.1 - 1 mg/L (96 h)		Fish
CAS: 85535-85-9	EC50 >0.1 - 1 mg/L (48 h)		Crustacean
EC: 287-477-0	EC50 >0.1 - 1 mg/L (72 h)		Algae

12.2 Persistence and degradability:

Not relevant

12.3 Bioaccumulative potential:

Not relevant

12.4 Mobility in soil:

Identification	Absorption/desorption	Volatility
Dimethyl ether	Koc Not relevant	Henry Not relevant
CAS: 115-10-6	Conclusion Not relevant	Dry soil Not relevant
EC: 204-065-8	Surface tension 1,136E-2 N/m (25 °C)	Moist soil Not relevant

12.5 Results of PBT and vPvB assessment:

Product contains PBT/vPvB substances: Alkanes, C14-17, chloro

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP7 Carcinogenic, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION**Transport of dangerous goods by land:**

With regard to ADR 2023 and RID 2023:

- CONTINUED ON NEXT PAGE -

X-TRA FOAM ADAPTER
24-07-7

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN1133
14.2 UN proper shipping name: ADHESIVES
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: I
14.5 Environmental hazards: No
14.6 Special precautions for user
 Special regulations: Not relevant
 Tunnel restriction code: D/E
 Physico-Chemical properties: see section 9
 Limited quantities: 500 mL
14.7 Maritime transport in bulk according to IMO instruments: Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:



- 14.1 UN number or ID number:** UN1133
14.2 UN proper shipping name: ADHESIVES
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: I
14.5 Marine pollutant: Yes
14.6 Special precautions for user
 Special regulations: Not relevant
 EmS Codes: F-E, S-D
 Physico-Chemical properties: see section 9
 Limited quantities: 500 mL
 Segregation group: Not relevant
14.7 Maritime transport in bulk according to IMO instruments: Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



- 14.1 UN number or ID number:** UN1133
14.2 UN proper shipping name: ADHESIVES
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: I
14.5 Environmental hazards: Yes
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Maritime transport in bulk according to IMO instruments: Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): *Alkanes, C14-17, chloro (85535-85-9)*
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

- CONTINUED ON NEXT PAGE -

X-TRA FOAM ADAPTER
24-07-7

SECTION 15: REGULATORY INFORMATION (continued)

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains more than 0.1 % of 4,4'-methylenediphenyl diisocyanate, isomers and homologues by weight. This product may not be distributed in its present form for first-time sale to the general public after 27th December 2010 unless the packaging contains protective gloves meeting the provisions of Regulation (EU) 2016/425.

Contains more than 0.1 % of diisocyanates by weight. 1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s).

2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use".

3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks.

4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum:

(a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s).

(b) the training elements in points (a) and (b) of paragraph 5 for the following uses:

- handling open mixtures at ambient temperature (including foam tunnels)
- spraying in a ventilated booth
- application by roller
- application by brush
- application by dipping and pouring
- mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore
- cleaning and waste
- any other uses with similar exposure through the dermal and/or inhalation route

(c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:

- handling incompletely cured articles (e.g. freshly cured, still warm)
- foundry applications
- maintenance and repair that needs access to equipment
- open handling of warm or hot formulations (> 45 °C)
- spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers)
- and any other uses with similar exposure through the dermal and/or inhalation route.

5. Training elements:

(a) general training, including on-line training, on:

- chemistry of diisocyanates
- toxicity hazards (including acute toxicity)
- exposure to diisocyanates
- occupational exposure limit values
- how sensitisation can develop
- odour as indication of hazard
- importance of volatility for risk
- viscosity, temperature, and molecular weight of diisocyanates
- personal hygiene
- personal protective equipment needed, including practical instructions for its correct use and its limitations
- risk of dermal contact and inhalation exposure

- CONTINUED ON NEXT PAGE -

**X-TRA FOAM ADAPTER
24-07-7**

SECTION 15: REGULATORY INFORMATION (continued)

- risk in relation to application process used
- skin and inhalation protection scheme
- ventilation
- cleaning, leakages, maintenance
- discarding empty packaging
- protection of bystanders
- identification of critical handling stages
- specific national code systems (if applicable)
- behaviour-based safety
- certification or documented proof that training has been successfully completed
- (b) intermediate level training, including on-line training, on:
 - additional behaviour-based aspects
 - maintenance
 - management of change
 - evaluation of existing safety instructions
 - risk in relation to application process used
 - certification or documented proof that training has been successfully completed
- (c) advanced training, including on-line training, on:
 - any additional certification needed for the specific uses covered
 - spraying outside a spraying booth
 - open handling of hot or warm formulations (> 45 °C)
 - certification or documented proof that training has been successfully completed
- 6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture(s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.
- 7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.
- 8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.
- 9. Member States shall include in their reports pursuant to Article 117(1) the following information:
 - (a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law
 - (b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates
 - (c) national exposure limits for diisocyanates, if there are any
 - (d) information about enforcement activities related to this restriction.
- 10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Not relevant

Texts of the legislative phrases mentioned in section 2:

- CONTINUED ON NEXT PAGE -

X-TRA FOAM ADAPTER
24-07-7

SECTION 16: OTHER INFORMATION (continued)

H222: Extremely flammable aerosol.
H332: Harmful if inhaled.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317: May cause an allergic skin reaction.
H362: May cause harm to breast-fed children.
H335: May cause respiratory irritation.
H373: May cause damage to organs through prolonged or repeated exposure.
H412: Harmful to aquatic life with long lasting effects.
H229: Pressurised container: May burst if heated.
H351: Suspected of causing cancer (Inhalation).

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H332 - Harmful if inhaled.
Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Carc. 2: H351 - Suspected of causing cancer.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Gas 1A: H220 - Extremely flammable gas.
Lact.: H362 - May cause harm to breast-fed children.
Press. Gas: H280 - Contains gas under pressure, may explode if heated.
Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

Aerosol 1: Calculation method
Acute Tox. 4: Calculation method
Skin Irrit. 2: Calculation method
Eye Irrit. 2: Calculation method
Resp. Sens. 1: Calculation method
Skin Sens. 1: Calculation method
Lact.: Calculation method
STOT SE 3: Calculation method
STOT RE 2: Calculation method
Aquatic Chronic 3: Calculation method
Aerosol 1: Calculation method
Carc. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

**X-TRA FOAM ADAPTER
24-07-7****SECTION 16: OTHER INFORMATION (continued)**

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -