

EPOXY PUTTY epoxy adhesive and putty

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier** EPOXY PUTTY**1.2. Relevant identified uses of the substance or mixture and uses advised against****Identified uses** Two component epoxy based adhesive.**1.3. Details of the supplier of the safety data sheet**EVOCHEM S.A.
Tzaverdella Place
133 41 PHILI , ATTICA
Phone.: 0030 210 5590460 , 0030 210 5590155
Fax: 0030 210 6254737 , 0030 210 5590244
info@evochem.gr; vmergoupis@evochem.gr;
sales@evochem.gr
www.evochem.gr**1.4. Emergency telephone number:** National Poisoning Center 2107793777**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification (EC 1272/2008)****Physical hazards** Not Classified**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317**Environmental hazards** Aquatic Chronic 3 - H412**Human health** May cause skin sensitisation or allergic reactions in sensitive individuals.**2.2. Label elements****Pictogram****Signal word** Warning**Hazard statements**
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

EPOXY PUTTY epoxy adhesive and putty

Precautionary statements	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	EPOXY RESIN (Number average MW ≤ 700), POLY[OXY(METHYL-1,2-ETHANEDIYL)], A-HYDRO-ω-HYDROXY-, ETHER WITH 2,2-BIS(HYDROXYMETHYL)-1,3-PROPANEDIOL (4:1), 2-HYDROXY-3-MERCAPTOPROPYL ETHER
Supplementary precautionary statements	<p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p>

2.3. Other hazards**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

TALC		20-50%
CAS number: 14807-96-6	EC number: 238-877-9	REACH registration number: 01-2120140278-58
Classification Not Classified		
EPOXY RESIN (Number average MW ≤ 700)		20-50%
CAS number: 25068-38-6	EC number: 500-033-5	REACH registration number: 01-2119456619-26
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411		
AMORPHOUS SODA LIME GLASS		20-50%
CAS number: 65997-17-3	EC number: 266-046-0	REACH registration number: 01-2119990048-30
Classification Not Classified		

<p>POLY[OXY(METHYL-1,2-ETHANEDIYL)], A-HYDRO-ω-HYDROXY-, ETHER WITH 2,2-BIS(HYDROXYMETHYL)-1,3-PROPANEDIOL (4:1), 2-HYDROXY-3-MERCAPTOPROPYL ETHER</p>			5-10%
CAS number: 72244-98-5	EC number: 615-735-8	REACH registration number: 01-2120118957-46	
<p>Classification Skin Sens. 1B - H317 Aquatic Chronic 3 - H412</p>			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove affected person from source of contamination. Get medical attention if any discomfort continues.
Ingestion	DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Wash skin thoroughly with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	No specific symptoms known.
Ingestion	May cause discomfort.
Skin contact	Causes skin irritation. May cause sensitisation or allergic reactions in sensitive individuals.
Eye contact	Irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Water spray, foam, dry powder or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Specific hazards	No unusual fire or explosion hazards noted.
Hazardous combustion products	Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting	No specific firefighting precautions known.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions No special storage precautions required.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

TALC

Long-term exposure limit (8-hour TWA): WEL 1 mg/m³ respirable dust

AMORPHOUS SODA LIME GLASS

Long-term exposure limit (8-hour TWA): 5 mg/m³ dust

WEL = Workplace Exposure Limit

EPOXY RESIN (Number average MW <= 700) (CAS: 25068-38-6)

DNEL	Industry - Inhalation; Long term systemic effects: 12.25 mg/m ³ Industry - Inhalation; Short term systemic effects: 12.25 mg/m ³ Industry - Dermal; Long term systemic effects: 8.33 mg/kg/day Industry - Dermal; Short term systemic effects: 8.33 mg/kg/day REACH dossier information
PNEC	- Fresh water; 0.006 mg/l - marine water; 0.0006 mg/l - Intermittent release; 0.018 mg/l - STP; 10 mg/l - Sediment (Freshwater); 0.996 mg/kg - Sediment (Marinewater); 0.0996 mg/kg - Soil; 0.196 mg/kg REACH dossier information

8.2. Exposure controls

Protective equipment



Appropriate engineering controls	No specific ventilation requirements.
Eye/face protection	Wear eye protection.
Hand protection	Wear protective gloves.
Hygiene measures	Wash promptly if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet.
Respiratory protection	No specific recommendations.
Environmental exposure controls	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Solid. Coloured paste.
Colour	Grey. Black.
Odour	Characteristic. Sulphur.
Odour threshold	Not determined.
pH	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	>35°C @ 760 mm Hg
Flash point	>100°C
Evaporation rate	Not applicable.
Evaporation factor	Not applicable.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	<500 Pa @ 20°C
Vapour density	Not applicable.
Relative density	2.25
Bulk density	Not applicable.
Solubility(ies)	Insoluble in water
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not applicable.
Explosive properties	Not applicable.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Avoid contact with the following materials: Acids.

10.5. Incompatible materials

Materials to avoid Acids. Amines.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin sensitisation

Skin sensitisation Sensitising.

Ingestion May cause discomfort.

Skin contact Irritating to skin. May cause sensitisation by skin contact.

Eye contact Irritation of eyes and mucous membranes.

Route of exposure Skin and/or eye contact.

Toxicological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Acute toxicity - oral

Acute toxicity oral (LD₅₀) 11,400.0
mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀) 1,200.0
mg/kg)

Species Rat

SECTION 12: Ecological information

12.1. Toxicity

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Acute aquatic toxicity

EPOXY PUTTY epoxy adhesive and putty

Acute toxicity - fish	LC50, 96 hours: 2 mg/l, Oncorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 1.8 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 11 mg/l, Freshwater algae EC ₅₀ , 96 hours: 220 mg/l, Scenedesmus subspicatus
Chronic aquatic toxicity	
Chronic toxicity - aquatic invertebrates	NOEC, 21 days: 0.3 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is not biodegradable.

Ecological information on ingredients.**EPOXY RESIN (Number average MW <= 700)**

Biodegradation - 12% Degradation (%): 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.**EPOXY RESIN (Number average MW <= 700)**

Bioaccumulative potential May accumulate in soil and water systems. BCF: 100 - 3000,

Partition coefficient log Pow: 3.242 Estimated Value

12.4. Mobility in soil

Mobility The product is insoluble in water and will spread on the water surface. The product is non-volatile. Semi-mobile.

Ecological information on ingredients.**EPOXY RESIN (Number average MW <= 700)**

Mobility Semi-mobile.

Adsorption/desorption coefficient Water - Koc: 1800 - 4400 @ 25°C Estimated Value

Henry's law constant 4.93E-05 Pa m³/mol @ 25°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.**EPOXY RESIN (Number average MW <= 700)**

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Disposal methods	Dispose of waste via a licensed waste disposal contractor.
Waste class	The waste code classification is to be carried out according to the European Waste Catalogue (EWC).

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU legislation	(EU) No 2015/830
Guidance	Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	15/05/2018
Version number	1.002
Supersedes date	12/02/2018
SDS number	20653

Hazard statements in full

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.