

**STRIP & CLEAN - Paint remover for varnishes, lacquers and enamel paints - 24-40**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** STRIP & CLEAN - Paint remover for varnishes, lacquers and enamel paints - 24-40  
1,3-dioxolane
- CAS: 646-06-0  
EC: 211-463-5  
Index: 605-017-00-2  
REACH: 01-2119490744-29-XXXX
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Stripper  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:** EVOCHEM S.A.  
Tzaverdella Place  
133 41 PHILI , ATTICA - GREECE  
Phone.: 0030 210 5590460 , 0030 210 5590155 -  
Fax: 0030 210 6254737 , 0030 210 5590244  
info@evochem.gr; vmergoupis@evochem.gr;  
sales@evochem.gr  
www.evochem.gr
- 1.4 Emergency telephone number:** National Poisoning Center 2107793777

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1 Classification of the substance or mixture:**

**Directive 67/548/EC and Directive 1999/45/EC:**

This product was classified in accordance with Directive 67/548/EC and Directive 1999/45/EC, adapting the requirements to Regulation (EC) n°1907/2006 (REACH regulation).

F: R11 - Highly flammable

Xn: R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed

**CLP Regulation (EC) n° 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.

Flam. Liq. 2: Flammable liquids, Category 2

Skin Irrit. 2: Skin irritation, Category 2

**2.2 Label elements:**

**Directive 67/548/EC and Directive 1999/45/EC:**

In accordance with the legislation, the elements on the label are as follows:



Highly flammable



Harmful

**R Phrases:**

R11: Highly flammable

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed

**S Phrases:**

S16: Keep away from sources of ignition - No smoking

S2: Keep out of the reach of children

S43: In case of fire, use polyvalent powder ABC

S46: If swallowed, seek medical advice immediately and show this container or label

S9: Keep container in a well-ventilated place

**Supplementary information:**

Non-applicable

**Substances that contribute to the classification:**

Xylene (mixture of isomers) (CAS: 1330-20-7)

- CONTINUED ON NEXT PAGE -

**STRIP & CLEAN - Paint remover for varnishes, lacquers and enamel paints - 24-40**

**SECTION 2: HAZARDS IDENTIFICATION (continue)**

**CLP Regulation (EC) n° 1272/2008:**

Danger



**Hazard statements:**

Flam. Liq. 2: H225 - Highly flammable liquid and vapour  
Skin Irrit. 2: H315 - Causes skin irritation

**Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand  
P102: Keep out of reach of children  
P103: Read label before use  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.  
P403+P235: Store in a well-ventilated place. Keep cool  
P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment

**Supplementary information:**

EUH019: May form explosive peroxides

**2.3 Other hazards:**

Non-applicable

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**Chemical description:** Solvent/s

**Components:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 646-06-0 EC: 211-463-5 Index: 605-017-00-2 REACH:01-2119490744-29-XXXX	<b>1,3-dioxolane</b> ATP CLP00	50 - <75 %
	Directive 67/548/EC F: R11	
	Regulation 1272/2008 Flam. Liq. 2: H225 - Danger	
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH:01-2119488216-32-XXXX	<b>Xylene (mixture of isomers)</b> ATP CLP00	9,9 - <19 %
	Directive 67/548/EC Xi: R38; Xn: R20/21; R10	
	Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	
CAS: 67-56-1 EC: 200-659-6 Index: 603-001-00-X REACH:01-2119433307-44-XXXX	<b>Methanol</b> ATP CLP00	0,9 - <2,4 %
	Directive 67/548/EC F: R11; T: R23/24/25, R39/23/24/25	
	Regulation 1272/2008 Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger	

To obtain more information on the risk of the substances consult sections 8, 11, 12 and 16.

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the MSDS of this product.

**By inhalation:**

This product is not classified as dangerous through inhalation, however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

**By skin contact:**

**STRIP & CLEAN - Paint remover for varnishes, lacquers and enamel paints - 24-40**

**SECTION 4: FIRST AID MEASURES (continue)**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with luke warm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the MSDS of the product.

**By consumption:**

Do not induce vomiting, but if it does happen keep the head up to avoid inhalation. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES**

**5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive subproducts are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertizing agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**6.2 Environmental precautions:**

This product is not classified as dangerous to the environment. Keep product away from drains, surface and underground water.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

- CONTINUED ON NEXT PAGE -

**STRIP & CLEAN - Paint remover for varnishes, lacquers and enamel paints - 24-40**

**SECTION 7: HANDLING AND STORAGE (continue)**

**7.1 Precautions for safe handling:**

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

Minimum Temp.: 5 °C  
Maximum Temp.: 35 °C  
Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	Environmental limits		
	IOELV (8h)	IOELV (STEL)	Year
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	50 ppm	221 mg/m <sup>3</sup>	2014
	100 ppm	442 mg/m <sup>3</sup>	
Methanol CAS: 67-56-1 EC: 200-659-6	200 ppm	260 mg/m <sup>3</sup>	2014

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
1,3-dioxolane CAS: 646-06-0 EC: 211-463-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	4,1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	19 mg/m <sup>3</sup>	Non-applicable
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	289 mg/m <sup>3</sup>	289 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Non-applicable
Methanol CAS: 67-56-1 EC: 200-659-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	40 mg/kg	Non-applicable	40 mg/kg	Non-applicable
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>

- CONTINUED ON NEXT PAGE -

**STRIP & CLEAN - Paint remover for varnishes, lacquers and enamel paints - 24-40**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)**

**DNEL (Population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
1,3-dioxolane CAS: 646-06-0 EC: 211-463-5	Oral	Non-applicable	Non-applicable	75 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,8 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	5,7 mg/m <sup>3</sup>	Non-applicable
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14,8 mg/m <sup>3</sup>	Non-applicable
Methanol CAS: 67-56-1 EC: 200-659-6	Oral	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable
	Dermal	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable
	Inhalation	50 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>

**PNEC:**

Identification				
1,3-dioxolane CAS: 646-06-0 EC: 211-463-5	STP	1 mg/L	Fresh water	19,7 mg/L
	Soil	2,62 mg/kg	Marine water	1,97 mg/L
	Intermittent	0,95 mg/L	Sediment (Fresh water)	77,7 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,77 mg/kg
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Methanol CAS: 67-56-1 EC: 200-659-6	STP	100 mg/L	Fresh water	154 mg/L
	Soil	23,5 mg/kg	Marine water	15,4 mg/L
	Intermittent	1540 mg/L	Sediment (Fresh water)	570,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable

**8.2 Exposure controls:**

A.- General security and hygiene measures in the work place

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the professional exposure limits. In case of using individual protection equipment they should have the ""CE marking"" in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the professional exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Chemical protective gloves		EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	Replace the gloves at any sign of deterioration.

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Panoramic glasses against liquid splash		EN 166:2001 EN 172:1994/A1:2000 EN 172:1994/A2:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Bodily protection

- CONTINUED ON NEXT PAGE -

**STRIP & CLEAN - Paint remover for varnishes, lacquers and enamel paints - 24-40**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)**

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing		EN ISO 13688:2013	For professional use only.
	Anti-slip work shoes		EN ISO 20347:2012 EN ISO 20344:2011	None

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatil organic compounds:**

With regard to Directive 1999/13/EC, this product has the following characteristics:

V.O.C. (Supply):	92,65 % weight
V.O.C. density at 20 °C:	905,22 kg/m <sup>3</sup> (905,22 g/L)
Average carbon number:	3,87
Average molecular weight:	79,71 g/mol

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Color:	Yellowish
Odor:	Characteristic

**Volatility:**

Boiling point at atmospheric pressure:	71 °C
Vapour pressure at 20 °C:	14650 Pa
Vapour pressure at 50 °C:	50110 Pa (50 kPa)
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	977 kg/m <sup>3</sup>
Relative density at 20 °C:	0,977
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 cSt
Concentration:	1370 - 1430 g/L (active ingredient)
pH:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**STRIP & CLEAN - Paint remover for varnishes, lacquers and enamel paints - 24-40**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continue)**

Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility property:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

**Flammability:**

Flash Point:	7 °C
Autoignition temperature:	237 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

**9.2 Other information:**

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected if the following technical instructions storage of chemicals. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Combustive materials	Combustible materials	Others
Not applicable	Not applicable	Avoid direct impact	Avoid direct impact	Not applicable

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

No experimental information is available on the product itself in relation to the toxicological properties. When performing the danger classification on corrosive or irritant effects the recommendations included in section 3.2.5 of Annex VI of Directive 67/548/EC, in paragraphs b) and c) of section 3 of article 6 of Directive 1999/45/EC and in section 3.2.3.3.5. of Annex I of CLP Regulation were taken into account.

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion:

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.

- CONTINUED ON NEXT PAGE -

**STRIP & CLEAN - Paint remover for varnishes, lacquers and enamel paints - 24-40**

**SECTION 11: TOXICOLOGICAL INFORMATION (continue)**

**B- Inhalation:**

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

**C- Contact with the skin and the eyes:**

Produces skin inflammation.

**D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):**

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

**E- Sensitizing effects:**

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitizing effects. For more information see section 3.

**F- Specific target organ toxicity (STOT)-time exposure:**

Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous as a result of a single exposure. For more information see section 3.

**G- Specific target organ toxicity (STOT)-repeated exposure:**

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

**H- Aspiration hazard:**

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
1,3-dioxolane CAS: 646-06-0 EC: 211-463-5	LD50 oral	3000 mg/kg	Rat
	LD50 dermal	15000 mg/kg	Rat
	LC50 inhalation	20650 mg/L (4 h)	Rat
Methanol CAS: 67-56-1 EC: 200-659-6	LD50 oral	100 mg/kg	Rat
	LD50 dermal	300 mg/kg	Rabbit
	LC50 inhalation	3 mg/L (4 h)	Rat
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (4 h)	Rat

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the ecotoxicological properties of the product itself is not available

**12.1 Toxicity:**

Identification	Acute toxicity		Specie	Genus
	LC50	EC50		
1,3-dioxolane CAS: 646-06-0 EC: 211-463-5	LC50	12000 mg/L (96 h)	Cyprionodon variegatus	Fish
	EC50	6500 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	LC50	13,5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	0,6 mg/L (96 h)	Gammarus lacustris	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Alga
Methanol CAS: 67-56-1 EC: 200-659-6	LC50	15400 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	12000 mg/L (96 h)	Nitrocras spinipes	Crustacean
	EC50	530 mg/L (168 h)	Microcystis aeruginosa	Alga

**12.2 Persistence and degradability:**

- CONTINUED ON NEXT PAGE -

**STRIP & CLEAN - Paint remover for varnishes, lacquers and enamel paints - 24-40**

**SECTION 12: ECOLOGICAL INFORMATION (continue)**

Identification	Degradability		Biodegradability	
	Methanol CAS: 67-56-1 EC: 200-659-6	BOD5	Non-applicable	Concentration
	COD	1.42 g O2/g	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	92 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
	1,3-dioxolane CAS: 646-06-0 EC: 211-463-5	BCF
	Pow Log	-0,37
	Potential	Low
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2,77
	Potential	Low
Methanol CAS: 67-56-1 EC: 200-659-6	BCF	3
	Pow Log	-0,77
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
	1,3-dioxolane CAS: 646-06-0 EC: 211-463-5	Koc	15	Henry
	Conclusion	Very High	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	5,249E+2 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Methanol CAS: 67-56-1 EC: 200-659-6	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	23550 N/m (25 °C)	Moist soil	Non-applicable

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Directive 2008/98/EC)
07 06 04*	Other organic solvents, washing liquids and mother liquors	Dangerous

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2000/532/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2000/532/EC: Commission Decision of 3 May 2000

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2013 and RID 2013:

- CONTINUED ON NEXT PAGE -

**STRIP & CLEAN - Paint remover for varnishes, lacquers and enamel paints - 24-40**

**SECTION 14: TRANSPORT INFORMATION (continue)**



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT RELATED MATERIAL  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** II  
**14.5 Dangerous for the environment:** No  
**14.6 Special precautions for user**  
 Special regulations: 163, 640D, 650  
 Tunnel restriction code: D/E  
 Physico-Chemical properties: see section 9  
 Limited quantities: 5 L  
**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 36-12:



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT RELATED MATERIAL  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** II  
**14.5 Dangerous for the environment:** No  
**14.6 Special precautions for user**  
 Special regulations: 163, 944  
 EmS Codes: F-E, S-E  
 Physico-Chemical properties: see section 9  
 Limited quantities: 5 L  
**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2014:



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT RELATED MATERIAL  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** II  
**14.5 Dangerous for the environment:** No  
**14.6 Special precautions for user**  
 Physico-Chemical properties: see section 9  
**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Non-applicable

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Active substances for which a decision of non-inclusion onto Annex I (Regulation (EU) No 528/2012): Non-applicable

- CONTINUED ON NEXT PAGE -

**STRIP & CLEAN - Paint remover for varnishes, lacquers and enamel paints - 24-40**

**SECTION 15: REGULATORY INFORMATION (continue)**

Regulation (EC) 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII, REACH):**

Non-applicable

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

**Other legislation:**

Non-applicable

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EC) N° 453/2010)

**Modifications related to the previous security card which concerns the ways of managing risks. :**

COMPOSITION/INFORMATION ON INGREDIENTS:

- Added Content  
1,3-dioxolane (646-06-0)

**Text of R-phrases considered in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**Directive 67/548/EC and Directive 1999/45/EC:**

- R10: Flammable
- R11: Highly flammable
- R20/21: Harmful by inhalation and in contact with skin
- R23/24/25: Toxic by inhalation, in contact with skin and if swallowed
- R38: Irritating to skin
- R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed

**CLP Regulation (EC) n° 1272/2008:**

- Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled
- Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled
- Flam. Liq. 2: H225 - Highly flammable liquid and vapour
- Flam. Liq. 3: H226 - Flammable liquid and vapour
- Skin Irrit. 2: H315 - Causes skin irritation
- STOT SE 1: H370 - Causes damage to organs

**Advice related to training:**

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

- <http://esis.jrc.ec.europa.eu>
- <http://echa.europa.eu>
- <http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

- CONTINUED ON NEXT PAGE -



**STRIP & CLEAN - Paint remover for varnishes, lacquers and  
enamel paints -  
24-40**

**SECTION 16: OTHER INFORMATION (continue)**

- ADR: European agreement concerning the international carriage of dangerous goods by road
- IMDG: International maritime dangerous goods code
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organisation
- COD: Chemical Oxygen Demand
- BOD5: 5-day biochemical oxygen demand
- BCF: Bioconcentration factor
- LD50: Lethal Dose 50
- CL50: Lethal Concentration 50
- EC50: Effective concentration 50
- Log-POW: Octanol–water partition coefficient
- Koc: Partition coefficient of organic carbon

The information contained in this security data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this security data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -