

#### MINOS METALLIC PAINT SPRAY BLACK - Metallic paint spray 24-102

# mino*s*

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING 1.1 Product identifier: MINOS METALLIC PAINT SPRAY BLACK - Metallic paint spray 24-102 1.2 Relevant identified uses of the substance or mixture and uses advised against: Relevant uses: Spray paint Uses advised against: All uses not specified in this section or in section 7.3 1.3 **Details of the supplier of the safety data sheet:** EVOCHEM S.A. **Tzaverdella Place** 133 41 PHILI, ATTICA - GREECE Phone.: 0030 210 5590460 , 0030 210 5590155 Fax: 0030 210 6254737 , 0030 210 5590244 info@evochem.gr; vmergoupis@evochem.gr; sales@evochem.gr www.evochem.gr 1.4 Emergency telephone number: National Poisoning Center 2107793777 SECTION 2: HAZARDS IDENTIFICATION 2.1 Classification of the substance or mixture: CLP Regulation (EC) nº 1272/2008: Classification of this product has been carried out in accordance with CLP Regulation (EC) nº 1272/2008. Aerosol 1: Pressurised container: May burst if heated., H229 Aerosol 1: Flammable aerosols, Category 1, H222 Eye Irrit. 2: Eye irritation, Category 2, H319 Skin Irrit. 2: Skin irritation, Category 2, H315 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336 2.2 Label elements: CLP Regulation (EC) nº 1272/2008: Danger Hazard statements: Aerosol 1: H229 - Pressurized container: May burst if heated Aerosol 1: H222 - Extremely flammable aerosol Eye Irrit. 2: H319 - Causes serious eye irritation Skin Irrit. 2: H315 - Causes skin irritation STOT SE 3: H336 - May cause drowsiness or dizziness **Precautionary statements:** P101: If medical advice is needed, have product container or label at hand P102: Keep out of reach of children P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P211: Do not spray on an open flame or other ignition source

P251: Do not pierce or burn, even after use

P280: Wear protective gloves/protective clothing/eye protection/face protection

P410+P412: Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F

P501: Dispose of contents and / or their container according to the separated collection system used in your municipality

# Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking

# Substances that contribute to the classification

Acetone; N-butyl acetate

# 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

\*\* Changes with regards to the previous version



# MINOS METALLIC PAINT SPRAY BLACK - Metallic paint spray 24-102

# minos

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

Chemical description: Mixture composed of additives, pigments and resins in solvents

### Components:

In accordance with Annex II of Regulation (EC) nº1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentratio
CAS: 67-64-1	Acetone 1 ATP CLP00	
EC: 200-662-2 Index: 606-001-00-8 REACH 01-2119471330-49-XXX	Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	24 - <50 %
CAS: 1330-20-7	Xylene 1 ATP CLP00	
EC: 215-535-7 ndex: 601-022-00-9 REACH 01-2119488216-32-XXX	Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	9,9 - <19 9
CAS: 123-86-4	N-butyl acetate 1 ATP CLP00	
EC: 204-658-1 Index: 607-025-00-1 REACH 01-2119485493-29-XXX	Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	2,4 - <4,9 %
CAS: 100-41-4	Ethylbenzene 1 ATP ATP06	
EC: 202-849-4 Index: 601-023-00-4 REACH 01-2119489370-35-XXX	Regulation 1272/2008 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	0,9 - <2,4 %
CAS: 67-56-1	Methanol 1 ATP CLP00	
EC: 200-659-6 Index: 603-001-00-X REACH 01-2119433307-44-XXX	Regulation 1272/2008 Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger	0,24 - <0,9 %
CAS: 108-94-1	Cyclohexanone <sup>2</sup> ATP CLP00	
EC: 203-631-1 Index: 606-010-00-7 REACH 01-2119453616-35-XXX	Regulation 1272/2008   Acute Tox. 4: H332; Flam. Liq. 3: H226 - Warning	0,24 - <0,9 %
CAS: 95-63-6	1,2,4-trimethylbenzene <sup>2</sup> ATP CLP00	
EC: 202-436-9 Index: 601-043-00-3 REACH 01-2119472135-42-XXX	Regulation 1272/2008   Acute Tox. 4: H332; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Liq. 3:     H226; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning   Image: Comparison of C	0,09 - <0,2 %
CAS: 111-76-2	2-butoxyethanol <sup>2</sup> ATP CLP00	
EC: 203-905-0 Index: 603-014-00-0 REACH 01-2119475108-36-XXX	Regulation 1272/2008 Acute Tox. 4: H302+H312+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	<0,09 %
CAS: 108-67-8	Mesitylene <sup>2</sup> ATP CLP00	
EC: 203-604-4 Index: 601-025-00-5 REACH Non-applicable	Regulation 1272/2008 Aquatic Chronic 2: H411; Flam. Liq. 3: H226; STOT SE 3: H335 - Warning	<0,09 %
CAS: 98-82-8	Cumene 2 ATP CLP00	
EC: 202-704-5 Index: 601-024-00-X REACH 01-2119473983-24-XXX	Regulation 1272/2008   Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335 - Danger	<0,09 %
CAS: 71-43-2	Benzene <sup>2</sup> ATP CLP00	
EC: 200-753-7 Index: 601-020-00-8 REACH 01-2119496063-37-XXX	Regulation 1272/2008 Asp. Tox. 1: H304; Carc. 1A: H350; Eye Irrit. 2: H319; Flam. Liq. 2: H225; Muta. 1B: H340; Skin Irrit. 2: H315; STOT RE 1: H372 - Danger	<0,09 %

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

\*\* Changes with regards to the previous version

# SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. **By inhalation:** 





# SECTION 4: FIRST AID MEASURES (continued)

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

## By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

# By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

#### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### 6.2 Environmental precautions:

Avoid spillage into an aqueous medium as it contains substances potentially dangerous for this. Contain the product absorbed in hermetically sealed containers. In the case of serious spillage into an aqueous medium notify the relevant authority.

#### 6.3 Methods and material for containment and cleaning up:

#### It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:



MINOS METALLIC PAINT SPRAY BLACK - Metallic paint spray 24-102

#### SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

See sections 8 and 13.

#### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid projections and pulverizations. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

# 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:5 °CMaximum Temp.:35 °CMaximum time:12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification		Environmental lin	nits
Acetone	IOELV (8h)	500 ppm	1210 mg/m <sup>3</sup>
CAS: 67-64-1	IOELV (STEL)		
EC: 200-662-2	Year	2017	
Xylene	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
CAS: 1330-20-7	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
EC: 215-535-7	Year	2017	
Ethylbenzene	IOELV (8h)	100 ppm	442 mg/m <sup>3</sup>
CAS: 100-41-4	IOELV (STEL)	200 ppm	884 mg/m <sup>3</sup>
EC: 202-849-4	Year	2017	
Methanol	IOELV (8h)	200 ppm	260 mg/m <sup>3</sup>
CAS: 67-56-1	IOELV (STEL)		
EC: 200-659-6	Year	2017	
Cyclohexanone	IOELV (8h)	10 ppm	40.8 mg/m <sup>3</sup>
CAS: 108-94-1	IOELV (STEL)	20 ppm	81.6 mg/m <sup>3</sup>
EC: 203-631-1	Year	2017	
1,2,4-trimethylbenzene	IOELV (8h)	20 ppm	100 mg/m <sup>3</sup>
CAS: 95-63-6	IOELV (STEL)		
EC: 202-436-9	Year	2017	
2-butoxyethanol	IOELV (8h)	20 ppm	98 mg/m <sup>3</sup>
CAS: 111-76-2	IOELV (STEL)	50 ppm	246 mg/m <sup>3</sup>
EC: 203-905-0	Year	2017	
Mesitylene	IOELV (8h)	20 ppm	100 mg/m <sup>3</sup>



# MINOS METALLIC PAINT SPRAY BLACK - Metallic paint spray 24-102

# minos

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Environmental limit	ts
CAS: 108-67-8	IOELV (STEL)		
EC: 203-604-4	Year	2017	
Cumene	IOELV (8h)	20 ppm	100 mg/m <sup>3</sup>
CAS: 98-82-8	IOELV (STEL)	50 ppm	250 mg/m <sup>3</sup>
EC: 202-704-5	Year	2017	
Benzene	IOELV (8h)	1 ppm	3.25 mg/m <sup>3</sup>
CAS: 71-43-2	IOELV (STEL)		
EC: 200-753-7	Year	2017	

#### Short exposure Long exposure Identification Systemic Local Systemic Local Acetone Dral Non-applicable Non-applicable Non-applicable Non-applicable CAS: 67-64-1 Non-applicable Non-applicable 186 mg/kg Non-applicable )erma EC: 200-662-2 Non-applicable 2420 mg/m<sup>3</sup> 1210 mg/m<sup>3</sup> Non-applicable nhalation Xvlene Dral Non-applicable Non-applicable Non-applicable Non-applicable CAS: 1330-20-7 Dermal Non-applicable Non-applicable 180 mg/kg Non-applicable EC: 215-535-7 Inhalation 289 mg/m<sup>3</sup> 289 mg/m<sup>3</sup> 77 mg/m<sup>3</sup> Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable N-butyl acetate Oral CAS: 123-86-4 Dermal Non-applicable Non-applicable Non-applicable Non-applicable EC: 204-658-1 Inhalation 960 mg/m<sup>3</sup> 960 mg/m<sup>3</sup> 480 mg/m<sup>3</sup> 480 mg/m<sup>3</sup> Ethylbenzene )ral Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable 180 mg/kg Non-applicable CAS: 100-41-4 ) ern EC: 202-849-4 nhalation Non-applicable 293 mg/m<sup>3</sup> 77 mg/m<sup>3</sup> Non-applicable Methanol Dral Non-applicable Non-applicable Non-applicable Non-applicable CAS: 67-56-1 Dermal 40 mg/kg Non-applicable 40 mg/kg Non-applicable EC: 200-659-6 Inhalation 260 mg/m<sup>3</sup> 260 mg/m<sup>3</sup> 260 mg/m<sup>3</sup> 260 mg/m<sup>3</sup> Oral Non-applicable Non-applicable Non-applicable Non-applicable Cyclohexanone Non-applicable 4 mg/kg Non-applicable CAS: 108-94-1 Dermal 4 mg/kg EC: 203-631-1 80 ma/m<sup>3</sup> 40 ma/m³ 40 ma/m³ Inhalation $80 \text{ mg/m}^3$ 1,2,4-trimethylbenzene Oral Non-applicable Non-applicable Non-applicable Non-applicable CAS: 95-63-6 Non-applicable Non-applicable 16171 mg/kg Non-applicable EC: 202-436-9 halation 100 mg/m<sup>3</sup> 100 mg/m<sup>3</sup> 100 mg/m<sup>3</sup> 100 mg/m<sup>3</sup> 2-butoxyethanol Dral Non-applicable Non-applicable Non-applicable Non-applicable CAS: 111-76-2 Dermal 89 mg/kg Non-applicable 75 mg/kg Non-applicable EC: 203-905-0 Inhalation 663 mg/m<sup>3</sup> 246 mg/m<sup>3</sup> 98 mg/m<sup>3</sup> Non-applicable Mesitylene Oral Non-applicable Non-applicable Non-applicable Non-applicable CAS: 108-67-8 Dermal Non-applicable Non-applicable 16171 mg/kg Non-applicable EC: 203-604-4 Inhalation 100 mg/m<sup>3</sup> 100 mg/m<sup>3</sup> 100 mg/m<sup>3</sup> 100 mg/m<sup>3</sup> Cumene Oral Non-applicable Non-applicable Non-applicable Non-applicable CAS: 98-82-8 Non-applicable Non-applicable 15,4 mg/kg Non-applicable EC: 202-704-5 nhalation Non-applicable 250 mg/m<sup>3</sup> 100 mg/m<sup>3</sup> Non-applicable

#### DNEL (General population):

		Short	Short exposure		exposure
Identification		Systemic	Local	Systemic	Local
Acetone	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	Non-applicable	200 mg/m <sup>3</sup>	Non-applicable
Xylene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	Non-applicable	Non-applicable	14,8 mg/m <sup>3</sup>	Non-applicable
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-658-1	Inhalation	859,7 mg/m <sup>3</sup>	859,7 mg/m <sup>3</sup>	102,34 mg/m <sup>3</sup>	102,34 mg/m <sup>3</sup>



# MINOS METALLIC PAINT SPRAY BLACK - Metallic paint spray 24-102

# minos

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Lon	g exposure
Identification		Systemic	Local	Systemic	Local
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m <sup>3</sup>	Non-applicable
Methanol	Oral	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable
CAS: 67-56-1	Dermal	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable
EC: 200-659-6	Inhalation	50 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>
Cyclohexanone	Oral	1,5 mg/kg	Non-applicable	1,5 mg/kg	Non-applicable
CAS: 108-94-1	Dermal	1 mg/kg	Non-applicable	1 mg/kg	Non-applicable
EC: 203-631-1	Inhalation	20 mg/m <sup>3</sup>	40 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	20 mg/m <sup>3</sup>
1,2,4-trimethylbenzene	Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
CAS: 95-63-6	Dermal	Non-applicable	Non-applicable	9512 mg/kg	Non-applicable
EC: 202-436-9	Inhalation	29,4 mg/m <sup>3</sup>	29,4 mg/m <sup>3</sup>	29,4 mg/m <sup>3</sup>	29,4 mg/m <sup>3</sup>
2-butoxyethanol	Oral	13,4 mg/kg	Non-applicable	3,2 mg/kg	Non-applicable
CAS: 111-76-2	Dermal	44,5 mg/kg	Non-applicable	38 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	426 mg/m <sup>3</sup>	123 mg/m <sup>3</sup>	49 mg/m <sup>3</sup>	Non-applicable
Mesitylene	Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
CAS: 108-67-8	Dermal	Non-applicable	Non-applicable	9512 mg/kg	Non-applicable
EC: 203-604-4	Inhalation	29,4 mg/m <sup>3</sup>	29,4 mg/m <sup>3</sup>	29,4 mg/m <sup>3</sup>	29,4 mg/m <sup>3</sup>
Cumene	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
CAS: 98-82-8	Dermal	Non-applicable	Non-applicable	1,2 mg/kg	Non-applicable
EC: 202-704-5	Inhalation	Non-applicable	Non-applicable	16,6 mg/m <sup>3</sup>	Non-applicable
PNEC:					
Identification					
Acetone	STP	100 mg/L	Fresh water		10,6 mg/L
CAS: 67-64-1	Soil	29,5 mg/kg	Marine water		1,06 mg/L
EC: 200-662-2	Intermittent	21 mg/L	Sediment (Fresh		30,4 mg/kg
	Oral	Non-applicable	Sediment (Marin		3,04 mg/kg
Xylene	STP	6,58 mg/L	Fresh water		0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water		0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh		12,46 mg/kg
	Oral	Non-applicable	Sediment (Marin		12,46 mg/kg
N-butyl acetate	STP	35,6 mg/L	Fresh water		0,18 mg/L
CAS: 123-86-4	Soil	0,0903 mg/kg	Marine water		0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh		0,981 mg/kg
	Oral	Non-applicable	Sediment (Marin		0,0981 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water		0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water		0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh		13,7 mg/kg
	Oral	20 g/kg	Sediment (Marin		1,37 mg/kg
Methanol	STP	100 mg/L	Fresh water		154 mg/L
CAS: 67-56-1	Soil	23,5 mg/kg	Marine water		15,4 mg/L
EC: 200-659-6	Intermittent	1540 mg/L	Sediment (Fresh		570,4 mg/kg
	Oral	Non-applicable	Sediment (Marin		Non-applicable
Cyclohexanone	STP	10 mg/L	Fresh water		0,0329 mg/L
CAS: 108-94-1	Soil	0,0143 mg/kg	Marine water		0,00329 mg/L
EC: 203-631-1	Intermittent	0,329 mg/L	Sediment (Fresh		0,168 mg/kg
	Oral	Non-applicable	Sediment (Marin		0,0168 mg/kg
1,2,4-trimethylbenzene	STP	2,41 mg/L	Fresh water		0,12 mg/L
	511	2,12,119/1			
	Soil	2.34 ma/ka	Marine water		0.12 ma/l
CAS: 95-63-6 EC: 202-436-9	Soil Intermittent	2,34 mg/kg 0,12 mg/L	Marine water Sediment (Fresh		0,12 mg/L 13,56 mg/kg



# minos

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
2-butoxyethanol	STP	463 mg/L	Fresh water	8,8 mg/L
CAS: 111-76-2	Soil	3,13 mg/kg	Marine water	0,88 mg/L
EC: 203-905-0	Intermittent	9,1 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	Non-applicable
Mesitylene	STP	2,02 mg/L	Fresh water	0,101 mg/L
CAS: 108-67-8	Soil	1,34 mg/kg	Marine water	0,101 mg/L
EC: 203-604-4	Intermittent	0,101 mg/L	Sediment (Fresh water)	7,86 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,86 mg/kg
Cumene	STP	200 mg/L	Fresh water	0,035 mg/L
CAS: 98-82-8	Soil	0,624 mg/kg	Marine water	0,0035 mg/L
EC: 202-704-5	Intermittent	0,012 mg/L	Sediment (Fresh water)	3,22 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,322 mg/kg

### 8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	CAT III	EN 149:2001+A1:2009 EN 405:2001+A1:2009	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

#### C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves		EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application

#### D.- Ocular and facial protection

	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory face protection	Face mask		EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
E	Bodily protection				
	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6529:2005 EN ISO 13688:2013 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.



MINOS METALLIC PAINT SPRAY BLACK - Metallic paint spray 24-102

# minos

				l (continued)	
	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN 13287:2008 EN ISO 20345:2011 EN 13832-1:2006	Replace boots at any sign of deterioration.
I	F Additional emerge	ency measures			
	Emergency me		tandards	Emergency measur	e Standards
	Emergency sho	ISO 3	SI Z358-1 8864-1:2002	Eyewash stations	DIN 12 899 ISO 3864-1:2002
í	Environmental exp	osure controls:			
	V.O.C. (Supply): V.O.C. density at 20 C Average carbon numb Average molecular we With regard to Directi V.O.C. density at 20 C EUlimit for the produc	2010/75/EU, this produ 86,56 % weigh PC: 735,78 kg/m <sup>3</sup> per: 4,09 eight: 70,1 g/mol ive 2004/42/EC, this produ	t (735,78 g/L) ict which is ready (735,78 g/L)		characteristics:
9.1	Information on bas	ND CHEMICAL PROPE sic physical and chemic tion see the product datas	al properties:		
	Appearance:				
ľ	Physical state at 20 %	<b>C</b> .			
		C:	Aeroso	I	
	Appearance:	C:	Aeroso Not av		
	Appearance: Colour:		Not av		
(			Not av	ailable	
(	Colour:		Not av	ailable ack	
(	Colour: Odour:		Not av	ailable ack teristic	
	Colour: Odour: Odour threshold:		Not av Bla Charao Non-ap	ailable ack teristic	
	Colour: Odour: Odour threshold: Volatility:	spheric pressure:	Not av Bla Charac Non-ap -42 °C	ailable ack teristic oplicable *	
	Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmos	spheric pressure: 0 °C:	Not av Bla Charac Non-ap -42 °C Non-ap	ailable ack teristic oplicable * (Propellant)	
	Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmos Vapour pressure at 20	spheric pressure: 0 °C: 0 °C:	Not av ■ Bla Charac Non-ap -42 °C Non-ap <3000	ailable ack teristic oplicable * (Propellant) oplicable *	
	Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmos Vapour pressure at 20 Vapour pressure at 50	spheric pressure: 0 °C: 0 °C: 0 °C:	Not av ■ Bla Charac Non-ap -42 °C Non-ap <3000	ailable ack teristic oplicable * (Propellant) oplicable * 00 Pa (300 kPa)	
	Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmos Vapour pressure at 20 Vapour pressure at 50 Evaporation rate at 20	spheric pressure: 0 °C: 0 °C: 0 °C:	Not av ■ Bla Charac Non-ap -42 °C Non-ap <3000	ailable ack teristic oplicable * (Propellant) oplicable * 00 Pa (300 kPa) oplicable *	
	Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmos Vapour pressure at 20 Vapour pressure at 20 Evaporation rate at 20 <b>Product description</b>	spheric pressure: 0 °C: 0 °C: 0 °C: n:	Not av ■ Bla Charac Non-ap -42 °C Non-ap <3000 Non-ap 850 kg	ailable ack teristic oplicable * (Propellant) oplicable * 00 Pa (300 kPa) oplicable *	
	Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmos Vapour pressure at 20 Vapour pressure at 50 Evaporation rate at 20 <b>Product description</b> Density at 20 °C:	spheric pressure: 0 °C: 0 °C: 0 °C: n: 1 °C:	Not av Bla Charac Non-ap -42 °C Non-ap <3000 Non-ap 850 kg Non-ap	ailable ack teristic oplicable * (Propellant) oplicable * 00 Pa (300 kPa) oplicable *	
	Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmos Vapour pressure at 20 Vapour pressure at 20 <b>Product description</b> Density at 20 °C: Relative density at 20	spheric pressure: 0 °C: 0 °C: 0 °C: n: 1 °C: 20 °C:	Not av ■ Bla Charac Non-ap <3000 Non-ap 850 kg Non-ap Non-ap	ailable ack teristic oplicable * (Propellant) oplicable * 00 Pa (300 kPa) oplicable *	
	Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmos Vapour pressure at 20 Vapour pressure at 20 <b>Product description</b> Density at 20 °C: Relative density at 20 Dynamic viscosity at 2	spheric pressure:   0 °C:   0 °C:   0 °C:   1 °C:   2 °C:   2 °C:   2 °C:   2 °C:	Not av Bla Charac Non-ap <3000 Non-ap 850 kg Non-ap Non-ap Non-ap	ailable ack teristic oplicable * (Propellant) oplicable * 00 Pa (300 kPa) oplicable * (/m <sup>3</sup> oplicable * oplicable *	



# MINOS METALLIC PAINT SPRAY BLACK - Metallic paint spray

24-102

SECTION 9: PHYSICAL AND CHEMICAL PROPER	RTIES (continued)
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Recipient pressure:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Flammability:	
Flash Point:	-104 °C (Propellant)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	410 °C (Propellant)
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *
Explosive:	
Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *
9.2 Other information:	
Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *
*Not relevant due to the nature of the product, not providin	g information property of its hazards.

# SECTION 10: STABILITY AND REACTIVITY

# 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

#### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

# 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases. Can react violently

# **10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

# SECTION 11: TOXICOLOGICAL INFORMATION \*\*

\*\* Changes with regards to the previous version

minor



# **n**ino*s*

#### SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)

#### **11.1** Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. With possibility of effects that are hazardous to the health, it is recommended not to breathe the vapours for long periods of time.

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

- A.- Ingestion (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.

- Mutagenicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.

- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

# Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acı	te toxicity	Genus
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg (ATEi)	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (4 h) (ATEi)	



# MINOS METALLIC PAINT SPRAY BLACK - Metallic paint spray 24-102

# minos

# SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)

Identification		Acute toxicity	Gen
Ethylbenzene	LD50 oral	3500 mg/kg	Ra
CAS: 100-41-4	LD50 dermal	15354 mg/kg	Rat
EC: 202-849-4	LC50 inhalation	17,2 mg/L (4 h)	Ra
Methanol	LD50 oral	100 mg/kg	Ra
CAS: 67-56-1	LD50 dermal	300 mg/kg	Rat
EC: 200-659-6	LC50 inhalation	3 mg/L (4 h)	Ra
N-butyl acetate	LD50 oral	12789 mg/kg	Ra
CAS: 123-86-4	LD50 dermal	14112 mg/kg	Rab
EC: 204-658-1	LC50 inhalation	23,4 mg/L (4 h)	Ra
Acetone	LD50 oral	5800 mg/kg	Ra
CAS: 67-64-1	LD50 dermal	7426 mg/kg	Rat
EC: 200-662-2	LC50 inhalation	76 mg/L (4 h)	Ra
Cyclohexanone	LD50 oral	2650 mg/kg	Ra
CAS: 108-94-1	LD50 dermal	3160 mg/kg	Rat
EC: 203-631-1	LC50 inhalation	11 mg/L (4 h)	Ra
1,2,4-trimethylbenzene	LD50 oral	3400 mg/kg	Ra
CAS: 95-63-6	LD50 dermal	3160 mg/kg	Rat
EC: 202-436-9	LC50 inhalation	11 mg/L (4 h)	Ra
2-butoxyethanol	LD50 oral	500 mg/kg	Ra
CAS: 111-76-2	LD50 dermal	1100 mg/kg	Ra
EC: 203-905-0	LC50 inhalation	11 mg/L (4 h)	Ra
Mesitylene	LD50 oral	6000 mg/kg	Ra
CAS: 108-67-8	LD50 dermal	Non-applicable	
EC: 203-604-4	LC50 inhalation	Non-applicable	
Cumene	LD50 oral	2700 mg/kg	
CAS: 98-82-8	LD50 dermal	Non-applicable	
EC: 202-704-5	LC50 inhalation	Non-applicable	
Benzene	LD50 oral	2900 mg/kg	Ra
CAS: 71-43-2	LD50 dermal	8263 mg/kg	Rat
EC: 200-753-7	LC50 inhalation	44,45 mg/L (4 h)	Ra


\*\* Changes with regards to the previous version

# SECTION 12: ECOLOGICAL INFORMATION \*\*

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification		Acute toxicity	Species	Genus	
Acetone	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: 67-64-1	EC50	23.5 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 200-662-2	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae	
Xylene	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: 1330-20-7	EC50	0.6 mg/L (96 h)	Gammarus lacustris	Crustacean	
EC: 215-535-7	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae	
N-butyl acetate	LC50	62 mg/L (96 h)	Leuciscus idus	Fish	
CAS: 123-86-4	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean	
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae	
Ethylbenzene	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish	
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae	






# minos

# SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)

Identification		Acute toxicity	Species	Genus
Methanol	LC50	15400 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 67-56-1	EC50	12000 mg/L (96 h)	Nitrocra spinipes	Crustacean
EC: 200-659-6	EC50	530 mg/L (168 h)	Microcystis aeruginosa	Algae
Cyclohexanone	LC50	527 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-94-1	EC50	800 mg/L (24 h)	Daphnia magna	Crustacear
EC: 203-631-1	EC50	370 mg/L (192 h)	Scenedesmus quadricauda	Algae
1,2,4-trimethylbenzene	LC50	7.72 mg/L (96 h)	Pimephales promelas	Fish
CAS: 95-63-6	EC50	6.14 mg/L (48 h)	Daphnia magna	Crustacear
EC: 202-436-9	EC50	Non-applicable		
2-butoxyethanol	LC50	1490 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 111-76-2	EC50	1815 mg/L (48 h)	Daphnia magna	Crustacear
EC: 203-905-0	EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Mesitylene	LC50	12.5 mg/L (96 h)	Carassius auratus	Fish
CAS: 108-67-8	EC50	50 mg/L (24 h)	Daphnia magna	Crustacear
EC: 203-604-4	EC50	53 mg/L (48 h)	Scenedesmus subspicatus	Algae
Cumene	LC50	2.7 mg/L (96 h)	Salmo gairdneri	Fish
CAS: 98-82-8	EC50	10.8 mg/L (48 h)	Daphnia magna	Crustacear
EC: 202-704-5	EC50	2.6 mg/L (72 h)	Selenastrum capricornutum	Algae
Benzene	LC50	5.9 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 71-43-2	EC50	66 mg/L (24 h)	Artemia salina	Crustacear
EC: 200-753-7	EC50	29 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae

# 12.2 Persistence and degradability:

Identification	D	egradability	Biodegradability	
Acetone	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-64-1	COD	Non-applicable	Period	28 days
EC: 200-662-2	BOD5/COD	0.96	% Biodegradable	96 %
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	0.79	% Biodegradable	84 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
Methanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-56-1	COD	1.42 g O2/g	Period	14 days
EC: 200-659-6	BOD5/COD	Non-applicable	% Biodegradable	92 %
Cyclohexanone	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 108-94-1	COD	Non-applicable	Period	14 days
EC: 203-631-1	BOD5/COD	0.65	% Biodegradable	87 %
1,2,4-trimethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 95-63-6	COD	Non-applicable	Period	28 days
EC: 202-436-9	BOD5/COD	0.43	% Biodegradable	18 %
2-butoxyethanol	BOD5	0.71 g O2/g	Concentration	100 mg/L
CAS: 111-76-2	COD	2.2 g O2/g	Period	14 days
EC: 203-905-0	BOD5/COD	0.32	% Biodegradable	96 %
Mesitylene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 108-67-8	COD	Non-applicable	Period	14 days
EC: 203-604-4	BOD5/COD	Non-applicable	% Biodegradable	0 %
Cumene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 98-82-8	COD	Non-applicable	Period	14 days
EC: 202-704-5	BOD5/COD	Non-applicable	% Biodegradable	40 %







#### SECTION 12: ECOLOGICAL INFORMATION \*\* (continued) Identification Degradability Biodegradability Non-applicable 100 mg/L Benzene OD5 Concentration CAS: 71-43-2 COD Non-applicable 14 days EC: 200-753-7 OD5/COD Non-applicable 6 Biodegradable 40 % 12.3 Bioaccumulative potential: Identification Bioaccumulation potentia Acetone 1 BCF CAS: 67-64-1 ow Log -0.24 EC: 200-662-2 Potential Low Xvlene BCF 9 CAS: 1330-20-7 ow Loa 2.77 EC: 215-535-7 Potential Low N-butyl acetate CF 4 ow Log CAS: 123-86-4 1.78 EC: 204-658-1 Potentia Low Ethylbenzene BCF 1 CAS: 100-41-4 ow Log 3.15 EC: 202-849-4 Potentia Low Methanol BCF 3 CAS: 67-56-1 Pow Log -0.77 EC: 200-659-6 Potentia Low BCF Cyclohexanone CAS: 108-94-1 ow Loq 0.81 EC: 203-631-1 otentia Low 154 1,2,4-trimethylbenzene BCF CAS: 95-63-6 Pow Log 3.78 EC: 202-436-9 Potentia Hiah 2-butoxyethanol BCF 3 CAS: 111-76-2 Pow Log 0.83 EC: 203-905-0 Potentia Low BCF Mesitylene 182 CAS: 108-67-8 ow Loo 3.42 EC: 203-604-4 otentia High 120 Cumene BCF CAS: 98-82-8 3 66 ow Log EC: 202-704-5 Potentia Hiah Benzene BCF 4 CAS: 71-43-2 ow Log 2.13 EC: 200-753-7 Potential Low Mobility in soil: 12.4 Identification Absorption/desorption Volatility Acetone Henry 2,93 Pa·m3/mol CAS: 67-64-1 Conclusion Yes Very High ory soil 2,304E-2 N/m (25 °C) EC: 200-662-2 Surface tension loist soil Yes Xylene Кос 202 Henry 524,86 Pa·m<sup>3</sup>/mol CAS: 1330-20-7 Conclusion Moderate Dry soi Yes EC: 215-535-7 Yes Surface tension Non-applicable Moist soil

\*\* Changes with regards to the previous version

N-butyl acetate

CAS: 123-86-4

EC: 204-658-1

Ethylbenzene

CAS: 100-41-4

EC: 202-849-4

- CONTINUED ON NEXT PAGE -

Кос

Koc

Conclusion

Conclusion

Surface tension

Surface tension

Non-applicable

Non-applicable

520

Moderate

2,478E-2 N/m (25 °C)

2,859E-2 N/m (25 °C)

Henry

Dry soil

Henry

Dry soil

1oist soil

Moist soil

Non-applicable


Non-applicable

Non-applicable

Yes

Yes

798,44 Pa·m<sup>3</sup>/mol





# minos

### SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)

Identification	Absor	rption/desorption	Volatility	
Methanol	Кос	Non-applicable	Henry	Non-applicable
CAS: 67-56-1	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-659-6	Surface tension	2,355E-2 N/m (25 °C)	Moist soil	Non-applicable
Cyclohexanone	Кос	17	Henry	9,119E-1 Pa·m³/m
CAS: 108-94-1	Conclusion	Very High	Dry soil	Yes
EC: 203-631-1	Surface tension	3,437E-2 N/m (25 °C)	Moist soil	Yes
1,2,4-trimethylbenzene	Кос	537	Henry	624,16 Pa·m³/mol
CAS: 95-63-6	Conclusion	Low	Dry soil	Yes
EC: 202-436-9	Surface tension	2,919E-2 N/m (25 °C)	Moist soil	Yes
2-butoxyethanol	Кос	8	Henry	1,621E-1 Pa·m³/m
CAS: 111-76-2	Conclusion	Very High	Dry soil	No
EC: 203-905-0	Surface tension	2,729E-2 N/m (25 °C)	Moist soil	Yes
Mesitylene	Кос	1445	Henry	888,62 Pa·m³/mol
CAS: 108-67-8	Conclusion	Low	Dry soil	Yes
EC: 203-604-4	Surface tension	2,805E-2 N/m (25 °C)	Moist soil	Yes
Cumene	Кос	Non-applicable	Henry	Non-applicable
CAS: 98-82-8	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 202-704-5	Surface tension	2,769E-2 N/m (25 °C)	Moist soil	Non-applicable
Benzene	Кос	Non-applicable	Henry	Non-applicable
CAS: 71-43-2	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-753-7	Surface tension	2,821E-2 N/m (25 °C)	Moist soil	Non-applicable

# 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

#### 12.6 Other adverse effects:

Not described

\*\* Changes with regards to the previous version

# SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	Gases in pressure containers (including halons) containing dangerous substances	Dangerous

### Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP4 Irritant — skin irritation and eye damage, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

#### **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC)  $n^{0}1907/2006$  (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

### SECTION 14: TRANSPORT INFORMATION

#### Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:



MINOS METALLIC PAINT SPRAY BLACK - Metallic paint spray 24-102

#### SECTION 14: TRANSPORT INFORMATION (continued) UN1950 14.1 UN number: AEROSOLS, flammable 14.2 UN proper shipping name: 14.3 Transport hazard class(es): 2 Labels: 2.1 14.4 Packing group: N/A 14.5 Environmental hazards: No 14.6 Special precautions for user Special regulations: 190, 327, 344, 625 Tunnel restriction code: D Physico-Chemical properties: see section 9 Limited quantities: 11 14.7 Transport in bulk according to Non-applicable Annex II of Marpol and the IBC Code: Transport of dangerous goods by sea: With regard to IMDG 38-16: 14.1 UN number: UN1950 14.2 UN proper shipping name: AEROSOLS, flammable 14.3 Transport hazard class(es): 2 Labels<sup>1</sup> 21 14.4 Packing group: N/A 14.5 Environmental hazards: No 14.6 Special precautions for user Special regulations: 63, 959, 190, 277, 327, 344 EmS Codes: F-D, S-U Physico-Chemical properties: see section 9 Limited quantities: 1 L **14.7** Transport in bulk according to Non-applicable Annex II of Marpol and the **IBC Code:** Transport of dangerous goods by air: With regard to IATA/ICAO 2017: 14.1 UN number: UN1950 14.2 UN proper shipping name: AEROSOLS, flammable 14.3 Transport hazard class(es): 2 Labels: 2.1 14.4 Packing group: N/A 14.5 Environmental hazards: No 14.6 Special precautions for user Physico-Chemical properties: see section 9 **14.7** Transport in bulk according to Non-applicable Annex II of Marpol and the **IBC Code:**

# SECTION 15: REGULATORY INFORMATION

**15.1** Safety, health and environmental regulations/legislation specific for the substance or mixture: Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Contains Benzene

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

minor





# SECTION 15: REGULATORY INFORMATION (continued)

Regulation (EU) No 98/2013 of the European Parliament and of the Council of 15 January 2013 on the marketing and use of explosives precursors: Contains Acetone, Aluminium powder (stabilised). Product under the provisions of Article 9 Shall not be used in:

---ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

#### Other legislation:

The product could be affected by sectorial legislation

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers Commission Directive 94/1/EC of 6 January 1994 adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of the relating Member States to aerosol dispensers

Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers

Commission Directive 2013/10/EU of 19 March 2013 amending Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

### SECTION 16: OTHER INFORMATION \*\*

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) Nº 1907/2006 (Regulation (EC) Nº 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

New declared substances

N-butyl acetate (123-86-4)

- Mesitylene (108-67-8)
- CLP Regulation (EC) nº 1272/2008 (SECTION 2, SECTION 16):
  - Pictograms
  - · Hazard statements
  - Precautionary statements

#### Texts of the legislative phrases mentioned in section 2:

- H315: Causes skin irritation
- H336: May cause drowsiness or dizziness
- H229: Pressurised container: May burst if heated
- H222: Extremely flammable aerosol
- H319: Causes serious eye irritation

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### CLP Regulation (EC) nº 1272/2008:



Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and

24-102

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure

Acute Tox, 4: H312+H332 - Harmful in contact with skin or if inhaled

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

interpretation of this safety data sheet, as well as the label on the product.

ADR: European agreement concerning the international carriage of dangerous goods by road

# SECTION 16: OTHER INFORMATION \*\* (continued)

Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 2: H225 - Highly flammable liquid and vapour Flam. Liq. 3: H226 - Flammable liquid and vapour Muta. 1B: H340 - May cause genetic defects Skin Irrit. 2: H315 - Causes skin irritation

STOT SE 1: H370 - Causes damage to organs STOT SE 3: H335 - May cause respiratory irritation STOT SE 3: H336 - May cause drowsiness or dizziness

Acute Tox. 4: H332 - Harmful if inhaled

Carc. 1A: H350 - May cause cancer

Classification procedure: Skin Irrit. 2: Calculation method STOT SE 3: Calculation method Aerosol 1: Calculation method Aerosol 1: Calculation method Eye Irrit. 2: Calculation method Advice related to training:

Principal bibliographical sources:

COD: Chemical Oxygen Demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

BOD5: 5-day biochemical oxygen demand

Log-POW: Octanol–water partition coefficient Koc: Partition coefficient of organic carbon

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

http://echa.europa.eu http://eur-lex.europa.eu Abbreviations and acronyms:

\*\* Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

minor