According to 1907/2006/EC (REACH), 2015/830/EU



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray

24-102

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Spray paint

Uses advised against: All uses not specified in this section or in section $7.3\,$

1.3 Details of the supplier of the safety data sheet: EVOCHEM S.A.

Tzaverdella Place

133 41 PHILI, ATTICA - GREECE

Phone.: 0030 210 5590460 , 0030 210 5590155 Fax: 0030 210 6254737 , 0030 210 5590244 info@evochem.gr ; vmergoupis@evochem.gr ;

sales@evochem.gr www.evochem.gr

1.4 Emergency telephone number: National Poisoning Center 2107793777

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) no 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) no 1272/2008.

Aerosol 1: Pressurised container: May burst if heated., H229

Aerosol 1: Flammable aerosols, Category 1, H222 Eye Irrit. 2: Eye irritation, Category 2, H319 Skin Irrit. 2: Skin irritation, Category 2, H315

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) nº 1272/2008:

Danger





Hazard statements:

Aerosol 1: H229 - Pressurized container: May burst if heated

Aerosol 1: H222 - Extremely flammable aerosol Eye Irrit. 2: H319 - Causes serious eye irritation Skin Irrit. 2: H315 - Causes skin irritation

STOT SE 3: H336 - May cause drowsiness or dizziness

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211: Do not spray on an open flame or other ignition source

P251: Do not pierce or burn, even after use

P280: Wear protective gloves/protective clothing/eye protection/face protection

P410+P412: Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F

P501: Dispose of contents and / or their container according to the separated collection system used in your municipality

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking

Substances that contribute to the classification

Acetone; N-butyl acetate

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) **Page 1/17**

^{**} Changes with regards to the previous version



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives, pigments and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) nº1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH 01-2119471330-49-XXX	Acetone ¹ ATP CLP00 Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	24 - <50 %
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH 01-2119488216-32-XXX	ATP CLP00 Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	9,9 - <19 %
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH 01-2119485493-29-XXX	N-butyl acetate Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	2,4 - <4,9 %
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH 01-2119489370-35-XXX	Regulation 1272/2008 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 -	0,9 - <2,4 %
CAS: 67-56-1 EC: 200-659-6 Index: 603-001-00-X REACH 01-2119433307-44-XXX	Methanol 1 ATP CLP00 Regulation 1272/2008 Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger	0,24 - <0,9 %
CAS: 108-94-1 EC: 203-631-1 Index: 606-010-00-7 REACH 01-2119453616-35-XXX	Cyclohexanone 2 ATP CLP00 Regulation 1272/2008 Acute Tox. 4: H332; Flam. Liq. 3: H226 - Warning	0,24 - <0,9 %
CAS: 95-63-6 EC: 202-436-9 Index: 601-043-00-3 REACH 01-2119472135-42-XXX	1,2,4-trimethylbenzene ² Regulation 1272/2008 Acute Tox. 4: H332; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning	0,09 - <0,24 %
CAS: 111-76-2 EC: 203-905-0 Index: 603-014-00-0 REACH 01-2119475108-36-XXX	2-butoxyethanol ² ATP CLP00 Regulation 1272/2008 Acute Tox. 4: H302+H312+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	<0,09 %
CAS: 108-67-8 EC: 203-604-4 Index: 601-025-00-5 REACH Non-applicable	Mesitylene ² Regulation 1272/2008 Aquatic Chronic 2: H411; Flam. Liq. 3: H226; STOT SE 3: H335 - Warning (1) (2) (4)	<0,09 %
CAS: 98-82-8 EC: 202-704-5 Index: 601-024-00-X REACH 01-2119473983-24-XXX	Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335 - Danger	<0,09 %
CAS: 71-43-2 EC: 200-753-7 Index: 601-020-00-8 REACH 01-2119496063-37-XXX	Regulation 1272/2008 Asp. Tox. 1: H304; Carc. 1A: H350; Eye Irrit. 2: H319; Flam. Liq. 2: H225; Muta. 1B: H340; Skin Irrit. 2: H315; STOT RE 1: H372 - Danger	<0,09 %

Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830
 Substance with a Union workplace exposure limit

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

SECTION 4: FIRST AID MEASURES

Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

^{**} Changes with regards to the previous version

According to 1907/2006/EC (REACH), 2015/830/EU



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 4: FIRST AID MEASURES (continued)

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid spillage into an aqueous medium as it contains substances potentially dangerous for this. Contain the product absorbed in hermetically sealed containers. In the case of serious spillage into an aqueous medium notify the relevant authority.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) **Page 3/17**



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid projections and pulverizations. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 35 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification		Environmental limits		
Acetone	IOELV (8h)	500 ppm	1210 mg/m ³	
CAS: 67-64-1	IOELV (STEL)			
EC: 200-662-2	Year	2017		
Xylene	IOELV (8h)	50 ppm	221 mg/m ³	
CAS: 1330-20-7	IOELV (STEL)	100 ppm	442 mg/m ³	
EC: 215-535-7	Year	2017		
Ethylbenzene	IOELV (8h)	100 ppm	442 mg/m ³	
CAS: 100-41-4	IOELV (STEL)	200 ppm	884 mg/m ³	
EC: 202-849-4	Year	2017		
Methanol	IOELV (8h)	200 ppm	260 mg/m ³	
CAS: 67-56-1	IOELV (STEL)			
EC: 200-659-6	Year	2017		
Cyclohexanone	IOELV (8h)	10 ppm	40.8 mg/m ³	
CAS: 108-94-1	IOELV (STEL)	20 ppm	81.6 mg/m ³	
EC: 203-631-1	Year	2017	,	
1,2,4-trimethylbenzene	IOELV (8h)	20 ppm	100 mg/m ³	
CAS: 95-63-6	IOELV (STEL)			
EC: 202-436-9	Year	2017		
2-butoxyethanol	IOELV (8h)	20 ppm	98 mg/m ³	
CAS: 111-76-2	IOELV (STEL)	50 ppm	246 mg/m ³	
EC: 203-905-0	Year	2017		
Mesitylene	IOELV (8h)	20 ppm	100 mg/m ³	
	li-			

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) **Page 4/17**



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identificat	Environmental limits			
CAS: 108-67-8		IOELV (STEL)		
EC: 203-604-4		Year	2017	
Cumene		IOELV (8h)	20 ppm	100 mg/m ³
CAS: 98-82-8		IOELV (STEL)	50 ppm	250 mg/m ³
EC: 202-704-5		Year	2017	•
Benzene		IOELV (8h)	1 ppm	3.25 mg/m ³
CAS: 71-43-2		IOELV (STEL)		
EC: 200-753-7		Year	2017	

DNEL (Workers):

		Short exposure		Long exposure	
Identification	Systemic	Local	Systemic	Local	
Acetone Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 67-64-1 Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable	
EC: 200-662-2 Inhalation	Non-applicable	2420 mg/m ³	1210 mg/m ³	Non-applicable	
Xylene Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 1330-20-7 Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable	
EC: 215-535-7 Inhalation	289 mg/m³	289 mg/m³	77 mg/m³	Non-applicable	
N-butyl acetate Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 123-86-4 Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
EC: 204-658-1 Inhalation	960 mg/m ³	960 mg/m ³	480 mg/m ³	480 mg/m ³	
Ethylbenzene Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 100-41-4 Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable	
EC: 202-849-4 Inhalation	Non-applicable	293 mg/m ³	77 mg/m³	Non-applicable	
Methanol Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 67-56-1 Dermal	40 mg/kg	Non-applicable	40 mg/kg	Non-applicable	
EC: 200-659-6 Inhalation	260 mg/m ³	260 mg/m ³	260 mg/m ³	260 mg/m ³	
Cyclohexanone Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 108-94-1 Dermal	4 mg/kg	Non-applicable	4 mg/kg	Non-applicable	
EC: 203-631-1 Inhalation	80 mg/m ³	80 mg/m ³	40 mg/m ³	40 mg/m ³	
1,2,4-trimethylbenzene Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 95-63-6 Dermal	Non-applicable	Non-applicable	16171 mg/kg	Non-applicable	
EC: 202-436-9 Inhalation	100 mg/m ³	100 mg/m ³	100 mg/m ³	100 mg/m ³	
2-butoxyethanol Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 111-76-2 Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable	
EC: 203-905-0 Inhalation	663 mg/m ³	246 mg/m ³	98 mg/m ³	Non-applicable	
Mesitylene Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 108-67-8 Dermal	Non-applicable	Non-applicable	16171 mg/kg	Non-applicable	
EC: 203-604-4 Inhalation	100 mg/m ³	100 mg/m ³	100 mg/m ³	100 mg/m ³	
Cumene Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 98-82-8 Dermal	Non-applicable	Non-applicable	15,4 mg/kg	Non-applicable	
EC: 202-704-5 Inhalation	Non-applicable	250 mg/m ³	100 mg/m ³	Non-applicable	

DNEL (General population):

	SHOLL	Snort exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Acetone	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	Non-applicable	200 mg/m ³	Non-applicable
Xylene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	Non-applicable	Non-applicable	14,8 mg/m ³	Non-applicable
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-658-1	Inhalation	859,7 mg/m ³	859,7 mg/m ³	102,34 mg/m ³	102,34 mg/m ³

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) **Page 5/17**



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable	
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable	
Methanol	Oral	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable	
CAS: 67-56-1	Dermal	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable	
EC: 200-659-6	Inhalation	50 mg/m ³	50 mg/m ³	50 mg/m ³	50 mg/m ³	
Cyclohexanone	Oral	1,5 mg/kg	Non-applicable	1,5 mg/kg	Non-applicable	
CAS: 108-94-1	Dermal	1 mg/kg	Non-applicable	1 mg/kg	Non-applicable	
EC: 203-631-1	Inhalation	20 mg/m ³	40 mg/m ³	10 mg/m ³	20 mg/m ³	
1,2,4-trimethylbenzene	Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable	
CAS: 95-63-6	Dermal	Non-applicable	Non-applicable	9512 mg/kg	Non-applicable	
EC: 202-436-9	Inhalation	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³	
2-butoxyethanol	Oral	13,4 mg/kg	Non-applicable	3,2 mg/kg	Non-applicable	
CAS: 111-76-2	Dermal	44,5 mg/kg	Non-applicable	38 mg/kg	Non-applicable	
EC: 203-905-0	Inhalation	426 mg/m ³	123 mg/m³	49 mg/m ³	Non-applicable	
Mesitylene	Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable	
CAS: 108-67-8	Dermal	Non-applicable	Non-applicable	9512 mg/kg	Non-applicable	
EC: 203-604-4	Inhalation	29,4 mg/m³	29,4 mg/m³	29,4 mg/m ³	29,4 mg/m ³	
Cumene	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable	
CAS: 98-82-8	Dermal	Non-applicable	Non-applicable	1,2 mg/kg	Non-applicable	
EC: 202-704-5	Inhalation	Non-applicable	Non-applicable	16,6 mg/m ³	Non-applicable	

PNEC:

Identification				
Acetone	STP	100 mg/L	Fresh water	10,6 mg/L
CAS: 67-64-1	Soil	29,5 mg/kg	Marine water	1,06 mg/L
EC: 200-662-2	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,04 mg/kg
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,0903 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0981 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	1,37 mg/kg
Methanol	STP	100 mg/L	Fresh water	154 mg/L
CAS: 67-56-1	Soil	23,5 mg/kg	Marine water	15,4 mg/L
EC: 200-659-6	Intermittent	1540 mg/L	Sediment (Fresh water)	570,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
Cyclohexanone	STP	10 mg/L	Fresh water	0,0329 mg/L
CAS: 108-94-1	Soil	0,0143 mg/kg	Marine water	0,00329 mg/L
EC: 203-631-1	Intermittent	0,329 mg/L	Sediment (Fresh water)	0,168 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0168 mg/kg
1,2,4-trimethylbenzene	STP	2,41 mg/L	Fresh water	0,12 mg/L
CAS: 95-63-6	Soil	2,34 mg/kg	Marine water	0,12 mg/L
EC: 202-436-9	Intermittent	0,12 mg/L	Sediment (Fresh water)	13,56 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	13,56 mg/kg

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) **Page 6/17**

According to 1907/2006/EC (REACH), 2015/830/EU

Evochem®

MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
2-butoxyethanol	STP	463 mg/L	Fresh water	8,8 mg/L
CAS: 111-76-2	Soil	3,13 mg/kg	Marine water	0,88 mg/L
EC: 203-905-0	Intermittent	9,1 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	Non-applicable
Mesitylene	STP	2,02 mg/L	Fresh water	0,101 mg/L
CAS: 108-67-8	Soil	1,34 mg/kg	Marine water	0,101 mg/L
EC: 203-604-4	Intermittent	0,101 mg/L	Sediment (Fresh water)	7,86 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,86 mg/kg
Cumene	STP	200 mg/L	Fresh water	0,035 mg/L
CAS: 98-82-8	Soil	0,624 mg/kg	Marine water	0,0035 mg/L
EC: 202-704-5	Intermittent	0,012 mg/L	Sediment (Fresh water)	3,22 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,322 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	CAT III	EN 149:2001+A1:2009 EN 405:2001+A1:2009	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CATIII	EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face mask	CATII	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Bodily protection

4	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) **Page 7/17**

According to 1907/2006/EC (REACH), 2015/830/EU



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CAT III	EN 13287:2008 EN ISO 20345:2011 EN 13832-1:2006	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2002	Eyewash stations	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 86,56 % weight

V.O.C. density at 20 °C: 735,78 kg/m³ (735,78 g/L)

Average carbon number: 4,09

Average molecular weight: 70,1 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 735,78 kg/m³ (735,78 g/L)

EUlimit for the product (Cat. B.E): 840 g/L (2010)

Components: Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Odour:

Odour threshold:

Aerosol

Not available

Silver

Characteristic

Non-applicable *

Volatility:

Boiling point at atmospheric pressure: -42 °C (Propellant)

Vapour pressure at 20 °C:

Non-applicable *

Vapour pressure at 50 °C: <300000 Pa (300 kPa)

Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C:

Relative density at 20 °C:

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Kinematic viscosity at 20 °C:

Non-applicable *

Non-applicable *

Concentration: 850 g/L (active ingredient)

*Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) **Page 8/17**



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

pH: Non-applicable * Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable * Recipient pressure: Non-applicable * Non-applicable * Explosive properties: Oxidising properties: Non-applicable *

Flammability:

Flash Point: -104 °C (Propellant)
Flammability (solid, gas): Non-applicable *
Autoignition temperature: 410 °C (Propellant)
Lower flammability limit: Non-applicable *
Upper flammability limit: Non-applicable *

Explosive:

Lower explosive limit:

Upper explosive limit:

Non-applicable *

Non-applicable *

9.2 Other information:

Surface tension at 20 °C:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases. Can react violently

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) **Page 9/17**

^{**} Changes with regards to the previous version

According to 1907/2006/EC (REACH), 2015/830/EU



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. With possibility of effects that are hazardous to the health, it is recommended not to breathe the vapours for long periods of time.

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
 - Mutagenicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
 - Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acu	Genus	
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg (ATEi)	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (4 h) (ATEi)	

^{**} Changes with regards to the previous version

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) Page 10/17



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Identification		Acute toxicity	Genus
Ethylbenzene	LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4	LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inhalation	17,2 mg/L (4 h)	Rat
Methanol	LD50 oral	100 mg/kg	Rat
CAS: 67-56-1	LD50 dermal	300 mg/kg	Rabbit
EC: 200-659-6	LC50 inhalation	3 mg/L (4 h)	Rat
N-butyl acetate	LD50 oral	12789 mg/kg	Rat
CAS: 123-86-4	LD50 dermal	14112 mg/kg	Rabbit
EC: 204-658-1	LC50 inhalation	23,4 mg/L (4 h)	Rat
Acetone	LD50 oral	5800 mg/kg	Rat
CAS: 67-64-1	LD50 dermal	7426 mg/kg	Rabbit
EC: 200-662-2	LC50 inhalation	76 mg/L (4 h)	Rat
Cyclohexanone	LD50 oral	2650 mg/kg	Rat
CAS: 108-94-1	LD50 dermal	3160 mg/kg	Rabbit
EC: 203-631-1	LC50 inhalation	11 mg/L (4 h)	Rat
1,2,4-trimethylbenzene	LD50 oral	3400 mg/kg	Rat
CAS: 95-63-6	LD50 dermal	3160 mg/kg	Rabbit
EC: 202-436-9	LC50 inhalation	11 mg/L (4 h)	Rat
2-butoxyethanol	LD50 oral	500 mg/kg	Rat
CAS: 111-76-2	LD50 dermal	1100 mg/kg	Rat
EC: 203-905-0	LC50 inhalation	11 mg/L (4 h)	Rat
Mesitylene	LD50 oral	6000 mg/kg	Rat
CAS: 108-67-8	LD50 dermal	Non-applicable	
EC: 203-604-4	LC50 inhalation	Non-applicable	
Cumene	LD50 oral	2700 mg/kg	
CAS: 98-82-8	LD50 dermal	Non-applicable	
EC: 202-704-5	LC50 inhalation	Non-applicable	
Benzene	LD50 oral	2900 mg/kg	Rat
CAS: 71-43-2	LD50 dermal	8263 mg/kg	Rabbit
EC: 200-753-7	LC50 inhalation	44,45 mg/L (4 h)	Rat

^{**} Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification		Acute toxicity	Species	Genus	
Acetone	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: 67-64-1	EC50	23.5 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 200-662-2	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae	
Xylene	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: 1330-20-7	EC50	0.6 mg/L (96 h)	Gammarus lacustris	Crustacean	
EC: 215-535-7	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae	
N-butyl acetate	LC50	62 mg/L (96 h)	Leuciscus idus	Fish	
CAS: 123-86-4	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean	
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae	
Ethylbenzene	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish	
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae	

^{**} Changes with regards to the previous version

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) Page 11/17



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification		Acute toxicity	Species	Genus	
Methanol	LC50	15400 mg/L (96 h)	Lepomis macrochirus	Fish	
CAS: 67-56-1	EC50	12000 mg/L (96 h)	Nitrocra spinipes	Crustacean	
EC: 200-659-6	EC50	530 mg/L (168 h)	Microcystis aeruginosa	Algae	
Cyclohexanone	LC50	527 mg/L (96 h)	Pimephales promelas	Fish	
CAS: 108-94-1	EC50	800 mg/L (24 h)	Daphnia magna	Crustacean	
EC: 203-631-1	EC50	370 mg/L (192 h)	Scenedesmus quadricauda	Algae	
1,2,4-trimethylbenzene	LC50	7.72 mg/L (96 h)	Pimephales promelas	Fish	
CAS: 95-63-6	EC50	6.14 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 202-436-9	EC50	Non-applicable			
2-butoxyethanol	LC50	1490 mg/L (96 h)	Lepomis macrochirus	Fish	
CAS: 111-76-2	EC50	1815 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 203-905-0	EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae	
Mesitylene	LC50	12.5 mg/L (96 h)	Carassius auratus	Fish	
CAS: 108-67-8	EC50	50 mg/L (24 h)	Daphnia magna	Crustacean	
EC: 203-604-4	EC50	53 mg/L (48 h)	Scenedesmus subspicatus	Algae	
Cumene	LC50	2.7 mg/L (96 h)	Salmo gairdneri	Fish	
CAS: 98-82-8	EC50	10.8 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 202-704-5	EC50	2.6 mg/L (72 h)	Selenastrum capricornutum	Algae	
Benzene	LC50	5.9 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: 71-43-2	EC50	66 mg/L (24 h)	Artemia salina	Crustacean	
EC: 200-753-7	EC50	29 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae	

12.2 Persistence and degradability:

Identification	D	egradability	Biod	legradability
Acetone	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-64-1	COD	Non-applicable	Period	28 days
EC: 200-662-2	BOD5/COD	0.96	% Biodegradable	96 %
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	0.79	% Biodegradable	84 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
Methanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-56-1	COD	1.42 g O2/g	Period	14 days
EC: 200-659-6	BOD5/COD	Non-applicable	% Biodegradable	92 %
Cyclohexanone	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 108-94-1	COD	Non-applicable	Period	14 days
EC: 203-631-1	BOD5/COD	0.65	% Biodegradable	87 %
1,2,4-trimethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 95-63-6	COD	Non-applicable	Period	28 days
EC: 202-436-9	BOD5/COD	0.43	% Biodegradable	18 %
2-butoxyethanol	BOD5	0.71 g O2/g	Concentration	100 mg/L
CAS: 111-76-2	COD	2.2 g O2/g	Period	14 days
EC: 203-905-0	BOD5/COD	0.32	% Biodegradable	96 %
Mesitylene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 108-67-8	COD	Non-applicable	Period	14 days
EC: 203-604-4	BOD5/COD	Non-applicable	% Biodegradable	0 %
Cumene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 98-82-8	COD	Non-applicable	Period	14 days
EC: 202-704-5	BOD5/COD	Non-applicable	% Biodegradable	40 %

^{**} Changes with regards to the previous version

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) Page 12/17



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 12: ECOLOGICAL INFORMATION ** (continued) Identification Degradability Benzene BOD5 Non-applicable Concentration 100 mg/L

CAS: 71-43-2 COD Non-applicable Period 14 days
EC: 200-753-7 BOD5/COD Non-applicable % Biodegradable 40 %

12.3 Bioaccumulative potential:

Identification	Bioa	accumulation potential
Acetone	BCF	1
CAS: 67-64-1	Pow Log	-0.24
EC: 200-662-2	Potential	Low
Xylene	BCF	9
CAS: 1330-20-7	Pow Log	2.77
EC: 215-535-7	Potential	Low
N-butyl acetate	BCF	4
CAS: 123-86-4	Pow Log	1.78
EC: 204-658-1	Potential	Low
Ethylbenzene	BCF	1
CAS: 100-41-4	Pow Log	3.15
EC: 202-849-4	Potential	Low
Methanol	BCF	3
CAS: 67-56-1	Pow Log	-0.77
EC: 200-659-6	Potential	Low
Cyclohexanone	BCF	2
CAS: 108-94-1	Pow Log	0.81
EC: 203-631-1	Potential	Low
1,2,4-trimethylbenzene	BCF	154
CAS: 95-63-6	Pow Log	3.78
EC: 202-436-9	Potential	High
2-butoxyethanol	BCF	3
CAS: 111-76-2	Pow Log	0.83
EC: 203-905-0	Potential	Low
Mesitylene	BCF	182
CAS: 108-67-8	Pow Log	3.42
EC: 203-604-4	Potential	High
Cumene	BCF	120
CAS: 98-82-8	Pow Log	3.66
EC: 202-704-5	Potential	High
Benzene	BCF	4
CAS: 71-43-2	Pow Log	2.13
EC: 200-753-7	Potential	Low

12.4 Mobility in soil:

	Identification	Absorption	on/desorption	Volati	lity
Ī	Acetone	Koc	1	Henry	2,93 Pa·m³/mol
	CAS: 67-64-1	Conclusion	Very High	Dry soil	Yes
	EC: 200-662-2	Surface tension	2,304E-2 N/m (25 °C)	Moist soil	Yes
1	Xylene	Koc	202	Henry	524,86 Pa·m³/mol
	CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
	EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes
Ī	N-butyl acetate	Koc	Non-applicable	Henry	Non-applicable
	CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable
	EC: 204-658-1	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable
Ī	Ethylbenzene	Koc	520	Henry	798,44 Pa·m³/mol
	CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes
Į	EC: 202-849-4	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes

^{**} Changes with regards to the previous version

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) **Page 13/17**

According to 1907/2006/EC (REACH), 2015/830/EU



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Absor	ption/desorption		Volatility
Methanol	Koc	Non-applicable	Henry	Non-applicable
CAS: 67-56-1	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-659-6	Surface tension	2,355E-2 N/m (25 °C)	Moist soil	Non-applicable
Cyclohexanone	Koc	17	Henry	9,119E-1 Pa·m³/mol
CAS: 108-94-1	Conclusion	Very High	Dry soil	Yes
EC: 203-631-1	Surface tension	3,437E-2 N/m (25 °C)	Moist soil	Yes
1,2,4-trimethylbenzene	Koc	537	Henry	624,16 Pa·m³/mol
CAS: 95-63-6	Conclusion	Low	Dry soil	Yes
EC: 202-436-9	Surface tension	2,919E-2 N/m (25 °C)	Moist soil	Yes
2-butoxyethanol	Koc	8	Henry	1,621E-1 Pa·m³/mol
CAS: 111-76-2	Conclusion	Very High	Dry soil	No
EC: 203-905-0	Surface tension	2,729E-2 N/m (25 °C)	Moist soil	Yes
Mesitylene	Koc	1445	Henry	888,62 Pa·m³/mol
CAS: 108-67-8	Conclusion	Low	Dry soil	Yes
EC: 203-604-4	Surface tension	2,805E-2 N/m (25 °C)	Moist soil	Yes
Cumene	Koc	Non-applicable	Henry	Non-applicable
CAS: 98-82-8	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 202-704-5	Surface tension	2,769E-2 N/m (25 °C)	Moist soil	Non-applicable
Benzene	Koc	Non-applicable	Henry	Non-applicable
CAS: 71-43-2	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-753-7	Surface tension	2,821E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	Gases in pressure containers (including halons) containing dangerous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP4 Irritant — skin irritation and eye damage, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) $n^{o}1907/2006$ (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) Page 14/17

^{**} Changes with regards to the previous version

According to 1907/2006/EC (REACH), 2015/830/EU

Evochem®

MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number: UN1950

14.2 UN proper shipping name: AEROSOLS, flammable

14.3 Transport hazard class(es): 2 Labels: 2

Labels: 2.1 **14.4 Packing group:** N/A

14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 190, 327, 344, 625

Tunnel restriction code: D

Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Transport in bulk according to Non-applicable

Annex II of Marpol and the IBC Code:

Transport of dangerous goods by sea:

With regard to IMDG 38-16:

14.1 UN number: UN1950

14.2 UN proper shipping name: AEROSOLS, flammable

14.3 Transport hazard class(es): 2 Labels: 2.1

14.4 Packing group: N/A **14.5 Environmental hazards:** No

14.6 Special precautions for user

Special regulations: 63, 959, 190, 277, 327, 344

EmS Codes: F-D, S-U
Physico-Chemical properties: see section 9
Limited quantities: 1 L

14.7 Transport in bulk according to Non-applicable

Annex II of Marpol and the

IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2017:



14.1 UN number: UN1950

14.2 UN proper shipping name: AEROSOLS, flammable

14.3Transport hazard class(es):2Labels:2.114.4Packing group:N/A14.5Environmental hazards:No

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Transport in bulk according to Non-applicable

Annex II of Marpol and the

IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Contains Benzene

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) Page 15/17

According to 1907/2006/EC (REACH), 2015/830/EU



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 15: REGULATORY INFORMATION (continued)

Regulation (EU) No 98/2013 of the European Parliament and of the Council of 15 January 2013 on the marketing and use of explosives precursors: Contains Acetone, Aluminium powder (stabilised). Product under the provisions of Article 9 Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers Commission Directive 94/1/EC of 6 January 1994 adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of the relating Member States to aerosol dispensers

Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers

Commission Directive 2013/10/EU of 19 March 2013 amending Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

· New declared substances

N-butyl acetate (123-86-4)

Mesitylene (108-67-8)

CLP Regulation (EC) no 1272/2008 (SECTION 2, SECTION 16):

- · Pictograms
- · Hazard statements
- · Precautionary statements

Texts of the legislative phrases mentioned in section 2:

- H315: Causes skin irritation
- H336: May cause drowsiness or dizziness
- H229: Pressurised container: May burst if heated
- H222: Extremely flammable aerosol
- H319: Causes serious eye irritation

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) no 1272/2008:

** Changes with regards to the previous version

Date of compilation: 19/04/2015 Revised: 05/12/2017 Version: 2 (Replaced 1) Page 16/17

According to 1907/2006/EC (REACH), 2015/830/EU



MINOS METALLIC PAINT SPRAY SILVER RAL 9006 - Metallic paint spray 24-102



SECTION 16: OTHER INFORMATION ** (continued)

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Acute Tox. 4: H332 - Harmful if inhaled

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Carc. 1A: H350 - May cause cancer

Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 2: H225 - Highly flammable liquid and vapour Flam. Liq. 3: H226 - Flammable liquid and vapour

Muta. 1B: H340 - May cause genetic defects Skin Irrit. 2: H315 - Causes skin irritation

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure

STOT SE 1: H370 - Causes damage to organs STOT SE 3: H335 - May cause respiratory irritation STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

Skin Irrit. 2: Calculation method STOT SE 3: Calculation method Aerosol 1: Calculation method Aerosol 1: Calculation method Eye Irrit. 2: Calculation method

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol–water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

^{**} Changes with regards to the previous version