



DIY Products

ANTIFREEZE

Technical Data Sheet

Reviewed: 06.06.2015



DESCRIPTION

ANTIFREEZE is a high quality anti-freeze liquid. Assures complete protection in all kinds of closed freezing-heating circuits, regardless of weather conditions, all throughout the year (-20°C - +106°C).

ADVANTAGES

- Complete anti-freeze and anti-thermal ability
- Antirust protection
- Suitable for all temperatures
- Reduces cleaning and maintenance costs

APPLICATIONS

- Protection of engine radiators as well as solar water heaters
- Protection of all closed freezing-heating circuits, regardless of type of metal (iron, copper, aluminium etc.)
- Protects from rust, corrosion and salt deposits.
- Minimizes the precipitation of metallic oxides.

INSTRUCTIONS FOR USE

1. **Engine radiators:** empty the radiator, wash with water and fill it up with ANTIFREEZE. Start the engine and allow liquid to circulate. If necessary fill in the required amount.
2. **Solar water heaters:** for total protection from ice allow ANTIFREEZE in the circuit throughout the year. Dilution depends on lower temperatures. If needed dilute with deionized water.

CLEANING

Clean tools with water immediately after use.

TECHNICAL CHARACTERISTICS

Appearance: Transparent liquid

Colour : Green - Blue

Odour : Odourless

Density 20°C: 1,1 ± 0,1 gr / ml

PH (50% v/v in water): 7.2

Reserve alkalinity (ml): 14

Freezing Point 50% v/v in water (°C): -10

Application temperature: +5°C to +40°C

STORAGE

In a well-ventilated place, cool and dry place at temperatures between +5°C - +50°C. Keep away from electrical devices, sources of ignition and fire. Protect from frost.

SHELF LIFE

12 months in unopened packaging in the above mentioned storage conditions

PACKAGING

1Lt, 4Lt

PACKAGING	CODE	BARCODE
1Lt	5147	5204094051473
4Lt	5148	5204094051480

HEALTH AND SAFETY INFORMATION

EUH208: Contains Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [ECno. 220-239-6] (3:1). May produce an allergic reaction

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



Evochem®

EVOCHEM S.A.

Tzavardella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr

