



Adhesives & Sealants

BRUSH SEALANT

Technical Data Sheet

Reviewed: 06.09.2019



DESCRIPTION

BRUSH SEALANT is an elastomeric thixotropic brush applied sealant suitable for most types of joints on car bodies, trucks, boats, caravans or prefabricated buildings. It is waterproof, offers anti-vibration protection and has excellent adhesion to most surfaces. Can be overpainted with most types of paints.

ADVANTAGES

- Dries fast
- Does not crack
- Does not lose its shape
- Remains permanently elastic

APPLICATIONS

Can be applied between metal surfaces prior to bonding, riveting or bolting to absorb cracking noises and vibrations.

- In all types of automotive joints.
- Sealing material between metal surfaces.
- Adhesive for car filters, filters, elastic carpeting and rubber joints.
- Suitable as a waterproofing sealing material.

INSTRUCTIONS FOR USE

1. Surfaces should be clean, dry and free from dust any oily residues.
2. Dilute if necessary with nitro solvent.
3. Can be applied with a brush in layers of at least 3 mm.
4. As an adhesive or rubber jointing material, apply to both surfaces.
5. Allow 10 – 15 minutes before joining.
6. Press the two surfaces together and apply light pressure.
7. Can be over painted after drying with DELUX, alkyd, enamel or most acrylic paints.

CLEANING

Clean tools immediately after use with nitro solvent

COVERAGE

1-2 m²/ kg

TECHNICAL CHARACTERISTICS

Form: Paste

Color: Beige

Odour: Characteristic of aromatic solvents

Specific Gravity: 1,04 g/mL

Viscosity: 20000 ± 5000 cPs

Flammability: Highly flammable

Solubility: In aromatic solvents

STORAGE

In a cool and dry place at temperatures between +5°C - +25°C. Protect from frost and direct sunlight.

SHELF LIFE

At least 24 months in unopened containers. Products should remain in their original unopened containers, bearing the manufacturers batch number.

PACKAGING

1kg cans

PACKAGING	CODE	BARCODE
1kg	01557	5204094015574

HEALTH AND SAFETY INFORMATION



Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects
Flam. Liq. 3: H226 - Flammable liquid and vapour
Skin Irrit. 2: H315 - Causes skin irritation
P101: If medical advice is needed, have product container or label at hand
P102: Keep out of reach of children
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P264: Wash thoroughly after handling
P280: Wear protective gloves/protective clothing/eye protection/face protection
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
P501: Dispose of contents/container according to the separated collection system used in your municipality. Substances that contribute to the classification: Xylene

Evochem®

EVOCHEM S.A.

Tzavardella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr





Adhesives & Sealants

BRUSH SEALANT

Technical Data Sheet

Reviewed: 06.09.2019

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



Evochem®

EVOCHEM S.A.

Tzavardella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr

