



Surface Adhesives

CARPET FIX

Technical Data Sheet

Reviewed: 30.07.2018



DESCRIPTION

CARPET FIX is a ready to use waterbased acrylic adhesive, suitable for rug and wall to wall carpet backing repair. Provides a new rubbery backing in worn carpets. Offers a great deal of features, such as fray-proofing, stitch locking and yarn reinforcement. Eliminates dust from the worn old substrate. Helps carpets retain their shape. The new backing will prevent sliding.

ADVANTAGES

- Prevents carpet movement and sliding
- Provides waterproof barrier between rug surface and floor
- Extends rug lifetime
- Does not transfer or leave residue on substrate
- Transparent when dry

APPLICATIONS

CARPET FIX is suitable for repairing worn backing in most machine made carpets and rugs.

INSTRUCTIONS FOR USE

1. Surfaces must be dry and clean from dust and grease.
2. Apply the adhesive with a brush or roller.
3. For best results apply two coats; allow the first coat to dry partially before applying the second coat.
4. Allow 24 hours or more for full cure before subjecting the carpet to heavy use.

It is advisable to perform a suitability test prior to full scale application

REMARKS

- Ideal application temperature: 18°C - 20°C
- Do not use below 12°C and relative humidity >60%
- Significant irregularities on the substrate's surface may lead to unsatisfactory bonding results.
- In order to avoid air bubbles inclusion spread the wallpaper gradually while unfolding.

CLEANING

Clean all equipment immediately after use with detergent and water.

SPREADING RATE

3-4 m²/kg

TECHNICAL CHARACTERISTICS

Consistency: Thick paste

Colour: White

Base: Special Polyvinyl acetate polymer

Dry film: Transparent, elastic

Odour: Slight

PH: 4-5

Water solubility: Unlimited at 20°C

Solids: 50 ± 1%

Specific gravity: 1,0 ± 0,03 gr/cm³ 25°C

Viscosity: 80000 - 100000 mpas 25°C BROOKFIELD

Flammability: Inflammable

Application temperature: +10°C - +30°C.

STORAGE

Store the containers in dry and cool storage conditions at temperatures 5°C - 30°C. Protect from moisture, frost and direct sunlight.

SHELF LIFE

At least 12 months in unopened containers. Products should remain in their original unopened containers, bearing the manufacturers batch number.

PACKAGING

Plastic containers: 1kg, 5kg

PACKAGING	CODE	BARCODE
1kg	1719	5204094017196
5kg	1714	5204094017141

HEALTH AND SAFETY INFORMATION



Eye Irrit. 2: H319 - Causes serious eye irritation Skin Sens. 1: H317 - May cause an allergic skin reaction P101: If medical advice is needed, have product container or label at hand P102: Keep out of reach of children P261: Avoid breathing dust/fume /gas/mist /vapours/spray P264: Wash thoroughly after handling P280: Wear protective gloves /protective clothing /eye protection/face protection P302+P352: IF ON SKIN: Wash with plenty of water P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P501: Dispose of contents and / or their container according to the separated collection system used in your municipality. Substances that contribute to the classification: Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS: 55965-84-9)

Evochem®

EVOCHEM S.A.

Tzaverdella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr





Surface Adhesives

CARPET FIX

Technical Data Sheet

Reviewed: 30.07.2018

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



Evochem®

EVOCHEM S.A.
Tzavardella place 13341, Fyli, Attica, Greece
Tel.: 210 5590460, 210 5590155 Fax: 210 5590244
E-mail: info@evochem.gr Website: www.evochem.gr

