

Cleaners CL17 OXY CLEAN

Technical Data Sheet

Reviewed: 30.07.2018



DESCRIPTION

OXY CLEAN CL 17 is extra strong concentrated cleaner suitable for ceramic tiles, tile grouts, natural and artificial stones. Removes fast, easily and effectively inorganic deposits such as cement, plaster, joint fillers etc. Cleans accumulated dirt from ageing, pollution, rain and frequent use. Removes persistent stains from oil, coffee, rust, paint etc. Restores the original appearance of surface applied. It is suitable for interior and exterior use.

ADVANTAGES

- Instant action
- · Very effective with stagnant stains
- Suitable for many surfaces
- · Restores the original appearance of surfaces
- · Exterior and interior use

APPLICATIONS

OXY CLEAN CL 17 is suitable for

- All types of absorptive and non-absorptive ceramic tiles such as cotto, terracotta, glazed and enameled tiles, pedestrian and garden cement tiles etc.
- Cement based tile grouts. Restores the original colour of the grout.
- Most types of natural stones such as Pilion and Karystos slates, building stones, decorative stones etc.
- Most types of artificial stones.
- Unpolished mosaic and cement floors
- Horizontal and vertical surfaces such as verandas, yards, garden patios, pedestrians, windowsills, building facades etc.
- It is suitable for interior and exterior use

CL 17 OXY CLEAN is highly recommended prior to the application of waterproofing and protection material WATER BLOCK.

INSTRUCTIONS FOR USE

- CL 17 OXY CLEAN is an extra strong cleaner. It is advisable to wear protective glasses and gloves.
- Plants, metal and porcelain surfaces must be carefully covered with plastic protection prior to application in order to avoid corrosion from vapours.
- Apply CL 17 OXY CLEAN on the surface and rub with a stiff brush. Allow soaking for 5 - 10 minutes. Do not allow the product to dry, brush occasionally.
- Remove the product from the surface with plenty of water, either wiping or rinsing.
- For persistent stains, repeat this process with longer working times and brushing.
- In case of light deposits, CL 17 OXY CLEAN can be diluted up to 20% with water.

REMARKS

- Due to the wide variety of substrates, a compatibility test is recommended in an inconspicuous spot prior to full scale application, in order to avoid rare circumstances of corrosion and staining.
- Allow 20 days after tiling and grouting before applying the product.
- CL 17 OXY CLEAN is not suitable for limestone, marble, decorative stones and sanitary ware.

CONSUMPTION

 $5 - 8 \text{ m}^2/\text{Lt}$

TECHNICAL CHARACTERISTICS

Form: Liquid Colour: Transparent

Odour: Characteristic of acid Specific gravity: 1 gr/ml 25°C Flammability: Not flammable

Application temperature: +5°C έως +35°C.

STORAGE

Products should be stored in a dry and cool place at a temperature of 5°C -35°C. Protect from humidity and direct sunlight.

SHELF LIFE

24 months from the production date in the above mentioned storage conditions. The product should remain in the original unopened packaging bearing the manufacturer's batch number.

PACKAGING

Plastic containers 1Lt, 4Lt

PACKAGING	CODE	BARCODE
1Lt	5004	5204094050049
4Lt	5005	5204094050056



EVOCHEM S.A.

Tzaverdella place 13341, Fyli, Attica, Greece Tel.: 210 5590460, 210 5590155 Fax: 210 5590244 E-mail: info@evochem.gr Website: www.evochem.gr











Cleaners CL17 OXY CLEAN

Technical Data Sheet

Reviewed: 30.07.2018

HEALTH AND SAFETY INFORMATION



Skin Corr. 1A: H314 - Causes severe skin burns and eye damage STOT SE 3: H335 - May cause respiratory irritation P101: If medical advice is needed, have product container or label at hand P102: Keep out of reach of children P264: Wash thoroughly after use P280: Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P501: Dispose of contents and / or their container according to the separated collection system used in your municipality Substances that contribute to the classification: Hydrochloric acid Restricted to professional users

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.









Tzaverdella place 13341, Fyli, Attica, Greece Tel.: 210 5590460, 210 5590155 Fax: 210 5590244 E-mail: info@evochem.gr Website: www.evochem.gr







