



DESCRIPTION

CL 38 TEAK CLEANER is a highly effective cleaner for teak and other types of tropical wood. Its unique concentrated formula enables easy removal of stains and weathering from exposure to environmental attack. Restores the original appearance of wood. Combine CL 38 TEAK CLEANER with TEAK OIL or DECK OIL to preserve and protect the clean surface.

ADVANTAGES

- High performance cleaning agent
- Highly concentrated
- · Restores the original appearance of wood
- Suitable for many types of timber

APPLICATIONS

- It is suitable for garden furniture, garden, pool and boat decks
- It is also suitable for any type of unvarnished wood construction such as pergolas, flower pots, fences etc.
- Can be applied on many types of tropical wood such as teak, iroko, bangirai, merbau, meranti as well as other types of exterior wood such as pine, fir, oregon etc.
- Regular application will help prevent the wood from greying and maintain the original colour and appearance.

INSTRUCTIONS FOR USE

- 1. Wet the surface to be cleaned and spray / apply the cleaner evenly.
- Scrub the surface across the wood grain with a scrub sponge or soft brush to remove dirt and residues.

Evochem®

EVOCHEM S.A.

Tzaverdella place 13341, Fyli, Attica, Greece Tel.: 210 5590460, 210 5590155 Fax: 210 5590244 E-mail: info@evochem.gr Website: <u>www.evochem.gr</u>

CL 38 TEAK CLEANER

Technical Data Sheet

Cleaners

- 3. Leave the cleaner on the wood for few minutes and scrub the surface again.
- 4. Rinse the whole area well with water, brushing at the same time to clear the grain.
- 5. Allow surface to dry out completely before applying TEAK OIL or DECKOIL.

CONSUMPTION 7-8m²/Lt

TECHNICAL CHARACTERISTICS

Form: Liquid Color: Transparent Odour: Characteristic of acid Density: 1,00 \pm 0.02 gr/cm³25 °C Flammability: Non Flammable Solubility in water: Unlimited Application temperature: +5°C έως +35°C

REMARKS

- Before use, test on an inconspicuous place.
- If the wooden surface was previously sealed with a film forming finish such as varnish or enamel paint, the finish must be completely removed with STRIPP N' CLEAN MERCOLA prior to application.
- Do not thin or add other soap to this product.
- The cleaner is very effective so care must be taken not to dull any paint and fiberglass or anodized aluminium.
- Wet the surfaces well prior to application and keep the cleaner to the wood area.
- Rinse well immediately after scrubbing.
- Do not use chlorine or other unsuitable cleaners for your teak wood, since they will destroy the wooden surface.

STORAGE

Products should be stored in a dry and cool place at a temperature of 5^{0} -35°C. Protect from humidity and direct sunlight.

SHELF LIFE

12 months from the production date in the above mentioned storage conditions. The product should remain in the original unopened packaging bearing the manufacturer's batch number.

PACKAGING

Spray 500ml, 4Lt

PACKAGING	CODE	BARCODE
Spray 500ml	05619	5204094056195
4Lt	05617	5204094056225

HEALTH AND SAFETY INFORMATION







Cleaners CL 38 TEAK CLEANER

Technical Data Sheet

Reviewed: 30.07.2018

H290 May be corrosive to metals. H319 - Causes serious eye irritation H315 Causes skin irritation. P102: Keep out of reach of children P264: Wash the hands thoroughly after handling P280: Wear protective gloves/ protective clothing/eye protection/face protection P337 + P313 If eye irritation persists: Get medical advice /attention P501: Dispose of contents and / or their container according to the separated collection system used in your municipality

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.





EVOCHEM S.A. Tzaverdella place 13341, Fyli, Attica, Greece Tel.: 210 5590460, 210 5590155 Fax: 210 5590244 E-mail: info@evochem.gr Website: www.evochem.gr

