



Surface Protection

CONCRETE SEALER

Technical Data Sheet

Reviewed: 06.06.2015



DESCRIPTION

CONCRETE SEALER is a high quality transparent, pure acrylic, sealer for stamped concrete and cementitious floors and artificial building materials. It has excellent penetrating capacity and UV resistance. It protects surfaces from humidity and stains. It offers significant strengthening and scrub resistance providing dust free surfaces. Depending on the number of coats applied creates a film, which protects and enhances the appearance of the artificial surfaces for decorative purposes. It is suitable for interior and exterior use.

ADVANTAGES

- Excellent finishing - enhances the natural beauty of surfaces
- Excellent penetration
- Excellent water repellence
- Excellent scrub resistance – dust-free surfaces
- Long lasting protection from stains, rain, humidity, fungi, mould etc.
- Resistance to temperature variations
- Excellent UV resistance
- Easy to apply – ready to use material
- Interior and exterior use

APPLICATIONS

- Protection and decoration of porous surfaces such as stamp concrete floors, artificial stones, cementitious and industrial floors and paving stones, bricks, artificial building materials, cement, decorative gypsum elements, concrete etc.
- Strengthening of loose or deteriorated substrates.

INSTRUCTIONS FOR USE

Substrate preparation

1. Surfaces must be dry and clean from dust unstable material, oil and rust.
2. New surfaces must be cleaned with wet sponge prior to application.
3. Old stained surfaces must be cleaned with OXY CLEAN CL 17 prior to application. Pressure clean surfaces if needed to remove dirt and use OXY CLEAN CL 17 for stagnant stains.
4. Surfaces must be completely dry prior to application.

Application

1. Stir material thoroughly before and during application.
2. Apply **CONCRETE SEALER** with a brush, roller or spray gun. Special attention must be given for even application.
3. When applied on very porous substrates a second coat is recommended. Allow at least 3 - 4 hours for drying between the two coats.
4. Windows, doors, plants etc must be carefully covered prior to application.
5. **CONCRETE SEALER** when dry is not harmful for humans and the environment.

CLEANING

Remove as much material as possible from brushes and rollers before cleaning. Clean all equipment immediately after use with nitro solvent or spray gun solvent.

REMARKS

Due to the wide variety of substrates and environmental conditions, a compatibility test is recommended in an inconspicuous spot prior to full scale application.

COVERAGE

8-10 m²/Lt depending on the surface texture, absorption and quality.

TECHNICAL CHARACTERISTICS

Type: Acrylic based sealer

Form: Liquid

Colour: Transparent

Odour: Typical of solvent

Specific gravity: 0,850 +/-5% gr/ml 25°C

Flammability: Flammable

Application temperature: +5°C έως +35°C

Thinning: 10%-20% depending on the surface with nitro solvent or spray gun solvent.

Drying time: Touch dry after 30 - 45 minutes. Recoat after 3 – 4 hours. Drying time depends on weather conditions and the thickness of the layer applied.

VOC (Volatile organic Compounds) CONTENT: (Directive 2004/42/CE) EU maximum VOC content limit values for this product (category A/h(SB):“binding primers-designed to stabilize loose substrate particles or impart hydrophobic properties”): 750 gr/lt (2010). This product contains maximum 745 gr/lt VOCs (ready for use product).

STORAGE

In a cool and dry place at temperatures between +5°C - +25°C, away from sources of ignition, flame and direct sunlight. Protect from frost.

SHELF LIFE

At least 12 months in unopened containers. Products should remain in their original unopened containers, bearing the manufacturers batch number.

Evochem®

EVOCHEM S.A.

Tzaverdella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr





Surface Protection

CONCRETE SEALER

Technical Data Sheet

Reviewed: 06.06.2015

PACKAGING

Tins 5Lt, 16Lt

PACKAGING	CODE	BARCODE
5Lt	5135	5204094051350
16Lt	5136	5204094051367

HEALTH AND SAFETY INFORMATION



Acute Tox. 4: H332 - Harmful if inhaled **Flam. Liq. 2: H225** - Highly flammable liquid and vapour **Repr. 2: H361d** - Suspected of damaging the unborn child **Skin Irrit. 2: H315** - Causes skin irritation **STOT RE 2: H373** - May cause damage to organs through prolonged or repeated exposure **STOT SE 3: H336** - May cause drowsiness or dizziness **P101:** If medical advice is needed, have product container or label at hand **P102:** Keep out of reach of children **P103:** Read label before use **P280:** Wear protective gloves/protective clothing/eye protection/face protection **P303+P361+P353:** IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower **P304+P340:** IF INHALED: Remove person to fresh air and keep comfortable for breathing **P370+P378:** In case of fire: Use ABC powder extinguisher to extinguish **P501:** Dispose of the contents/containers in accordance with the current legislation on waste treatment. Substances that contribute to the classification: Toluene (CAS: 108-88-3); Xylene (mixture of isomers) (CAS: 1330-20-7)

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



TECHNICAL SUPPORT

210.5590460

MONDAY TO FRIDAY 8:00 - 16:00

Evochem®

EVOCHEM S.A.
Tzaverdella place 13341, Fyli, Attica, Greece
Tel.: 210 5590460, 210 5590155 Fax: 210 5590244
E-mail: info@evochem.gr Website: www.evochem.gr

