



Wood Protection & Treatment DECOR XYLOFARM THIXO

Technical Data Sheet

Reviewed: 16.06.2023



DESCRIPTION

DÉCOR XYLOFARM THIXO is a thixotropic solvent-based wood stain varnish for easy and convenient application on vertical and horizontal surfaces with excellent performance and coverage. Based on a new hybrid polyurethane and acrylic technology, enriched with a blend of waxes and new technology special solvent-based resins it penetrates deeply into the wood protecting it against common environmental attacks. Contains UV filters for effective protection from exposure to the sun ultraviolet rays. It is water repellent, protects wood from discoloration, blue stains and deterioration. Does not peel, crack or blister (there is no need for sanding) and it is highly elastic. Offers effective protection from all weather conditions and enhances wood's natural beauty. Due to its ingredients, protects the dry film from fungus growth especially in areas exposed to high humidity or / and adverse weather conditions. It is suitable for interior and exterior use. It is available in transparent and many natural shades of wood.

ADVANTAGES

- **3 in 1: protects, decorates, waterproofs**
- Thixotropic – non drip
- New hybrid technology
- Enriched with a blend of waxes
- Long term protection – up to 8 years
- Contains UV filters
- Excellent penetration
- Highly elastic, does not peel, crack or blister
- Resistance to ageing
- Very easy application
- Interior and exterior use

APPLICATIONS

- Total protection and care of new wood constructions such as doors, window frames, ceilings, claddings, fences, roofs, pergolas and any other wooden surface.
- Maintenance of existing wooden surfaces, constructions and furniture.

INSTRUCTIONS FOR USE

1. Wooden surfaces must be clean from dust and grease. To remove grease and dust use **PRESTAIN CLEANER** and to remove resin use nitro solvent or acetone.
2. To remove old varnishes and paints use paint & varnish remover **STRIPP & CLEAN**.
3. The humidity of the wood must not exceed 12%.

4. It is advisable to apply 2 coats of wood preservative **XYLOFARM EXTRA**. In case of damaged wood by wood eating insects, apply one coat of **XYLOFARM AQUA KILLER** before the preservative.
5. Then apply **DÉCOR XYLOFARM** in 2-3 coats. When exposed in extreme weather conditions a third layer must be applied. Use transparent **DÉCOR XYLOFARM** during the second or third layer for lighter shades.
6. Light sanding (#220 – 280, 3M Fre – Cut™ 618) the wooden surface before application and between layers will guarantee proper adhesion and penetration along with best aesthetic result.
7. A well-ventilated area is necessary when the material is applied.
8. Close lid tightly after use and store in a cool place away from direct sunlight.

ATTENTION

Do not paint surfaces under direct sunlight. The wood stain will dry too quickly and will minimize the penetration effect. Painted surfaces must not be exposed to rain for the first 48 hours. Protecting horizontal flooring surfaces requires application of a floor varnish after the wood stain such as **PARQUET VARNISH AQUA**. Oil-based products are best applied with natural bristle brushes in contrast to water-based products which are best applied with synthetic bristle brushes.

LEAD STATEMENT

WARNING: Treatment of old surfaces such as dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Lead dust may be released. Lead is toxic. Exposure to lead dust can cause serious illness. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

CLEANING

Tools must be cleaned immediately after use with white spirit or nitro solvent.

COVERAGE

10 - 14 m²/Lt depending on wood absorption

TECHNICAL CHARACTERISTICS

Type: solvent based wood preservative based on special synthetic resins

Form: thixotropic liquid

Color: 16 shades

Odor: characteristic of solvents

Specific gravity: 820 kg/m³ 25°C

Viscosity: 20 sec 20°C

Application: brush, cloth, roller

Application temperature: +5°C έως +35°C.

Thinning: no thinning required, ready to use material

Drying time: touch dry after 2 hours, recoat after 6 hours.

VOC (Volatile Organic Compounds) CONTENT: (Directive 2004/42/CE) EU maximum VOC content limit values for this product (category Af(SB): Interior and exterior minimal build wood stains): 700 gr/lit. This product contains maximum 680 gr/lit VOCs.

Evochem®

EVOCHEM S.A.

Tzavardella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr





Wood Protection & Treatment DECOR XYLOFARM THIXO

Technical Data Sheet

Reviewed: 16.06.2023

SHADE	CODE	BARCODE
Transparent 750ml	05511	5204094055112
Transparent 2.5Lt	05512	5204094055129
Transparent 10Lt	5661	5204094056614
White 750ml	5823	5204094058236
White 2,5Lt	5824	5204094058243
White 10Lt	5825	5204094058250
Pine 750ml	05526	5204094055266
Pine 2.5Lt	05527	5204094055273
Pine 10Lt	5814	5204094058144
Oregon 750ml	5746	5204094057468
Oregon 2.5Lt	5747	5204094057475
Oregon 10Lt	5815	5204094058151
Oak 750ml	05570	5204094055594
Oak 2,5Lt	05571	5204094055600
Oak 10Lt	5561	5204094055617
Light Oak 750ml	5844	5204094058441
Light Oak 2,5Lt	5845	5204094058458
Light Oak 10Lt	5847	5204094058472
Chestnut 750ml	05514	5204094055143
Chestnut 2.5Lt	05515	5204094055150
Chestnut 10Lt	5812	5204094058120
Walnut 750ml	05517	5204094055174
Walnut 2.5Lt	05518	5204094055181
Walnut 10Lt	5813	5204094058137
Iroko 750ml	5848	5204094058489
Iroko 2,5Lt	5849	5204094058496
Iroko 10Lt	5851	5204094058519
Teak 750ml	05528	5204094055358
Teak 2.5Lt	05519	5204094055518
Teak 10Lt	5552	5204094055525
Olive 750ml	05564	5204094055563
Olive 2,5Lt	05565	5204094055570
Olive 10Lt	5558	5204094055587
Wenge 750ml	05560	5204094055532
Wenge 2,5Lt	05561	5204094055549
Wenge 10Lt	5555	5204094055556
Mahogany 750ml	05520	5204094055204
Mahogany 2,5Lt	05521	5204094055211
Mahogany 10Lt 1	5522	5204094055228
Gray 750ml	5852	5204094058526
Gray 2,5Lt	5853	5204094058533
Gray 10Lt	5855	5204094058557
Cypress 750ml	05523	5204094055235
Cypress 2,5Lt	05524	5204094055242
Cypress 10Lt	5525	5204094055259
Blue 750ml	05552	5204094055297
Blue 2,5Lt	05553	5204094055303
Blue 10Lt	5531	5204094055310

STORAGE

Store in dry and cool storage conditions at temperatures 5°C -30°C. Protect from moisture, frost, and direct sunlight.

SHELF LIFE At least 36 months in unopened containers. Products should remain in their original unopened containers, bearing the manufacturers batch number.

PACKAGING

750ml, 2,5Lt, 10Lt

HEALTH AND SAFETY INFORMATION

Consult Material Safety Data Sheet prior to application.

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



TECHNICAL SUPPORT

210.5590460

MONDAY TO FRIDAY 8:00 - 16:00

Evochem®

EVOCHEM S.A.

Tzavredella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr



DECOR XYLOFARM COLOUR SHADES



White



Transparent



Pine



Oregon



Oak



Light Oak



Chestnut



Walnut



Iroko



Teak



Olive



Wenge



Mahogany



Gray



Cypress



Blue

NEW

NEW