

**DESCRIPTION**

ISOMIX BETON PRIMER is an excellent adhesion quartz primer based on a blend of acrylic resins and selected quartz sand. It is specially formulated for smooth and low absorption surfaces. It shows great resistance in an alkaline environment.

ADVANTAGES

- Excellent surface adhesion and high capacity of penetration on low absorption surfaces.
- Ideal for strengthening the surface applied
- Adhesion bridge for the application of wall plaster or other mortars.
- Dries fast and does not cause yellowing
- Interior and exterior use
- Easy to apply – coloured for distinguishing applied areas

APPLICATIONS

- Suitable for priming smooth surfaces as an adhesion bridge before the application of wall plaster or acrylic stucco.
 - It is suitable for priming smooth cement surfaces, plasterboards, polystyrene plates EPS & XPS, concrete etc.
 - It is also suitable for priming the surface of old ceramic tiles before laying and gluing new ones on top.
- It is advisable to perform a suitability test prior to full scale application.**

INSTRUCTIONS FOR USE**Surface preparation**

Surfaces must be dry and clean from dust, grease and loose particles and other contamination

Application

1. **ISOMIX BETON PRIMER** is ready to use – does not need any thinning.
2. Stir the product very well prior its application.
3. Apply with a roller or other available spraying system.

CLEANING

Clean all equipment immediately after use with soapy water.

SPREADING RATE

0,2 – 0,4 kg/m² depending on the surface's porosity.

TECHNICAL CHARACTERISTICS

Type: Viscous liquid
Colour: Light brick color
Smell: Characteristic
pH: 8.5 – 9
Vapour tension (20°C): 24hPa
Specific gravity: 1530-1630 kg/m³ 25°C
Viscosity: 15000-25000 mPas 23 °C
Diluted: Water
Drying times: 2 - 3 hours,

STORAGE

Store in dry and cool storage conditions at temperatures 5°C - 30°C. Protect from moisture, frost and direct sunlight.

SHELF LIFE

At least 12 months in unopened containers. Products should remain in their original unopened containers, bearing the manufacturers batch number.

PACKAGING

4 kg and 15 kg

PACKAGING	CODE	BARCODE
4kg	07027	5204094070276
15kg	07033	5204094070405

HEALTH AND SAFETY INFORMATION

P101: If medical advice is needed, have product container or label at hand **P102:** Keep out of reach of children **P103:** Read label before use **P501:** Dispose of the contents/containers in accordance with the current legislation on waste treatment **EUH208:** Contains Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one[EC no. 220-239-6] (3:1). May produce an allergic reaction



The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.

