



Plasterboard & Cementboard Products

ISOMIX FIBRETAPE

Technical Data Sheet

Reviewed: 06.06.2015



PACKAGING

5cm X 25m, 5cm X 90m

PACKAGING	CODE	BARCODE
5cm X 25m	08288	5204094082880
5cm X 90m	08289	5204094082897

DESCRIPTION

ISOMIX FIBRE TAPE is a fiberglass self-adhesive tape suitable for plasterboard joints as well as for reinforcing cracks and joints on plaster and other building surfaces. It is coated with anti-alkaline dressings to prevent quick aging of the plaster -filler due to the corrosive action of alkalis present in coating mortars. It presents dimensional stability and tear resistance. Colour white, dimensions 5cm X 25m and 5cm X 90m.

ADVANTAGES

- Crack preventing
- Improved resistance and durability of coatings - fillers
- Dimensional stability
- High tensile strength and elastic properties
- Resistance to temperature variations
- High resistance to alkali environment

APPLICATIONS

- Reinforces plasterboard joints
- Reinforces joints, gaps, cracks, holes etc.
- It can be embedded in ISOMIX ARMOGIPS or JOINT FILLER
- Suitable for interior and exterior use.

INSTRUCTIONS FOR USE

- The fiberglass tape is placed on the joint, followed by the plaster - filler application. The tape must be embedded in the coat.

TECHNICAL CHARACTERISTICS

Roll length: 25m, 90m

Roll width: 5cm

Size of weave: 3mmX3mm

Colour: White

Coating: Acrylic resins

Tensile strength: 7,8 kN/m

STORAGE

Must be stored in a cool storage conditions from +0°C έως +40°C.

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



Evochem®

EVOCHEM S.A.

Tzavardella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr

