



DESCRIPTION

JOINT FILLER is a ready mixed white acrylic plasterboard filler suitable for filling joints and cracks as well as smoothing and preparing surfaces prior to painting. It provides a flat and smooth final surface ready for priming and painting. It is also suitable for filling and coating cracks and holes on plaster and concrete surfaces.

ADVANTAGES

- Ready mixed formula
- Smoothes uneven surfaces
- Excellent workability, offers a tough smooth finish
- Dries fast
- Presents low shrinkage
- Forms a perfect substrate, ready for painting
- Interior use
- Rapid and clean application

APPLICATIONS

- It is suitable for filling and coating cracks as well as smoothing and preparing plasterboards prior to painting.
- Filling and grouting plasterboards combined with joint tapes
- Fills gaps and imperfections on plaster and gypsum surfaces and constructions.

INSTRUCTIONS FOR USE

Surfaces must be dry and clean from dust, grease, loose particles and other contamination. For deeper cracks or joints application of water-based primer ISOCRYL PRIMER DUR AQUA is recommended.

Smoothing surfaces

1. Apply filler with a spatula in two layers
2. Allow the first coat to dry before applying the second

Grouting and gap filling

1. Place the self-sticking tape along the joint or crack
2. Apply filler with a spatula in two layers
3. Allow the first coat to dry before applying the second
4. If a non self-sticking tape is used apply a first layer of filler along the joint
5. While the product is still fresh place the tape along the joint and press it into the filler
6. Allow the first coat to dry and follow with the second layer

7. Allow the second coat to dry and follow with sanding to a smooth finish
 8. The final surface may be primed and painted
 9. Close lid immediately after use to prevent drying
- It is advisable to perform a suitability test prior to full scale application**

CLEANING UP

Remove as much material as possible from tools before cleaning. Clean all equipment immediately after use with warm water.

REMARKS

- Do not use to fill plastics or metals
- Do not apply in temperatures (ambient and surface) below 5°C
- Not suitable for repairs to permanently wet areas

COVERAGE

2 - 3 kg/m²

TECHNICAL CHARACTERISTICS

Type: Acrylic surface filler

Consistency: Thixotropic paste

Colour: White

Smell: Characteristic of acrylic resin

Specific gravity: 1650- 1700 kg/m³ 25°C

Method of application: Spatula

Curing System: Physical drying

Drying times: May be sanded in 4 - 5 hours, depending on ambient temperature

Application temperature: 5°C - 35°C

STORAGE

In a cool and dry place at temperatures between +5°C - +25°C

SHELF LIFE

12 months in an unopened packaging in the above mentioned storage conditions.

PACKAGING

1kg, 6kg

PACKAGING	CODE	BARCODE
1kg	07018	5204094070184
6kg	07031	5204094070160



HEALTH AND SAFETY INFORMATION

EUH208: Περιέχει μίγμα των : 5-χλωρο-2-μεθυλο-4-ισοθειαζολιν-3-όνη [EC no. 247-500-7] και 2-μεθυλο-2H-ισοθειαζολ-3-όνη [EC no. 220-239-6] (3:1). Μπορεί να προκαλέσει αλλεργική αντίδραση.

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.

