



DESCRIPTION

MINOS WHEEL PAINT is a premium grade metallized paint specially formulated to repair, refresh and renovate metal wheels. Dries fast and provides a tough, long lasting finish that resists scratches and nicks, and will not tarnish, weather or rust.

ADVANTAGES

- Metallic shine
- Excellent coverage
- Dries fast
- Durable finish resists dust and chemicals
- Restores to the original wheel appearance
- Resists cracking, flaking, peeling
- Easy to use

APPLICATIONS

MINOS WHEEL PAINT is suitable for repairing, refreshing and renovating metal wheels, hubcaps, auto trims, motorcycles, bicycles and other metal surfaces.

METHOD OF APPLICATION

Surface preparation

The surface should be clean, dry and free of grease. Sand the surface to remove loose paint, varnish and rust.

Application

1. Before use, shake the can for 2 minutes and spray a sample.
2. Apply in several thin layers on the surface to be treated from a distance of 25-30cm.
3. Shake the can before applying the next layer.
4. After use, turn can upside down and press the nozzle for 5" to clean the valve.

CLEANING

With white spirit

CONSUMPTION

2-3m²/400ml

TECHNICAL DATA

Form: Liquid

Colour: Silver metallic

Odour: Characteristic

Relative density: 0,78gr/ml

Touch dry: 10 - 25 minutes

Final curing: 1 - 2 hours

Temperature resistance: Up to 80°C

Application temperature: 10°C - 30°C

VOC (Volatile Organic Compounds) CONTENT: (Directive 2004/42/CE) EU maximum VOC content limit values for this product (category Be 'Special finishes'): 840 gr/lit (2010). This product contains maximum 820 gr/lit VOCs (ready for use product).

STORAGE

In a cool and dry place at temperatures between +5°C - +25°C away from sources of ignition. Avoid direct sunlight.

SHELF LIFE

At least 5 years in unopened original package, under above mentioned storage conditions.

PACKAGING

Spray 400ml

PACKAGING	CODE	BARCODE
400ml	9220	5204094092209

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION



Aerosol 1: H229 - Pressurized container: May burst if heated
Aerosol 1: H222 - Extremely flammable aerosol
Eye Irrit. 2: H319 - Causes serious eye irritation
Skin Irrit. 2: H315 - Causes skin irritation
STOT SE 3: H336 - May cause drowsiness or dizziness
P101: If medical advice is needed, have product container or label at hand
P102: Keep out of reach of children
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211: Do not spray on an open flame or other ignition source
P251: Do not pierce or burn, even after use
P280: Wear protective gloves/protective clothing/eye protection/face protection
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F
P501: Dispose of contents and / or their container according to the separated collection system used in your municipality
EUH066: Repeated exposure may cause skin dryness or cracking.
Substances that contribute to the classification: Acetone; Ethyl acetate

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.

