



DESCRIPTION

MINOS SIGNAL HORN is a gas horn with strong acoustic signal. Provides a brilliant form of temporary alarm cover. Warns of danger in case of fire, fog etc.

ADVANTAGES

- Easy to use
- Strong signal
- Replacement containers available

APPLICATIONS

It is ideal for small boats, constructions sites, excursions, sports etc.

METHOD OF APPLICATION

1. Screw the horn on the container valve.
2. Press the button firmly on the top of the horn.
3. Keep the container always in a vertical position.

TECHNICAL DATA

Form: Liquid

Colour: Transparent

Odour: Characteristic

Density at 20°C: 470 kg/m³

Temperature resistance: Up to 80°C

Application temperature: 10°C - 30°C

STORAGE

In a cool and dry place at temperatures between +5°C - +25°C away from sources of ignition. Avoid direct sunlight.

SHELF LIFE

At least 5 years in unopened original package, under above mentioned storage conditions.

PACKAGING

Gas horn set 450ml and gas horn replacement 450ml

PACKAGING	CODE	BARCODE
Gas horn set 450ml	9242	5204094092421
Gas horn replacement 450ml	95185	5204094090106

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION



H220 Extremely flammable gas H280 Contains gas under pressure; may explode if heated P102 Keep out of reach of children P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P243 Take precautionary measures against static discharge P202 Do not handle until all safety precautions have been read and understood P308 + P313 IF exposed or concerned: Get medical advice/attention P410 + P403 Protect from sunlight. Store in a well-ventilated place P412 Do not expose to temperatures exceeding 50°C/122°F. Substances that contribute to the classification: Hydrocarbons, C3-4-rich, petroleum distillates CAUTION! Do not leave the product in a car, boat or other closed areas exposed to direct sunlight.

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.

