



#### DESCRIPTION

**MINOS SILICONE SPRAY** is a multi-purpose, colorless silicone-based lubricant suitable for lubrication, waterproofing and protection of plastic, rubber and metal parts. Forms a transparent protective film that eliminates squeaks and protects surfaces from humidity and weather conditions. Suitable for use on most materials such as metals, plastics, wood etc.

#### ADVANTAGES

- Excellent penetration
- Water-repellent
- Resistant to weather influences
- High heat resistant
- Prevents freezing and drying out of rubber parts
- Prevents creaking and squeaking of plastic parts
- Easy to apply
- Environmentally friendly

#### APPLICATIONS

**MINOS SILICONE SPRAY** has thousands of uses around the house, at work, hobbies etc.

- Mould releasing and lubrication in the automotive, clothing and furniture industries where the clean, low toxicity lubrication properties of silicone are ideal.
- Ideal for waterproofing surfaces such as camping accessories (tents, umbrellas) marine parts, boats etc.
- Great for use on belts, linkages, pulleys, valves, slide conveyors, guide rails, tools, locks, doors, hinges, and more.
- Lubrication and protection for dashboards, leatherette and rubber parts.

#### METHOD OF APPLICATION

##### Surface preparation

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand metal surfaces.

##### Application

1. Before use, shake the can for 2 minutes.
2. Apply a thin layer of MINOS SILICONE SPRAY from a distance of 25-30cm.
3. Optimum lubrication is obtained after evaporation of the solvents.
4. After use, turn can upside down and press the nozzle for 5" to clean the valve.

#### CLEANING

With white spirit

#### CONSUMPTION

Depends on application

#### TECHNICAL DATA

**Form:** Liquid

**Colour:** Transparent

**Odour:** Characteristic

**Relative density:** 0,75gr/ml

**Application temperature:** 10°C - 30°C

**VOC (Volatile Organic Compounds) CONTENT:** (Directive 2004/42/CE) EU maximum VOC content limit values for this product (category Be 'Special finishes'): 840 gr/lt (2010). This product contains maximum 820 gr/lt VOCs (ready for use product).

#### STORAGE

In a cool and dry place at temperatures between +5°C - +25°C away from sources of ignition. Avoid direct sunlight.

#### SHELF LIFE

At least 5 years in unopened original package, under above mentioned storage conditions.

#### PACKAGING

Spray 400ml

PACKAGING	CODE	BARCODE
400ml	9203	5204094092032

#### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION



Aerosol 1: H229 - Pressurized container: May burst if heated  
Aerosol 1: H222 - Extremely flammable aerosol  
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects  
P101: If medical advice is needed, have product container or label at hand  
P102: Keep out of reach of children  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P211: Do not spray on an open flame or other ignition source  
P251: Do not pierce or burn, even after use  
P273: Avoid release to the environment  
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F  
P501: Dispose of contents and / or their container according to the separated collection system used in your municipality

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.

