



DESCRIPTION

PGP ACRYLIC FILLER is ready mixed white acrylic masonry filler suitable for both interior and exterior use. It is suitable for smoothing and preparing surfaces prior to painting, as well as filling and coating cracks and holes on walls, ceilings, floors and doors. May be applied on plaster, concrete, brick, stones, render and wood.

ADVANTAGES

- Ready mixed formula
- Smoothens uneven surfaces
- Excellent workability, offers a tough smooth finish
- Dries fast and can be easily sanded
- Presents low shrinkage – does not crack
- Forms a non-absorbent white substrate, ready for painting
- Interior and exterior use
- Rapid and clean application

APPLICATIONS

- It is suitable for smoothing and preparing as well as filling cracks of interior and exterior walls and ceilings prior to the final coat.
- It is suitable for plaster, smooth concrete surfaces, aerated concrete blocks, plasterboards, cementboards etc.

INSTRUCTIONS FOR USE

1. Surfaces must be dry and clean from dust, grease and loose particles and other contamination
2. For deeper cracks or joints application of water-based acrylic primer is necessary
3. Apply with a spatula or spreader
4. Press the filler onto the surface to a maximum depth of 9mm
5. For deep cavities apply in layers and allow each to dry (approximately 1 hour)
6. Fill hole proud to allow for sanding and finish with a wet knife
7. Once dry, sand to a smooth finish
8. The final surface may be primed and painted
9. Close lid immediately after use to prevent drying

It is advisable to perform a suitability test prior to full scale application

REMARKS

- Do not use to fill plastics or metals
- Do not apply externally when rain is imminent (within 5 hours of application)

- Do not apply at temperatures (ambient and surface) below 5°C
- Not suitable for repairs to permanently wet areas
- Do not apply in layers more than 9mm deep. For deeper holes build up in layers allowing each layer to dry before applying the next

CLEANING

Remove as much material as possible from tools before cleaning. Clean all equipment immediately after use with warm water.

TECHNICAL CHARACTERISTICS

Type: Acrylic surface filler

Consistency: Thixotropic paste

Colour: White

Smell: Characteristic of acrylic resin

Specific gravity: 1800- 1850 kg/m³ 25°C

Method of application: Spatula

Curing System: Physical drying

Drying times: May be sanded in 3 - 4 hours, depending on ambient temperature

Application temperature: 10°C - 35°C

STORAGE

Store in dry and cool storage conditions at temperatures 5°C-30°C. Protect from moisture, frost and direct sunlight.

SHELF LIFE

At least 12 months in unopened containers. Products should remain in their original unopened containers, bearing the manufacturers batch number.

PACKAGING

400gr, 800gr, 5kg

PACKAGING	CODE	BARCODE
400gr	7157	5204094071570
800gr	7158	5204094071587
5kg	7159	5204094071594

HEALTH AND SAFETY INFORMATION

P101: If medical advice is needed, have product container or label at hand **P102:** Keep out of reach of children **P103:** Read label before use **P501:** Dispose of the contents/containers in accordance with the current legislation on waste treatment **EUH208:** Contains Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one[EC no. 220-239-6] (3:1). May produce an allergic reaction



Fillers

PGP ACRYLIC FILLER

Technical Data Sheet

Reviewed: 06.06.2015

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



Evochem®

EVOCHEM S.A.
Tzavardella place 13341, Fyli, Attica, Greece
Tel.: 210 5590460, 210 5590155 Fax: 210 5590244
E-mail: info@evochem.gr Website: www.evochem.gr

