

Plumbing Products PVC PRIMER

Technical Data Sheet

Reviewed: 06.06.2015



DESCRIPTION

PVC PRIMER is a specially formulated solvent for cleaning and preparing the PVC pipes prior to bonding. It removes grease, oil and dirt from PVC pipes. It attacks the PVC surface, allowing a deep penetration of the adhesive which results in a strong permanent joint.

ADVANTAGES

- Degreasing and cleaning
- Deep penetration
- Guarantees perfect bonding
- Fast drying formula

APPLICATIONS

- Degreasing, cleaning and preparing PVC pipes for high strength bonding
- Suitable as a thinner for PVC ADHESIVE
- Release joints of PVC pipes through impregnation of the connection joint

INSTRUCTIONS FOR USE

Apply **PVC PRIMER** with the special brush provided on surfaces to be bonded

Clean and degrease surfaces thoroughly and allow drying. Follow with PVC adhesive for a high strength bond.

It is advisable to perform a suitability test for each application.

TECHNICAL CHARACTERISTICS

Consistency: Liquid Colour: Transparent Smell: Characteristic Application method: Brush

Thinning: none

Specific gravity: 0,805 gr/m³ 20°C Application temperature: +10°C - +30°C

STORAGE

Products should be stored in a dry and cool place at a temperature of 5°-35°C, away from sources of ignition. Protect from humidity and direct sunlight.

SHELF LIFE

12 months from the production date in the above mentioned storage conditions. The product should remain in the original unopened packaging bearing the manufacturer's batch number.

PACKAGING

Tins 500ml

PACKAGING	CODE	BARCODE
500ml	01880	5204094018803

HEALTH AND SAFETY INFORMATION



Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 2: H225 - Highly flammable liquid and vapour STOT SE 3: H336 - May cause drowsiness or dizziness P101: If medical advice is needed, have product container or label at hand P102: Keep out of reach of children P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P264: Wash thoroughly after use P280: Wear protective gloves/protective clothing/eye protection/face protection P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P501: Dispose of contents and / or their container according to the separated collection system used in your municipality EUH066: Repeated exposure may cause skin dryness or cracking

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.

TECHNICAL SUPPORT 210.5590460

MONDAY TO FRIDAY 8:00 - 16:00





Tzaverdella place 13341, Fyli, Attica, Greece Tel.: 210 5590460, 210 5590155 Fax: 210 5590244 E-mail: info@evochem.gr Website: www.evochem.gr







