



DIY Products

SLIP OIL

Technical Data Sheet

Reviewed: 06.06.2015



DESCRIPTION

All-purpose liquid lubrication oil suitable for protection and lubrication in moving mechanical parts. Reduces friction and protects from rust, corrosion and humidity. Its precise, easy to use drip spout enables precise application, drop by drop.

ADVANTAGES

- Excellent lubricating properties
- Excellent penetration
- Corrosion protection
- Solvent-free
- Easy application

APPLICATIONS

- It is ideal for lubricating brake linkages, tools, latches, cams, window regulators, locks, hinges, springs, sliding doors and windows, sewing machines, bicycles etc.
- It is ideal for all moving mechanical parts.

INSTRUCTIONS FOR USE

1. Apply oil directly from nozzle on the substrate
2. Allow product to soak for a while and if needed apply once more.

CLEANING UP

Clean residues with warm water and soap.

CONSUMPTION

1,5 ml/cm

TECHNICAL CHARACTERISTICS

Physical form: Greasy liquid

Colour: Yellowish

Odour: Characteristic

Relative density: 0,90 gr/ml

Temperature resistance: Up to 150°C

Application temperature: 10°C - 35°C

STORAGE

In a cool and dry place at temperatures between +5°C - +25°C

SHELF LIFE

At least 2 years in unopened packaging in the above mentioned storage conditions

PACKAGING

80ml bottle

PACKAGING	CODE	BARCODE
80ml	9154	5204094091547

HEALTH AND SAFETY INFORMATION

The product is not classified as dangerous according to CLP Regulation (EC) n° 1272/2008

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



Evochem®

EVOCHEM S.A.

Tzavardella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr

