



Surface Adhesives

SUPER TAPIS

Technical Data Sheet

Reviewed: 06.06.2015



DESCRIPTION

SUPER TAPIS is a ready to use mixed paste adhesive, based on a polymer dispersion of PVAC, specially formulated for wallpaper application. It offers extra strong bonding and high performance on many different substrates. It has an excellent temperature and humidity resistance.

ADVANTAGES

- Excellent bonding strength
- Humidity resistance
- Temperature resistance
- Environmentally friendly

APPLICATIONS

SUPER TAPIS is suitable for bonding plain, plasticized and special types of wallpaper, on various different substrates such as wood, walls, chipboard and hardboard, MDF, formica, metallic surfaces etc.

INSTRUCTIONS FOR USE

1. All surfaces must be dry and clean from dust and grease and fit closely together
2. Stir adhesive thoroughly before use
3. Always refer to wallpapers manufacturers label for specific hanging instructions
4. Apply the adhesive with a brush or a toothed spatula
5. After spreading the adhesive on the surface, position the wallpaper and apply pressure, preferably with a roller (leveling)

It is advisable to perform a suitability test prior to full scale application

REMARKS

- Ideal application temperature: 18°C - 20°C
- Do not use below 12°C and relative humidity >60%
- Significant irregularities on the substrate's surface may lead to unsatisfactory bonding results.
- In order to avoid air bubbles inclusion spread the wallpaper gradually while unfolding.

CLEANING

Clean all equipment immediately after use with detergent and water.

CONSUMPTION

150 - 200 gr / m² depending on surface porosity and condition

TECHNICAL CHARACTERISTICS

Consistency: Thick paste

Colour: White

Base: Special Polyvinyl acetate polymer

Dry film: Transparent, elastic

Odour: Slight

PH: 4-5

Water solubility: Unlimited at 20°C

Solids: 50 ± 1%

Specific gravity: 1,0 ± 0,03 gr/cm³ 25°C

Viscosity: 80000 - 100000 mpas 25°C BROOKFIELD

Flammability: Inflammable

STORAGE

Store the containers in dry and cool storage conditions at temperatures 5°C - 30°C. Protect from moisture, frost and direct sunlight.

SHELF LIFE

At least 12 months in unopened containers. Products should remain in their original unopened containers, bearing the manufacturers batch number.

PACKAGING

Plastic containers 1kg, 5kg

PACKAGING	CODE	BARCODE
1kg	01719	5204094017172
5kg	01715	5204094017158

Evochem®

EVOCHEM S.A.

Tzavardella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr





Surface Adhesives

SUPER TAPIS

Technical Data Sheet

Reviewed: 06.06.2015

HEALTH AND SAFETY INFORMATION

P101: If medical advice is needed, have product container or label at hand **P102:** Keep out of reach of children **P103:** Read label before use **P501:** Dispose of the contents / containers in accordance with the current legislation on waste treatment
EUH208: Contains Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one[EC no. 220-239-6] (3:1). May produce an allergic reaction.

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



Evochem®

EVOCHEM S.A.

Tzavardella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr

