



Solvents

SWAN ACETONE

Technical Data Sheet

Reviewed: 06.06.2015



HEALTH AND SAFETY INFORMATION

PROTECT THE ENVIRONMENT – USE CHEMICALS WITH CAUTION



Causes serious eye irritation. Highly flammable liquid and vapour. May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Wash thoroughly after use. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of contents and / or their container according to the separated collection system used in your municipality. Repeated exposure may cause skin dryness or cracking.

DESCRIPTION

SWAN ACETONE is an organic solvent produced from propane. It is mainly used as a cleaning and degreasing solvent and as a solvent and thinner for paints and other chemicals.

APPLICATIONS

- Cleaning equipment and surfaces.
- Paint thinner.
- Dissolves two-part epoxies and super glue before hardening.
- Heavy-duty degreaser, especially for metal prior to painting.

TECHNICAL CHARACTERISTICS

Type: Organic solvent produced from propane

Consistency: Liquid

Colour: Transparent

Smell: Characteristic

Relative density: 0.79 ± 0.02 gr/cm³ 25 °C

Flammability: Flammable

Solubility (% by weight in water): < 0.1

STORAGE

Products should be stored in a dry and cool place at a temperature of 5°C -35°C, away from sources of ignition. Protect from humidity and direct sunlight.

SHELF LIFE

24 months from the production date in the above mentioned storage conditions. The product should remain in the original unopened packaging bearing the manufacturer's batch number.

PACKAGING

750ml, 4Lt, 16Lt

PACKAGING	CODE	BARCODE
750ml	06043	5204094060437
4Lt	06012	5204094060383
16Lt	06039	5204094060390

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



Evochem®

EVOCHEM S.A.

Tzavardella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr

