



Solvents

SWAN LINSEED OIL

Technical Data Sheet

Reviewed: 06.06.2015



PACKAGING

750ml, 4Lt, 16Lt

PACKAGING	CODE	BARCODE
750ml	06044	5204094060444
4Lt	06075	5204094060086
16Lt	06071	5204094060093

HEALTH AND SAFETY INFORMATION

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Dispose of the contents/containers in accordance with the current legislation on waste treatment

DESCRIPTION

SWAN LINSEED OIL is high quality pure oil coming from flax seeds. It contains a mixture of fatty acid glycerids, including linoleic and linolenic acid. It has several uses as an admixture, paint additive or as a primer.

APPLICATIONS

- Applied as a primer on building surfaces
- Used as an additive for production of masonry filler
- Used as a painting additive, making oil paints more fluid, transparent and glossy.
- When used as a wood finish, linseed oil soaks into the pores, leaving a shiny but not glossy surface that shows off the grain of the wood.

TECHNICAL CHARACTERISTICS

Consistency: Oily liquid
Colour: Brown
Smell: Characteristic
Specific gravity: 0,93 kg/Lt 25°C
Flash point: >100°C (Abel).
Flammability: Non flammable.
Application temperature: 5°C - 35°C

STORAGE

Products should be stored in a dry and cool place at a temperature of 5°C -35°C, away from sources of ignition. Protect from humidity and direct sunlight.

SHELF LIFE

12 months from the production date in the above mentioned storage conditions. The product should remain in the original unopened packaging bearing the manufacturer's batch number.

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



Evochem®

EVOCHEM S.A.
Tzavardella place 13341, Fyli, Attica, Greece
Tel.: 210 5590460, 210 5590155 Fax: 210 5590244
E-mail: info@evochem.gr Website: www.evochem.gr

