

# Solvents SWAN NITRO SOLVENT

**Technical Data Sheet** 

Reviewed: 06.06.2015



### DESCRIPTION

**SWAN NITRO SOLVENT** is a clear – transparent solvent based on blend of organic solvents with high evaporation speed. It is mainly used as a thinner in the metal, structural and wood sectors.

## **APPLICATIONS**

- Thinning solvent borne coatings and primers.
- · Cleaning equipment after painting.

# **TECHNICAL CHARACTERISTICS**

Type: A blend of ketone, ester, alcohol and aromatic solvents

Consistency: Liquid Colour: Water white Smell: Characteristic

Relative density: 0.82 ± 0.02 gr/cm<sup>3</sup> 25 °C

Flammability: Flammable

Solubility (% by weight in water): < 0.1

# **STORAGE**

Products should be stored in a dry and cool place at a temperature of 5°C -35°C, away from sources of ignition. Protect from humidity and direct sunlight.

# SHELF LIFE

12 months from the production date in the above mentioned storage conditions. The product should remain in the original unopened packaging bearing the manufacturer's batch number.

# **PACKAGING**

750ml, 4Lt, 16Lt

PACKAGING	CODE	BARCODE
750ml	06019	5204094060192
4Lt	06029	5204094060161
16Lt	06017	5204094060178

# **HEALTH AND SAFETY INFORMATION**



May be fatal if swallowed and enters airways. Highly flammable liquid and vapour. Suspected to damage the fetus. Causes skin irritation. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Do NOT induce vomiting. Dispose of the contents/containers in accordance with the current legislation on waste treatment. Repeated exposure may cause skin dryness or cracking. Substances that contribute to the classification: Toluene; Ethyl Acetate.

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.





**EVOCHEM S.A.** 

Tzaverdella place 13341, Fyli, Attica, Greece Tel.: 210 5590460, 210 5590155 Fax: 210 5590244 E-mail: info@evochem.gr Website: www.evochem.gr







