



Solvents

SWAN POLYURETHANE SOLVENT EXTRA

Technical Data Sheet

Reviewed: 06.06.2015



HEALTH AND SAFETY INFORMATION



May be fatal if swallowed and enters airways. Causes serious eye irritation. Highly flammable liquid and vapour. Suspected to damage the fetus. Causes skin irritation. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep container tightly closed. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of the contents/containers in accordance with the current legislation on waste treatment. Repeated exposure may cause skin dryness or cracking. Substances that contribute to the classification: Toluene; 2-butanone

DESCRIPTION

SWAN POLYURETHANE SOLVENT EXTRA is a colorless organic solvent blend based on highly volatile organic solvents, providing quick drying. It is mainly used as a thinner for polyurethane varnishes and lacquers, when the temperature of the environment is normal or low.

APPLICATIONS

- Provides quick drying when used for polyurethane varnishes and lacquers
- Effective paint tools cleaning

TECHNICAL CHARACTERISTICS

Type: Solvent blend comprised of ketones, esters, aliphatic and aromatic solvents

Consistency: Liquid

Colour: Transparent

Smell: Characteristic

Relative density: $0.87 \pm 0.02 \text{ gr/cm}^3$ 25°C

Flammability: Flammable

Solubility (% by weight in water): < 0.1

STORAGE

Products should be stored in a dry and cool place at a temperature of 5°C - 35°C , away from sources of ignition. Protect from humidity and direct sunlight.

SHELF LIFE

12 months from the production date in the above mentioned storage conditions. The product should remain in the original unopened packaging bearing the manufacturer's batch number.

PACKAGING

750ml, 4Lt, 16Lt

PACKAGING	CODE	BARCODE
750ml	06023	5204094060239
4Lt	06036	5204094060215
16Lt	06022	5204094060222

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



Evochem®

EVOCHEM S.A.

Tzavardella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr

